



HP Clear Gloss Cast Overlaminates is the solution that lasts. Your prints will withstand the demanding conditions of outdoor display, from weather to cleaning, and the HP Performance Warranty covers you up to 5 years¹.

Ideal for customers using HP Air Release Adhesive Gloss Cast Vinyl, HP Clear Gloss Cast Overlaminates provides protection from UV radiation, enhances the durability of the underlying graphics and enables maximum flexibility.

Durable, long-term applications—like vehicle wraps—are built to last. HP Clear Gloss Cast Overlaminates provides protection from UV radiation, enhances the durability of the underlying graphics and enables maximum flexibility.

When you use HP Clear Gloss Cast Overlaminates, your prints withstand the demanding conditions of outdoor display from weather to cleaning and the HP Performance Warranty covers image performance, durability, and clean removal up to 5 years².

Use HP Clear Gloss Cast Overlaminates together with HP Air Release Adhesive Gloss Cast Vinyl. Air release channels make installation easy and prints leave behind little glue residue, so removal is clean and easy, even after 5 years.

¹When used with HP Air Release Adhesive Gloss Cast Vinyl, this solution comes with a new HP Performance Warranty. Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl.

²When used with HP Air Release Adhesive Gloss Cast Vinyl, this solution comes with a new HP Performance Warranty. Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl.

HP Clear Gloss Cast Overlamine

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	275 g/m ² per ISO 536 Test Method												
Thickness	3.2 mil/81.3 microns per ISO 534 Test Method												
Lamination	Yes (cold)												
Finish	Gloss												
Tensile strength	65.6 per ISO 1421 Test Method												
Adhesive backing	Acrylic adhesive												
Flame Retardant	No												
Waterfastness	Yes												
Shelf time	2 years, unopened in original packaging												
Storage temperature	10 to 35° C												
Storage humidity	30 to 70% RH												
Country of origin	Product of USA												
Ordering information	<table><thead><tr><th>Product Numbers</th><th>Roll sizes</th><th>UPC codes</th></tr></thead><tbody><tr><td>CH036A</td><td>1524 mm x 45.7 m</td><td>884962549292</td></tr><tr><td>CH037A</td><td>1372 mm x 45.7 m</td><td>884962549308</td></tr><tr><td>CH038A</td><td>1372 mm x 91.4 m</td><td>884962549315</td></tr></tbody></table>	Product Numbers	Roll sizes	UPC codes	CH036A	1524 mm x 45.7 m	884962549292	CH037A	1372 mm x 45.7 m	884962549308	CH038A	1372 mm x 91.4 m	884962549315
Product Numbers	Roll sizes	UPC codes											
CH036A	1524 mm x 45.7 m	884962549292											
CH037A	1372 mm x 45.7 m	884962549308											
CH038A	1372 mm x 91.4 m	884962549315											
Warranty	Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly.												

© 2009 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit
<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA0-1862 EEE

