



**HP White Satin Poster Paper produces durable prints with rich detail and brilliant colour that grabs attention indoors and outdoors. Versatility across inks helps you offer new applications.**

**Ideal for print service providers looking for a competitively priced, reliable substrate compatible across HP Latex, low-solvent, solvent, and UV-curable inks and ideal for short-run indoor/outdoor advertising campaigns and billboard applications.**

Offer indoor and outdoor campaigns produced on HP White Satin Poster Paper, manufactured according to ISO 14001, the voluntary international standard for environmental management systems.

Scratch-resistant prints dry quickly and stay intact after folding. Use water-resistant prints outdoors, without lamination<sup>1</sup>. HP White Satin Poster Paper delivers the easy, trouble-free printing you expect from HP.

Get attention-grabbing, vibrant colour, high-definition sharpness and brilliant colour saturation for indoor and outdoor campaigns, including billboards. Expand your applications with versatile HP White Satin Poster Paper.

<sup>1</sup> Image permanence and water-resistance ratings by HP Image Permanence Lab  
Outdoor display permanence tested according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change  
For more information, see [www.hp.com/go/supplies/printpermanence](http://www.hp.com/go/supplies/printpermanence).

# HP White Satin Poster Paper

## Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

For the latest ICC/media profiles, please visit [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies) (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

## Product specifications

| Weight   | 136 g/m <sup>2</sup> per ISO 536 Test Method  |                 |            |           |        |                |              |        |                |              |        |                |              |
|--|---|-----------------|------------|-----------|--------|----------------|--------------|--------|----------------|--------------|--------|----------------|--------------|
| Thickness  | 6.5 mil/165 microns per ISO 534 Test Method   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Opacity  | 95% per TAPPI T-425 Test Method   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Whiteness  | 110 per CIE Ganz 82 Test Method   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Lamination   | Yes, hot and cold   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Finish   | Satin   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Operating temperature                                    | 15 to 30° C   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Operating humidity                                       | 30 to 70% RH  |                 |            |           |        |                |              |        |                |              |        |                |              |
| Lightfastness (Archivability) Low-solvent Ink            | In test   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Lightfastness (Indoor Commercial Window) Low-solvent Ink | In test   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Lightfastness (Indoor Home or Office) Low-solvent Ink    | In test   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Flame Retardant  | No  |                 |            |           |        |                |              |        |                |              |        |                |              |
| Waterfastness  | Yes   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Shelf time   | 1 year, unopened in original packaging  |                 |            |           |        |                |              |        |                |              |        |                |              |
| Storage temperature                                      | 18 to 30° C   |                 |            |           |        |                |              |        |                |              |        |                |              |
| Storage humidity   | 35 to 55% RH  |                 |            |           |        |                |              |        |                |              |        |                |              |
| Country of origin  | Product of Germany  |                 |            |           |        |                |              |        |                |              |        |                |              |
| Ordering information                                     | <table><thead><tr><th>Product Numbers</th><th>Roll sizes</th><th>UPC codes</th></tr></thead><tbody><tr><td>CH001A</td><td>1372 mm x 61 m</td><td>884962282847</td></tr><tr><td>CH002A</td><td>1524 mm x 61 m</td><td>884962282854</td></tr><tr><td>CH010A</td><td>1067 mm x 61 m</td><td>884962372609</td></tr></tbody></table> | Product Numbers | Roll sizes | UPC codes | CH001A | 1372 mm x 61 m | 884962282847 | CH002A | 1524 mm x 61 m | 884962282854 | CH010A | 1067 mm x 61 m | 884962372609 |
| Product Numbers  | Roll sizes  | UPC codes       |            |           |        |                |              |        |                |              |        |                |              |
| CH001A   | 1372 mm x 61 m  | 884962282847    |            |           |        |                |              |        |                |              |        |                |              |
| CH002A   | 1524 mm x 61 m  | 884962282854    |            |           |        |                |              |        |                |              |        |                |              |
| CH010A   | 1067 mm x 61 m  | 884962372609    |            |           |        |                |              |        |                |              |        |                |              |
| Warranty   | Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly.   |                 |            |           |        |                |              |        |                |              |        |                |              |

© 2009 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-9432 EEE

