





For

HEALTH TEST REPORT

Shenzhen Yale Electronics Co,.Ltd

bluetooth headset

Additional Model No.: Please Refer to Page 5 上 LCS Testing Lat

Prepared for Address	 Shenzhen Yale Electronics Co, Ltd the 4th Floor, Building No.2, Yujingtai Industrial Park, Huaxing Road, Dalang, Longhua New District, Shenzhen, China
Prepared by Address Tel Fax Web Mail	 Shenzhen LCS Compliance Testing Laboratory Ltd. Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China (+86)755-82591330 (+86)755-82591332 www.LCS-cert.com webmaster@LCS-cert.com
Date of receipt of test sample Number of tested samples Serial number Date of Test Date of Report	 July 04, 2022 2 Prototype July 04, 2022 ~ July 11, 2022 July 12, 2022



Generic standard for assessme	HEALTH TEST REPORT I 62479: 2010 & EN 50663: 2017 ent of low power electronic and elec ictions for electromagnetic fields (10	
Report Reference No	Ç	,
Date of Issue	: July 12, 2022	
Festing Laboratory Name	: Shenzhen LCS Compliance T	esting Laboratory Ltd.
Address	: Room 101, 201, Building A and Industrial Park, Yabianxueziwei District, Shenzhen, Guangdong	, Shajing Street, Bao'an
	Full application of Harmonised	standards
Testing Location/ Procedure	 Partial application of Harmonise Other standard testing method 	
Applicant's Name	: Shenzhen Yale Electronics Co	o,.Ltd
Address	: the 4th Floor, Building No.2, Yu xing Road, Dalang, Longhua Ne	
Test Specification		
Standard	EN 62479: 2010 EN 50663: 2017	
Test Report Form No	: LCSEMC-1.0	
TRF Originator	: Shenzhen LCS Compliance Tes : Dated 2011-03	sting Laboratory Ltd.
This publication may be reprodu as the Shenzhen LCS Complian owner and source of the materia no responsibility for and will not	esting Laboratory Ltd. All rights in ced in whole or in part for non-com ce Testing Laboratory Ltd. is acknown il. Shenzhen LCS Compliance Test assume liability for damages result material due to its placement and o	mercial purposes as long owledged as copyright ting Laboratory Ltd. takes ing from the reader's
Test Item Description : blue	·	
Trade Mark: AW Test Model T1 F Ratings	El Pro	
Batt	tery: DC 3.7V, 35mAh ositive	
Compiled by:	Supervised by:	Approved by:
l la l'u	(any Luo	Jains Fiang

Page 2 of 8





HEALTH -- TEST REPORT

Test Report No. : LCSA063022020EC

July 12, 2022 Date of issue 讯检测股份

Test Model	: T1 Pro		
EUT	: bluetooth headset		
Applicant	: Shenzhen Yale Electror	nics Co,.Ltd	
Address		o.2, Yujingtai Industrial Park, onghua New District, Shenzhen,	
Telephone	: /		
Fax			
Manufacturer	: Shenzhen Yale Electror	nics Co,.Ltd	
	: the 4th Floor, Building No.2, Yujingtai Industrial Park, Huaxing Road, Dalang, Longhua New District, Shenzhen,		
	China		
Telephone			
Fax	:/**		
Factory	: Shenzhen Yale Electror	nics Co,.Ltd	
Address	: the 4th Floor, Building No.2, Yujingtai Industrial Park,		
	Huaxing Road, Dalang, L	onghua New District, Shenzhen,	
	China		
Telephone	:/		
Fax	:/		
台测股份	会测股份	一時期限份	
Test Result Positive		Positive	

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Revision History			
Report Version	Issue Date	Revision Content	Revised By
000	July 12, 2022	Initial Issue	





1. GENERAL INFORMATION

GENERAL INFORMATION	
1.1. Product Description for Equipment Under 1	ost (FUT)

EUT	: bluetooth headset
Test Model	: T1 Pro
Additional Model No.	: T50,T51,T52,T52 Pro,T53,T58,T60,T66,T65,T67,T68, T69,T70,T26 Pro,T13 Pro,T13,T15,T15P,T16,T28 Pro, T29 Pro,T29 ANC,T28,T28P,T29,T29P,T12,T12P,T12S, T11,T11P,T23,T35,T36,T55,T25
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	: For Earphone:Input:DC 5V, 60mA Battery: DC 3.7V, 35mAh
Hardware Version	: V1.0
Software Version	: V1.0
Bluetooth	:
Frequency Range	: 2402MHz ~ 2480MHz
Channel Number	: 79 channels for Bluetooth V5.3(BDR/EDR)
Channel Spacing	: 1MHz for Bluetooth V5.3(BDR/EDR)
Modulation Type	: GFSK, π/4-DQPSK for Bluetooth V5.3 (BDR/EDR)
Bluetooth Version	: V5.3
Antenna Description	: Internal Antenna, 1.2dBi(Max.)





1071 *





1.2. Objective

According to its specifications, the EUT must comply with the requirements of the following standards:

EN 62479: 2010 – Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz)

EN 50663: 2017 – Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz)

1.3. Test Methodology

All measurements contained in this report were conducted with EN 62479: 2010 and EN 50663: 2017.

1.4. Facilities

All measurement facilities used to collect the measurement data are located at Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.5. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
	ADAPTER	THX-120050KB		CE
Note: The adapter is supplied by leb and only use tested				

Note: The adapter is supplied by lab and only use tested.

1.6. External I/O Cable

I/O Port Description	Quantity	Cable
Power Port	LCS 1 Stur	N/A





1.7. Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

1.8. Laboratory Accreditations And Listings

Site Description	
EMC Lab.	: NVLAP Accreditation Code is 600167-0.
	FCC Designation Number is CN5024.
	CAB identifier is CN0071.
	CNAS Registration Number is L4595.
Name of Firm	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Site Location	: Room 101, 201, Building A and Room 301, Building C, Juji Industrial
	Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen,
	Guangdong, China
	/* ·

1.9. Measurement Uncertainty

Test Item		Uncertainty
Radio Frequency	:	0.9 x 10 ⁻⁴
Total RF Power, Conducted	:	1.0 dB
RF Power Density, Conducted	:	1.8 dB
Spurious Emissions, Conducted	:	1.8 dB
All Emissions, Radiated	S.	3.1 dB
Temperature		0.5°C
Humidity	:	1 %
DC And Low Frequency Voltages	:	1 %





2. HUMAN EXPOSURE TO THE ELECTROMAGNETIC FIELDS

2.1 Test Methodology

2.1.1.General description of applied standards

According to its specifications, the EUT must comply with the requirements of the following standards:

EN 62479- Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

EN 50663- Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz).

2.1.2.Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

2.2 Test limit

If the average power emitted by apparatus operating in the frequency range 10 MHz – 300G is less than or equal to 20 mW and the transmitting peak power is less than 20 W then the apparatus is deemed to comply with the basic restrictions without testing.

2.3 Test Results

Since Max.output power for Bluetooth is 0.69mW (-1.62dBm According to radio test report LCSA063022020EB) less than 20mW specified in EN 62479 and EN 50663. This unit will not generate the harmful EM emission above the reference level as specified in EC Council Recommendation (1999/519/EC).

The unit complies with the EN 62479 and EN 50663 for RF exposure requirement.

-THE END OF TEST REPORT-

No non-compliance noted.

