

HDBaseT

HDBaseT Receiver Box**HBT-6**

| | |
|------------------------|--|
| Video/Audio Input | HDBaseT RJ-45 x1 |
| Video/Audio Output | HDMI x1 |
| Supported Video Format | 3840x2160p: 30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 525i59.94 NTSC, 625i50 PAL |
| Video Process | 4K2K30 4:4:4 8bit 4K2K60 4:2:0 8bit |
| Video bandwidth | Single-link 340MHz [10.2Gbps] |
| DVIP | --- |
| RS-422/ RS-232 | YES |
| Power | DC IN: DC 48V |
| PoE Output | 30W |
| HDBaseT Distance | 1080p@60 60m (198ft) by CAT6 cable 4K2K@30 35m (114ft) by CAT6 cable |
| HDMI compliance | HDMI Deep Color, full 3D & 4K2K@30 |
| HDCP compliance | HDCP 2.2/1.4 |
| Audio support | Surround sound [up to 7.1ch) or stereo digital audio |
| Dimension (LxWxH) | 88 x 76 x 30 mm |
| Weight | 154 g |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HBT-6 main unit 1 x AC cord 1 x DC 48V power adaptor 2 x Screw |