

Dual 4K Output Module for CORIOmaster®

CM-HDMI-4K-SC-2OUT

OVERVIEW

The Dual HDMI scaled output module allows you to deliver a single 4K60 or dual independent outputs up to 4K30. A new cloning feature allows the second output to be used as a clone of output 1 and can be used up to and including 4K60.



Designed For

C3-540 CORIOmaster, C3-510 CORIOmaster mini, C3-503 CORIOmaster micro	Module installs in to any of the output slots
---	---

Max Installable

CORIOmaster	C3-540 CORIOmaster 14x C3-510 CORIOmaster mini 5x C3-503 CORIOmaster micro 2x
-------------	---

Constraints

None	Can be installed with other types of modules in the same system
------	---

SPECIFICATIONS

Output		Environmental		
Video	2x HDMI 2.0 connectors	Operating temp	0 °C to 40 °C (32 °F to 104 °F)	
Resolution Support	720x480i 59.94	Operating humidity	10% to 85% non-condensing	
	720x480p 59.94	Storage temp	-10° to +70° C (+14° to 158° F)	
	720x576i 50	Storage humidity	10% to 85% non-condensing	
	720x576p 50	Product item number		
	1280x720p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60	CM-HDMI-4K-SC-2OUT	Dual 4K scaled output module for CORIOmaster	
	1920x1080i 50, 59.94, 60	Associated products		
1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60	C3-540 CORIOmaster	4RU chassis		
3840x2160p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60	C3-510 CORIOmaster mini	1RU chassis		
Compatibility	HDMI 2.0 and HDCP 1.4	C3-503 CORIOmaster micro	1RU ½ width chassis	
Color space	BT.601 on standard resolutions BT.709 for HD and UHD	Specifications subject to change without notification		
Warranty	Limited warranty: 5 years parts and labor			
Regulatory compliance	FCC, CE, RoHS, UL			
Mechanical				
Size (H x W x D)	21 x 96 x 170 mm (0.9" x 3.9" x 6.8")			
Weight (Net)	160 g (5 oz)			