



Mid to Large Meeting Room Laser Projector with Excellent ROI

FEATURES

- DLP® technology for vibrant and rich picture quality
- Impressive 9,000 ANSI lumens of brightness, WUXGA resolution, and 20,000:1 contrast ratio for clear, crisp and bright projection
- Long lasting laser light source for constant brightness level and color performance for up to 20,000 hours operations
- Exquisitely vivid colors and natural picture with Rec. 709 color space capacity and HDR support
- Robustic operations thanks to its advanced thermal cooling technology and sealed optical engine
- Installation flexibility is ensured with 7 optional lenses and easy image adjustment
- Loud and clear sound delivered by built-in 2x10W speakers
- Simple one-cable connection thanks to HDBaseT with up to 4K-UHD signal support
- DICOM Simulation Mode for medical training and seminars
- Full compatibility with NovoConnect Solution for wireless presentation and collaboration



Powerful laser projector for corporate

A smart choice for mid to large corporate meeting rooms thanks to its low total cost of ownership, the DU7295Z laser projector packs tremendous value for companies seeking maintenance-free durability up to 20,000 hours with easy installation and management. DU7295Z ensures superior visibility with 9,000 ANSI lumen brightness and vibrant true-to-life colors with Rec. 709 color space, along with exceptionally quiet 33dB operation. Furthermore, the DU7295Z can be complemented with Vivitek's NovoConnect Solution for wireless presentation and collaboration.



DU7295Z

SPECIFICATIONS

| | | |
|---------------|----------------------------------|---|
| Image | Display Type | Single chip DLP® Technology by Texas Instruments |
| | Brightness | 9000 ANSI Lumens |
| | Native Resolution | WUXGA (1920 x 1200) |
| | Max. Supported Resolution | 4K-UHD (3840 x 2160) @60Hz |
| | Contrast Ratio | 20,000:1 |
| | Native Aspect Ratio | 16:10 |
| | Keystone Correction | Vertical +/-30°; Horizontal +/-25° |
| Optical | Throw Ratio | 7 optional lenses from 0.78:1 to 3.0-5.0:1 throw ratio range |
| | Zoom Ratio | Manual Zoom & Focus |
| | Offset | Manual Lens Shift |
| | Lens Shift Range | Manual; Vertical +55%, -15%; Horizontal +/-5% |
| Features | Features | 3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock |
| Compatibility | Video | SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L), 4K-UHD |
| Connectivity | I/O Connection Ports | VGA-In (15pin D-Sub), HDMI Number of Ports v.2.0 (x2), DVI-D, Component (5 BNC) (RGBHV) , Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (RCA), RJ45 (x2: LANx1, HDBaseTx1), RS-232 (x2: In and Out), 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote) |
| General | Lamp Life and Type | Lamp free design. Laser light source lasts up to 20,000 hours |
| | Dimensions (W x D x H) | 470 x 517 x 202 mm |
| | Weight | 25 kg |
| | Noise Level | 40dB/36dB (Normal/Eco. Mode) |
| | Warranty | Large Venue Laser Phosphor Warranty: 5 Year projector / 5 years or 20.000h on the Laser Phosphor illumination source.(Whichever comes first) |
| | Standard Accessories | VGA Cable, Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord |
| | Optional Accessories | Remote Control P/N (5041846600) |
| | UPC Code | DU7295Z-WH: 813097024459; DU7295Z-BK: 813097024541 |

OPTIONAL LENSES

| Lens Name | Short Throw | Semi Short Throw | Standard Lens | Wide Fix | Wide Zoom | Long Zoom 1 | Long Zoom 2 |
|----------------------------|-------------------------------------|--------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|------------------------------|
| Aspect Ratio | 16:10 | 16:10 | 16:10 | 16:10 | 16:10 | 16:10 | 16:10 |
| Throw Ratio | 1.10 - 1.30:1 | 1.25 - 1.60:1 | 1.54 - 1.93:1 | 0.78:1 | 0.77 - 1.10:1 | 1.93 - 2.89:1 | 3.00 - 5.01:1 |
| Projection Distance | 1-9 | 1.3-8 | 1.5-7 | 0.8-5 | 1-5 | 2-20 | 3-20 |
| Image Size | 36-379 | 39-300 | 37-211 | 48-298 | 43-300 | 33-481 | 28-309 |
| Zoom | 1.18 | 1.28 | 1.25 | 1 | 1.42 | 2.5 - 3.1 | 1.67 |
| F Number | 2.05 - 2.27 | 2.0 - 2.44 | 2.0 - 2.09 | 2.5 | 2.1 - 2.6 | 28.5 - 42.75 mm | 2.2 - 2.5 |
| Focal Length | 16.64 - 19.54 mm | 18.65 - 23.85 mm | 22.8 - 28.5 mm | 11.46 mm | 11.45 - 16.32 mm | 44.5 - 74.19 mm | 44.5 - 74.19 mm |
| Part Number | 5811120054-SVV (VL907G/LNS-5STZ) | 5811122743-SVV (VL912G/LNS-5SZ12) | 5811120865-SVV (VL906G/LNS-7SZ1) | 5811120818-SVV (VL904G/LNS-5FX2) | 5811122742-SVV (VL911G/LNS-5WZ2) | 5811119237-SVV (VL908G/LNS-7LZ1) | 5811120055-SVV (LNS-5LZ2) |