



16-Device USB Charging Station Cabinet with Sync for iPad and Android Tablets, Wall-Mount and Cart Options, 230V, BS1363 to C13 Plug, Black

MODEL NUMBER: CSCXB16USB











Provides 2.4A USB charging, syncing, secure storage and cord management for up to 16 tablets and other devices.

Features

Charges, Syncs, Secures and Organizes Up to 16 Tablets and Other USB Devices

This charging cabinet provides fast charging, convenient syncing, secure storage and cord management for up to 16 iPad, Android, Surface and Kindle tablets, as well as smartphones and other USB devices. Ideal for education, office, commercial, retail, industrial and healthcare environments, this locking steel cabinet with a black powder-coated finish keeps valuable mobile devices safe, secure and always ready to use.

Fast Charging and Convenient Syncing

The CSCXB16USB features 16 USB ports capable of delivering the fastest charging supported by each device, up to 2.4A per port. A USB uplink port connects to a host computer for wired syncing, though the CSCXB16USB also supports wireless syncing and simultaneous syncing/charging (up to 1.5A per port during wired syncing). The 3.7-meter (12-foot) AC input cord with BS1363-to-C13 plug reaches distant outlets to help you place the cart in a convenient location.

Comprehensive Protection Against Theft, Tampering, Overheating and Abrasions

The CSCXB16USB locks with the included keys to help protect devices from theft, damage or tampering. A three-point locking mechanism latches doors at the top, middle and bottom. For extra security, you can replace or supplement the built-in lock with your own padlock, and rear ports accommodate an optional cable or chain lock to secure the entire unit in place. Flow-through ventilation prevents devices from overheating. The protective shelf is specially coated to prevent device scratches and scuffs, and the cord access ports include rubber grommets to protect against abrasions. A solid top doubles as a work surface and helps prevent accidental drips and spills from damaging devices.

Clutter-Reducing Organization

USB ports and charging cords are carefully stored out of sight. A front trim panel easily removes without tools to permit quick service access. Each device has its own charging cord access port.

Flexible Configuration

The CSCXB16USB ships fully assembled for quick installation on a desktop or floor in a structurally sound area or wall mounting with user-supplied tools and hardware. You can also convert it to a mobile cart with the optional CSHANDLEKIT2 (sold separately), and roll it where needed. The split front doors open 180

Highlights

- Secures up to 16 mobile devices behind locking doors to help prevent tampering
- 230V cabinet features 3.7 m cord with BS1363-to-C13 plug for reaching distant outlets
- Removable dividers accommodate thicker devices such as battery chargers
- Supports wall mounting or desktop/floor placement in a structurally sound area
- Ships fully assembled for immediate placement in an office, classroom, etc.

Package Includes

- CSCXB16USB 16-Device USB Charging Station Cabinet, Black
- (2) Keys
- Owner's manual





degrees for improved device and service access. You can remove the shelf dividers to fit thicker devices, such as battery chargers, and a firmware upgrade port allows future updates.

Specifications

OVERVIEW		
OVERVIEW UPC Code	037332285010	
Charging Form Factor	Stationary Cabinet	
Product Type	Multi-Device Charger	
Charger Functions	Charge; Secure; Sync	
Device Compatibility	Tablet	
Device Slots	16	
Device diots		
INPUT		
Nominal Input Voltage(s) Supported	230V AC	
Voltage Compatibility (VAC)	230	
Input Frequency	50Hz	
Input Plug Type	BS1363	
Input Cord Length (ft.)	12	
Input Cord Length (m)	3.66	
POWER		
Power Consumption (Watts)	56.00	
CHARGING		
Number of Charging Ports	16	
Total Charging Amps	40	
Total Charging Watts	200	
Charging Method	USB	
Charging Port Type	USB A (FEMALE)	
Charging Ports Details	Pass through	
Charging Ports / Amps	(16) 2.4A	
Overcharge Protection	Yes	
Charging Amps per Port	2.4A	
PHYSICAL		
Color	Black	
Material of Construction	Steel	
ł		





Charging Station Form Factor	Stationary Cabinet	
Unit Dimensions (hwd / in.)	18.800 x 30.330 x 20.200	
Unit Weight (lbs.)	85.98	
Unit Weight (kg)	39.00	
Number of Shelves	1	
ENVIRONMENTAL		
Operating Temperature Range	32° to 86°F (0° to 30°C)	
Storage Temperature Range	5° to 122°F (-15° to 50°C)	
Relative Humidity	5% TO 95% RH (NON CONDENSING)	
Operating Humidity Range	5% TO 95% RH (NON CONDENSING)	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
Cord Management	Yes	
Overcurrent Protection	Yes	
EMI/RFI Line Noise Protection	Yes	
Flow-Through Ventilation	Yes	
IP68 Rated	No	
IP20 Rated	No	
UV Sterilization	No	
Locking	Yes	
Lock Type	Key	
LED Lights	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 62368-1 (Canada); UL 62368-1	
Product Compliance	CE (Europe); RoHS; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	2-year limited warranty	
CATEGORY PAGE FILTERS (Y/N ONLY)		
External Receptacle	No	





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.