





## Specifications

- **Module Dimensions (L x W x H):** 136mm x 76mm x 45mm (without faceplate)
- **Faceplate Dimensions (L x W x H):** 146mm x 86mm x 5mm
- **Cut Out Dimensions (L x W x H):** 109mm x 50mm x 36mm
- **Mounting hole spacing:** UK 121mm CTC, EU 60mm CTC
- **Backbox Requirements:** UK double gang backbox / EU double gang backbox
- **Shipping Weight:** 0.6kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature:** -4°F to 140°F (-20°C to 60°C)
- **Power Supply:** Class 1 IEEE 802.3af PoE or 12v/1A DC 2-Pin Phoenix connector

## Included Accessories

<b>Faceplate</b>	1 x Magnetic Faceplate
------------------	------------------------

## Connectivity

- **Audio Input Connectors:** 2 x Analogue balanced / unbalanced 3-Pin XLR connector
- **Audio Output Connectors:** 2 x Analogue balanced / unbalanced 3-Pin XLR connector
- **Network Connectors:** 1 x PoE Dante® Ethernet connection (RJ45)
- **Configuration Switches:** 4 x 5 position rotary dials (Sensitivity / Gain), 2 x Push button (48V Phantom power)
- **Firmware Upgrade:** 1 x Micro-USB

## Acknowledgements

Dante® is a registered trademark of Audinate Pty Ltd.

## Regulatory Compliance



Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.