

# MAKE IT MINI



The V SFX Gold delivers the high quality experience you've come to expect from the V series in SFX form factor. Enjoy the same great features with fully support ATX3.0, 80 Plus Gold efficiency, full-modular cabling, an FDB fan, 16AWG PCIe high efficiency cables, and a 10 year warranty. But now you can have it in a mini-ITX case. With the V SFX Gold, the V series is now viable for cases ranging from mini-ITX all the way up through E-ATX systems. And with the included bracket this unit is compatible with all of them.

### **FEATURES**

**SFX Form Factor :** This unit is compatible with all SFX cases and suitable for mini-ITX system builds.

**SFX-to-ATX Bracket :** The included bracket allows users to install this unit securely in traditional ATX cases.

**80 PLUS Gold Certified :** This certification guarantees a typical efficiency of 90% under normal operating conditions.

Fully support ATX3.0 : Fully support ATX3.0 with Peak power 200% & 300W output 12VHPWR native cable.

**Full-Modular Cabling :** Modular cables reduce clutter, increase airflow, and improve overall efficiency and thermal performance.

**10 Year Warranty :** This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.

#### PACKAGE INFORMATION

Cable Type	EAN	UPC
MPY-7501-SFHAGV-3US	4719512134559	884102106873
MPY-7501-SFHAGV-3UK	4719512134566	884102106880
MPY-7501-SFHAGV-3EU	4719512134573	884102106897
MPY-7501-SFHAGV-3ST	4719512134580	884102106903
MPY-7501-SFHAGV-3AU	4719512134597	884102106910
MPY-7501-SFHAGV-3BR	4719512134603	884102106927
MPY-7501-SFHAGV-3KR	4719512134610	884102106934
MPY-7501-SFHAGV-3TW	4719512134627	884102106941
MPY-7501-SFHAGV-3JP	4719512134634	884102106958
MPY-7501-SFHAGV-3IN	4719512134641	884102106965
MPY-7501-SFHAGV-3WO	4719512134658	884102106972

Nett Weight	1.42 kg
Gross Weight	1.86 kg
Package Dimensions	260 x 190 x 100mm (10.24 x 7.48 x 3.94")
Carton Dimensions	520 x 275 x 215mm (20.47 x 10.83 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	24 pcs

## **SPECIFICATIONS**

Product Name		V750 SFX Gold ATX3.0		
Item Code		MPY-7501-SFHAGV		
ATX Version		ATX3.0 & SFX 12V Ver. 3.42		
PFC		Active PFC		
Input Voltage		100-240V		
Input Current		10-5A		
Input Frequency		50-60Hz		
Dimensions (L x W x H)		100 x 125 x 63.5mm		
Fan Size		92mm		
Fan Bearing		FDB		
Efficiency		90% @ Typical Load		
80 PLUS Rating		80 PLUS Gold		
ErP 2014 Lot 3		Yes		
Operating Tem	perature	0~50°C		
Power Good Signal		100-500ms		
Hold Up Time		16ms		
MTBF		>100,000 hours		
Protections		OVP / OPP / SCP / OCP / UVP / OTP / Surge and Inrush Protection		
Regulatory		TUV, cTUVus, CE, BSMI, FCC, CCC, EAC, RCM, CB, UKCA		
Connectors	ATX 24 Pin	x1 = 1x (300mm)		
	EPS 4+4 Pin	x1 = 1x (450mm)		
	EPS 8 Pin	x1 = 1x (450mm)		
	SATA	x8 = 2x (100+115+115+115mm)		
	Peripheral 4 Pin	x4 = 1x (100+115+115+115mm)		
	PCI-e 6+2 Pin	x4 = 2x (400+120mm)		
	12VHPWR	x1 = 1x (650mm)		

AC INPUT	100-240V~, 10-5A, 50~60Hz					
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb	
	20A	20A	62.5A	0.3A	3A	
TOTAL POWER	120W		750W	3.6W	15W	
	750W					



# **FEATURES**








SFX Form Factor

SFX-to-ATX Bracket

80 PLUS Gold Certified







Quiet FDB Fan

Full-Modular Cabling

10 Year Warranty

