



LCD DISPLAY

# VX3480-2K-PRO

## Key Features

- Ultrawide expansive display
- Experience fluid gameplay with the blazing-fast 165Hz refresh rate
- Swift 1ms MPRT ensures razor-sharp visuals in fast-paced gaming
- AMD FreeSync™ Premium technology eliminates screen tearing and reduces stuttering
- HDR10 delivers stellar contrast and color accuracy



## Product Description

Engineered for truly expansive visuals, the ViewSonic VX3480-2K-PRO features a stunning, 34" ultrawide display. With a rapid 165Hz refresh rate and 1ms MPRT response time, games are rendered with smooth, blur-free visuals. The ultrawide 21:9 aspect provides an immersive experience for both productivity and gameplay. Variable refresh rate technology synchronizes your monitor and GPU outputs, virtually eliminating tearing and stuttering during your gameplay. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

**Visit Us**[www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Display Size (in.):	34
Viewable Area (in.):	34
Panel Type:	VA Technology
Resolution:	3440 x 1440
Resolution Type:	UWQHD (UltraWide QHD)
Static Contrast Ratio:	4,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	300 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	21:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	165
Variable Refresh Rate Technology:	FreeSync Premium
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 90% size (Typ) sRGB: 128% size (Typ)
Pixel Size:	0.232 mm (H) x 0.232 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	3440x1440
Mac® Resolution (max):	3440x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3440x1440

**CONNECTOR**

USB 2.0 Type A:	1
3.5mm Audio Out:	1
HDMI 2.0:	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

**POWER**

Eco Mode (Conserve):	24W
Eco Mode (optimized):	32W
Consumption (typical):	43W
Consumption (max):	45W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

**ADDITIONAL HARDWARE****CONTROLS**

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	HDMI (v2.0): 24 ~ 150KHz, DisplayPort (v1.4): 30 ~ 254KHz
Frequency Vertical:	HDMI (v2.0): 48 ~ 100Hz, DisplayPort (v1.4): 48 ~ 165Hz

**VIDEO INPUT**

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

**ERGONOMICS**

Height Adjust (mm):	140
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°

**WEIGHT (IMPERIAL)**

Net (lbs):	15.6
Net Without Stand (lbs):	11.3
Gross (lbs):	21.5

**WEIGHT (METRIC)**

Net (kg):	7.1
Net Without Stand (kg):	5.1
Gross (kg):	9.8

**DIMENSIONS (IMPERIAL) (WXHxD)**

Packaging (in.):	36.7 x 19.6 x 8.4
Physical (in.):	32.06 x 18.82~22.99 x 10.41
Physical Without Stand (in.):	32.06 x 14.02 x 1.64

**DIMENSIONS (METRIC) (WXHxD)**

Packaging (mm):	933 x 498 x 213
Physical (mm):	814.2 x 478.11~584.02 x 264.33
Physical Without Stand (mm):	814.2 x 356.01 x 41.72

**GENERAL**

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, CCC, China RoHS, China Energy Label
--------------	--

PACKAGE CONTENTS:	VX3480-2K-PRO x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local,
-------------------	---



Kensington Lock Slot: 1

state or federal laws.

Warranty:

\*Warranty offered may differ from market to market

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

