

**AVer**



**SUPERIOR  
PRO AV  
TRACKING**

**AVer TR315**

AI Auto Tracking PTZ Camera



AVer's new TR315 AI Auto Tracking PTZ Camera extends powerful and dependable Pro AV prowess to users across the spectrum of industries. The TR315 showcases proprietary functions – including Presenter Mode, Zone Mode, and Hybrid Mode tracking – driven by advanced AI processing. Seamlessly blending a 12X Optical Zoom lens, 4K 60 fps resolution, and the finesse of hybrid auto tracking and smooth PTZ operations, it's already the quintessential choice for broadcasting, streaming, or recording.



4K Ultra HD Resolution



12X Optical Zoom



IP/HDMI/USB/3G-SDI



Intuitive Web UI



5-Year Warranty



Human Detection AI



Presenter Mode



Zone Mode



Hybrid Mode



Voice Tracking\*

\* Voice Tracking requires PTZ Link.

## 12X Optical Zoom Magnifies Details

Experience the exceptional power of the TR315 camera's astounding 12X optical zoom. This feature seamlessly operates even while the camera is panning and tilting, granting you the ability to accentuate content and quickly shift between shooting perspectives. Embrace the advantage of dynamic, crystal-clear video feeds through the TR315's unparalleled PTZ performance.



## HDMI/USB/IP. 4K 60 FPS.

Leverage the TR315's 4K 60 fps streaming potential through HDMI, USB, and IP outputs. Free from intricate configurations and cable entanglements, you can effortlessly use multiple devices simultaneously to produce fluid video streams.



## AI Auto Tracking Makes Streaming Smart & Effortless

Powered by highly precise processing, AVer's cutting-edge AI Auto Tracking algorithms easily identify and capture human figures and moving objects. You'll never lose track of your target again with the TR315's unmatched tracking precision.



## Presenter Mode

Get unparalleled tracking performance with Presenter Mode. This dynamic feature empowers presenters to venture beyond the stage to engage with their audience while the camera maintains seamless tracking.



## Zone Mode

Zone Mode elevates your ability to capture content across multiple displays. Generate up to four dedicated Content Zones to consistently capture displayed information or items, prioritizing important presentation materials over the presenter's movements.



## Hybrid Mode

Free your performers by enabling unrestricted movement with Hybrid Mode. Use preset areas for zone tracking, letting the camera seamlessly switch to a full view of each pre-defined location as performers move through the areas. If they move beyond these zones, the camera seamlessly adapts, switching to presenter mode to effortlessly and precisely track their movements.



# Product Specifications

Part no. 61S912000AD  
EAN code 4719552127849

Camera		General		
Image Sensor	1/2.8" 4K Exmor CMOS	Power Requirement	AC 100 - 240V to DC 12V/5A	
Effective Picture Elements	8 Megapixels	Power Consumption	18W	
Output Resolutions	4K/60, 4K/59.94, 4K/50, 4K/30, 4K/29.97, 4K/25, 1080p/60, 1080p/59.94, 1080p/50, 1080p/30, 1080p/29.97, 1080p/25, 1080i/60, 1080i/59.94, 1080i/50, 720p/60, 720p/59.94, 720p/50	PoE	PoE+	
		Dimensions (W x H x D)	180.0 x 192.0 x 145.0 mm	
		Net Weight	2.0 (±0.1) kg	
Minimum Illumination	0.46 lux (IRE50, F1.6, 30fps)	Application	Indoor	
S/N Ratio	≥ 50 dB	Tally Lamp	Yes	
Gain	Auto, Manual	Security	Kensington Slot	
TV Line	1600 (Center)	Remote Control	Infrared	
Shutter Speed	1/1 to 1/32,000 sec	Operating Conditions	Temperature : 0 °C to +40 °C ; Humidity : 20% to 80%	
Exposure Control	Auto, Manual, Priority AE (Shutter, IRIS), BLC, WDR	Storage Conditions	Temperature : -20 °C to +60 °C ; Humidity: 20% to 95%	
White Balance	Auto, Manual	IP Streaming		
Optical Zoom	12X	Resolution	2160p 60fps	
Digital Zoom	1X	Network Video Compress Formats	H.264, H.265, MJPEG	
Viewing Angles	DFOV : 80.6° (Wide) to 7.7° (Tele) HFOV : 72.8° (Wide) to 6.7° (Tele) VFOV : 44.1° (Wide) to 3.8° (Tele)	Network Audio Compress Formats	AAC-LC (48K), PCM (8K)	
		Maximum Frame Rate	2160p 60fps	
		Bit-Rate Control Modes	VBR, CBR (selectable)	
Focal Length	f = 3.9 mm (Wide) to 46.8 mm (Tele)	Range of Bit-Rate Setting	512 Kbps to 32 Mbps	
Aperture (Iris)	F = 1.6 (Wide) to 2.8 (Tele)	Network Interface	10 / 100 / 1000 Base-T	
Minimum Working Distance	0.3 m (Wide), 1.5 m (Tele)	Multi-Stream Capability	4 4K 60fps: RTSP, HDMI & USB 1080p 60fps: 3G-SDI	
Pan / Tilt Angles	Pan : ±170°, Tilt : +90° / -30°		Network Protocols	IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, DHCP, RTP / RTCP, RTSP, RTMP, SRT, HLS, NDI, LLDP, VISCA over IP
Pan / Tilt Speed (Manual)	Pan : 0.1° to 100° / sec, Tilt : 0.1° to 100° / sec			NDI® HX3
Preset Speed	Pan : 200° / sec, Tilt : 200° / sec	USB		
Preset Positions	10 (IR), 256 (RS-232 / RS-422 / IP)	Connector	USB 3.1	
Camera Control - Interface	RS-232 (DIN8), RS-422 (RJ45), IP, USB	Video Format	MJPEG, YUY2	
Camera Control - Protocols	VISCA (RS-232 / RS-422 / IP), PELCO-D & PELCO-P (RS-232 / RS-422), CGI (IP), USB, ONVIF	Audio Format	PCM	
Image Processing	Noise Reduction (2D / 3D), Flip, Mirror, WDR, BLC	Maximum Video Resolution	2160p	
Power Frequencies	50 Hz, 60 Hz	USB Video Class (UVC)	UVC 1.1	
AI Auto Tracking Functions		USB Audio Class (UAC)	UAC 1.0	
Tracking Modes	Presenter Mode, Zone Mode, Hybrid Mode	Web UI		
Privacy Protection Mechanisms		Live Video Preview	Yes	
Protection Mode	Sleep Mode	Camera PTZ Control	Pan, Tilt, Zoom, Focus, Preset Control	
AI Control Functions		Camera/Image Adjustment	Exposure, White Balance, Picture	
Gesture Control	Yes	Network Configuration	DHCP, IP Address, Gateway, Subnet Mask, DNS	
Audio		Software Tools		
Channel	2ch Stereo	IP Search and Configuration Tool	Support Windows® 7 or later	
Codec	AAC-LC (48K), PCM (8K)	PTZ Management	Support Windows® 7 or later	
Sample Rates	48 / 44.1 / 32 / 24 / 16 / 8 KHz	PTZ Control Panel	Supports iOS & iPadOS® 9 or later	
Interface		PTZ Link	Supports Windows® 7 or later, macOS® 10.14 or later	
Video Outputs	3G-SDI, HDMI, IP, USB	OBS Plugin for PTZ Cameras	Supports Windows® 8 or later, macOS® High Sierra v10.13 or later	
Audio Outputs	3G-SDI, HDMI, IP, USB	CaptureShare	Supports Windows® 7 or later, macOS® 10.14 or later	
Audio Inputs	Mic in, Line in			
Warranty				
Camera	5 Years			
Accessories	1 Year			
Package Contents				
	Camera, Remote Control, RS-232 In/Out Cable, Din 8 To D-Sub 9 Cable, Power Adapter, Power Cord, Cable Ties (x4), M2 x 4 mm Screws (x3), M3 x 6 mm Screws (x3), 1/4"-20L 6.5mm Screws (x2), Cable Fixing Plate, Ceiling Mount Brackets (x2), Drilling Paper, Quick Start Guide			
Optional Accessories				
	AVER CL01 PTZ Camera Controller, L-Type Wall Mount			

\* Specifications may vary depending on location and are subject to change without notice.

\* Specifications may vary depending on location and are subject to change without notice.

## Product Appearance

Front



Back



©2023 AVer Information Inc. All rights reserved.  
All brand names and logos are trademarks of their respective companies.

www.aver.com



Learn More

Distributor/Dealer

202312