

Product datasheet

Specifications



APC Back-UPS, 1050VA/600W
Floor/Wall Mount, 230V, 8x British
BS1363A outlets, USB Type A+C
Port, User Replaceable Battery

BE1050G2-UK

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	600 W
Rated power in VA	1050 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	BS1363A British
output connection type	6 BS 1363 2 BS 1363 surge
Battery type	Lead-acid battery
Provided equipment	User manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery charger power	6 W rated
Battery power in VAh	93 VAh runtime
Battery life	2...5 year(s)
Extended runtime	0

General

Number of power module free slots	0
Number of power module filled slots	0

Redundant	No
-----------	----

Physical

Colour	Black
--------	-------

Height	12 cm
--------	-------

Width	13 cm
-------	-------

Depth	36.5 cm
-------	---------

Net weight	4.6 kg
------------	--------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	Yes
----------------	-----

Input

Network frequency	47...63 Hz
-------------------	------------

Input voltage limits	180...266 V
----------------------	-------------

Maximum input current	6 A
-----------------------	-----

Switching current capacity	10 A
----------------------------	------

Output

Maximum configurable power in W	600 W
---------------------------------	-------

Output frequency	47...63 Hz 50/60 Hz +/- 1 Hz sync to mains Unsynchronised
------------------	---

UPS type	Standby
----------	---------

Wave type	Stepped approximation to a sinewave
-----------	-------------------------------------

Efficiency	80 % (full load)
------------	------------------

Graph start point	40
-------------------	----

Maximum configurable power in VA	1050 VA
----------------------------------	---------

Transfer time	6 ms typical : 10 ms maximum
---------------	------------------------------

Conformance

Product certifications	CE EAC
------------------------	-----------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Equipment protection policy	Lifetime : 100000 euros
-----------------------------	-------------------------

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...90 %
-------------------	----------

Operating altitude	0...3000 ft
--------------------	-------------

Ambient air temperature for storage	-15...45 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...4572.0000000000 m
Acoustic level	45 dBA

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators

Surge Protection and Filtering

Surge energy rate	310 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19 cm
Package 1 Width	44.1 cm
Package 1 Length	18.6 cm
Package 1 Weight	4.4 kg
SCC14	10731304738302

Logistical informations

Country of origin	PH
-------------------	----

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

 **Rohs Exemption Information** [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)