

Key Features

- 6,000 ANSI Lumens offering bright images in any environment
- Up to a 180" ultra-large screen with a lower cost-perinch
- 0.44 short throw for seamless viewing experience without shadows
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams
 Rooms
- Installation flexibility: H/V keystone correction, 360° projection, and warping



Product **Description**

The LSC601WU-ST is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 2nd generation laser phosphor technology, this projector delivers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can display an ultra-large screen up to 180" in WUXGA resolution. With a 0.44 short throw ratio, it can project a 100" image from just 0.95 m away, enabling a seamless viewing experience without shadows. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V keystone correction, 360° projection, and warping capabilities, the LSC601WU-ST offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

- 1. Front IR
- 2. Service
- 3. USB-A (5V/2A)
- 4. HDMI x2
- 5. Computer
- 6. Monitor Out 7. RS232
- 8. Audio Out
- 9. Audio In
- 10. RJ45 11. Rear IR
- 12. HDBaseT
- 13. AC In
- 14. LED Indicator
- 15. Keypad
- 16. Focus Ring
- 17. Power Button

Visit Us

www.viewsonic.com



SPECIFICATION		OTHERS	
Native Resolution:	1920x1200	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz
Brightness:	6000 (ANSI Lumens)	11,7	(AC in)
Brightness (Center Lumens):	6500	Power Consumption:	Normal: 345W, Standby: <0.5W
Contrast Ratio:	3000000:1	Operating Temperature:	0~40°C
Display Color:	1.07 Billion Colors	Carton:	Brown
Light Source Type:	Laser Phosphor	Net Weight:	8.0kg
Light Source Life (hours) with Normal Mode:	20000	Gross Weight:	11.03kg
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Dimensions (WxDxH) with Adjustment Foot:	405x404x164mm
Lens:	F=1.6 f=6.39mm	Packing Dimensions:	510x498x260mm
Projection Offset:	98%+/-5%	OSD Language:	English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi, total
Throw Ratio:	0.44		
Optical Zoom:	Fixed		
Digital Zoom:	1.0x-4.0x		
Image Size:	55"- 180"		
Throw Distance:	0.521-1.71m (100"@0.948m)	25 languages English, S-Chinese, T-	
Keystone:	H:+/-15° , V:+/-15°	User Guide Language:	Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Audible Noise (Normal):	35dB		
Audible Noise (Eco):	25dB		
Input Lag:	60ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	STANDARD ACCESSORY	iaiiguages
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	Power Cord:	1
Horizontal Frequency:	15K-100KHz	Remote Control:	1
Vertical Scan Rate:	23-85Hz	QSG:	Yes
INPUT		Air Filter:	Yes
Computer in (share with	1	Warranty Card:	Yes (CN Only)
component):	· ·	OPTIONAL ACCESSORY Air Filter:	Yes
AV in (3.5mm):	1	Wall/Ceiling Mount:	PJ-WMK-007
HDMI:	2 (HDMI 1.4/ HDCP 1.4)	waii/Ceiling Mount.	F3-WWK-007
USB Type A:	1 (5V/2A)		
HDBaseT:	1		
OUTPUT			
Monitor out:	1		
Audio-out (3.5mm):	1		
Speaker:	16W		
USB Type A (Power):	1 (USB2.0 - 5V/2A, share with USB A Input)		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		



USB Type B (Services):