




# HP Permanent Gloss Adhesive Vinyl



## The HP large format printing system—the complete solution

HP Latex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



## Choose this REACH compliant,<sup>1</sup> economical vinyl

### Grab attention with bright, vibrant image quality

Capture vibrant graphic detail, display brilliant color. From event signage to retail displays, achieve a high-quality look with this versatile, easy-to-handle, quick-mount self-adhesive vinyl—ideal for a wide range of indoor and outdoor applications.

### Count on lasting, durable results

Depend on lasting results. Prints achieve 3 years un laminated display permanence outdoors;<sup>2</sup> 5 years in-window.<sup>3</sup> You get optimal results—including weather-resistance without additional lamination—using HP Latex Inks.

### Differentiate with environmental certification

Offer a vinyl that complies with high health standards. HP Permanent Gloss Adhesive Vinyl is REACH compliant<sup>1</sup>—a regulation of the European Union adopted to improve the protection of human health and the environment.

<sup>1</sup> This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at [HP.Printing.Products.and.Consumable.Supplies](http://HP.Printing.Products.and.Consumable.Supplies).

<sup>2</sup> With HP Latex Inks. HP image permanence and scratch, smudge, and water resistance estimates by HP Image Permanence Lab on a range of media including HP printing materials. For more information, see [globalBMG.com/hp/printpermanence](http://globalBMG.com/hp/printpermanence).

<sup>3</sup> With HP Latex Inks. Interior in-window display ratings by HP Image Permanence Lab on a range of media including HP printing materials. For more information, see [globalBMG.com/hp/printpermanence](http://globalBMG.com/hp/printpermanence).

Target customers	Applications	Benefits
Print service providers	Trade show and event displays	Vibrant graphic detail
	Signage	Brilliant color
	POP and retail displays	Gloss finish
		Highly opaque for a high-quality look
		Easy to handle and mount
		Outdoor display permanence 3 years un laminated, up to 5 years laminated <sup>2</sup>
		Indoor, in-window display permanence 5 years un laminated, up to 10 years laminated <sup>3</sup>
		Permanent adhesive
		Provides reassurance with REACH compliance <sup>1</sup>

## Technical specifications



### HP Permanent Gloss Adhesive Vinyl

For the latest ICC profiles/paper presets, please visit [globalBMG.com/hp/paperpresets](http://globalBMG.com/hp/paperpresets).

<b>Weight (Without liner)</b>	150 g/m <sup>2</sup> per ISO 536 Test Method																																
<b>Weight (With liner)</b>	270 g/m <sup>2</sup> per ISO 536 Test Method																																
<b>Thickness (Without liner)</b>	121 microns/4.8 mil per ISO 20534 Test Method																																
<b>Thickness (With liner)</b>	248 microns/9.8 mil per ISO 20534 Test Method																																
<b>Opacity</b>	Greater than 95% per TAPPI T-425 Test Method																																
<b>Brightness</b>	83% per TAPPI T-452 Test Method																																
<b>Whiteness</b>	78 per CIE Whiteness (D65/10°)																																
<b>Finish</b>	Gloss																																
<b>Tensile strength</b>	MD > 40 N/25 mm / CD > 40 N/25 mm per ASTM D 882-02																																
<b>Operating temperature</b>	15 to 35° C / 59 to 95° F																																
<b>Operating humidity</b>	30 to 80% RH																																
<b>Display permanence (Commercial in-window)</b>	5 years unlaminated, up to 10 years laminated with HP Latex Inks <sup>4</sup>																																
<b>Display permanence (Outdoor)</b>	3 years unlaminated, up to 5 years laminated with HP Latex Inks <sup>5</sup>																																
<b>Water resistance</b>	Water resistant with HP Latex Inks <sup>6</sup>																																
<b>Dry time</b>	Instant dry																																
<b>Lamination</b>	Yes, cold																																
<b>Shelf life</b>	1 year, unopened in original packaging																																
<b>Storage temperature</b>	5 to 40° C / 41 to 104° F																																
<b>Storage humidity</b>	5 to 95% RH																																
<b>Country of origin</b>	Product of China																																
<b>Ordering information</b>	<table border="1"> <thead> <tr> <th>Product numbers</th> <th>Roll sizes</th> <th>UPC codes</th> <th>Region</th> </tr> </thead> <tbody> <tr> <td>J3H61A</td> <td>762 mm x 45,7 m (30 in x 150 ft)</td> <td>848412014891</td> <td>Worldwide</td> </tr> <tr> <td>J3H62A</td> <td>914 mm x 45,7 m (36 in x 150 ft)</td> <td>848412014907</td> <td>Worldwide</td> </tr> <tr> <td>J3H63A</td> <td>1067 mm x 45,7 m (42 in x 150 ft)</td> <td>848412009293</td> <td>Worldwide</td> </tr> <tr> <td>J3H64A</td> <td>1372 mm x 45,7 m (54 in x 150 ft)</td> <td>848412009309</td> <td>Worldwide</td> </tr> <tr> <td>J3H65A</td> <td>1372 mm X 91,4 m (54 in X 300 ft)</td> <td>848412014938</td> <td>Worldwide</td> </tr> <tr> <td>J3H66A</td> <td>1524 mm x 45,7 m (60 in x 150 ft)</td> <td>848412009316</td> <td>Worldwide</td> </tr> <tr> <td>J3H67A</td> <td>1524 mm x 91,4 m (60 in x 300 ft)</td> <td>848412009323</td> <td>Worldwide</td> </tr> </tbody> </table>	Product numbers	Roll sizes	UPC codes	Region	J3H61A	762 mm x 45,7 m (30 in x 150 ft)	848412014891	Worldwide	J3H62A	914 mm x 45,7 m (36 in x 150 ft)	848412014907	Worldwide	J3H63A	1067 mm x 45,7 m (42 in x 150 ft)	848412009293	Worldwide	J3H64A	1372 mm x 45,7 m (54 in x 150 ft)	848412009309	Worldwide	J3H65A	1372 mm X 91,4 m (54 in X 300 ft)	848412014938	Worldwide	J3H66A	1524 mm x 45,7 m (60 in x 150 ft)	848412009316	Worldwide	J3H67A	1524 mm x 91,4 m (60 in x 300 ft)	848412009323	Worldwide
Product numbers	Roll sizes	UPC codes	Region																														
J3H61A	762 mm x 45,7 m (30 in x 150 ft)	848412014891	Worldwide																														
J3H62A	914 mm x 45,7 m (36 in x 150 ft)	848412014907	Worldwide																														
J3H63A	1067 mm x 45,7 m (42 in x 150 ft)	848412009293	Worldwide																														
J3H64A	1372 mm x 45,7 m (54 in x 150 ft)	848412009309	Worldwide																														
J3H65A	1372 mm X 91,4 m (54 in X 300 ft)	848412014938	Worldwide																														
J3H66A	1524 mm x 45,7 m (60 in x 150 ft)	848412009316	Worldwide																														
J3H67A	1524 mm x 91,4 m (60 in x 300 ft)	848412009323	Worldwide																														

**Warranty** HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see [globalBMG.com/hp/mediawarranties](http://globalBMG.com/hp/mediawarranties).



<sup>4</sup> Interior in-window display ratings by HP Image Permanence Lab on a range of media including HP printing materials. For more information, see [globalBMG.com/hp/printpermanence](http://globalBMG.com/hp/printpermanence).

<sup>5</sup> HP image permanence and scratch, smudge, and water resistance estimates by HP Image Permanence Lab on a range of media including HP printing materials. For more information, see [globalBMG.com/hp/printpermanence](http://globalBMG.com/hp/printpermanence).

<sup>6</sup> Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see [globalBMG.com/hp/printpermanence](http://globalBMG.com/hp/printpermanence).

**For detailed information on the HP large format printing materials portfolio and to order, visit [globalBMG.com/hp](http://globalBMG.com/hp)**

© 2014 Hewlett-Packard Development Company. © 2014 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.

4AA3-5620ENW, Rev. 10, September 2014

