




# HP Elite USB-C™ Docking Station G2



## Creating a complete workspace has never been simpler

Charge your device, view content on dual displays<sup>1</sup>, access a range of accessories<sup>1</sup>, and connect to a desktop PC<sup>1</sup> experience with a single cable connection to the HP Elite USB-C™ Docking Station G2.

### Quick and easy connectivity enabled by USB-C™

Connect the attached cable to a USB-C™ port, or use the included USB-C™ to USB-A adapter with legacy devices for quick access to your wired network, multiple displays, and accessories through the dock's DisplayPort, HDMI, RJ-45, and five USB ports.

### Power on

Keep working with a power pass through that powers your device while it charges.<sup>2</sup>

### Built for enterprise

Support network manageability of your device and the docking station with integrated Wake on LAN<sup>3</sup>, PXE boot, and 802.1x authentication on the docking station, and get physical security from a security lock slot.<sup>4</sup>

### Park it or pack it

Place the compact dock on your desk with minimal impact to your workspace, or take it to go with your tablet.

### Rest easy

Get the reassurance of a one-year limited warranty.

1. Sold separately.

2. See product QuickSpecs for exact charging capacities. Only available with direct USB-C™ cable connection; not available with USB-A to USB-C™ connection.

3. Internet access required and sold separately.

4. Lock sold separately

## Specifications

### HP Elite USB-C™ Docking Station G2

<b>Part Number</b>	X7W54AA
<b>Dimensions (H x W x D)</b>	6x2.76x0.77 in 152.4x70x19.6 mm
<b>Weight</b>	0.66 +/-0.4lbs (300+/-20g)
<b>Stand-alone power requirements</b>	
<b>Normal Operating Voltage</b>	19.5V
<b>Average Operating Power</b>	55 W
<b>Max Operating Power</b>	62 W
<b>Temperature</b>	
Operating	32-104 F (0-40 C)
Non-operating	-40 to 158 F (-40 to +70C)
<b>Relative humidity</b>	
Operating	5%- 95% RH , non-condensing
Non-operating	90% RH, 84.2F (29° C) maximum wet bulb temperature
<b>Altitude</b>	
Operating	10000 ft (3048 m)
Non-operating	30000 ft (9144 m)
<b>Shock</b>	
Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine

### HP USB-C to USB-A Adapter (included with HP Elite USB-C Docking Station G2)

<b>Dimensions (H x W x D)</b>	5.6 x .92 x .43 in 142.4 x 23.3 x 11.0 mm
<b>Weight</b>	0.038 lbs (0.0173 kg)
<b>Stand-alone power requirements</b>	
<b>Normal Operating Voltage</b>	5V
<b>Average Operating Power</b>	0.5 W
<b>Max Operating Power</b>	1 W
<b>Temperature</b>	
Operating	32-104 F (0-40 C)
Non-operating	-40 to 158 F (-40 to +70C)
<b>Relative humidity</b>	
Operating	5%- 95% RH , non-condensing
Non-operating	90% RH, 84.2F (29° C) maximum wet bulb temperature
<b>Altitude</b>	
Operating	10000 ft (3048 m)
Non-operating	30000 ft (9144 m)
<b>Random vibration (Operating):</b>	0.21 grms
<b>Random vibration (Non-operating):</b>	2.09 grms
<b>Option kit contents</b>	HP Elite USB-C Docking Station G2, AC power cable, 65W A/C adapter, HP USB Type A to Type C Adapter, Tether, Documentation.

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are U.S. registered trademarks of the Microsoft group of companies. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

