RevNo	Revision note	Date	Signature	Checked



REQUIREMENTS:

1:100% short,open and miss wire test.

2:Insulation resistance:DC300V 10MΩ(Min)
Conduction resistance 5Ω(Max)

PIN OUT



NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT
⑥	OUTER MOLDED	BLACK 45P PVC	0.038	KG
⑤	INTER MOLDED	LDPE	0.021	KG
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
③	CONNECTOR	HDB 15PIN/MALE BLUE INSULATOR,NICKEL PLATED SHELL, GOLD PLATED PIN	2	PCS
①	CABLE	(1C*28#+D+AL+PVC)*3C+6C*28#+AL+D+B JACKET:BLACK PVC OD:8.0±0.15 MARKING:AWM STYLE 2919 80℃ 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	1	M

Ltemref	Quantity	Title/Name,designation,material,dimension etc		Article No./Reference	
Designed by ACHY	Checked by HELEN	Approved by - date MARCH 6.2012	File name HDB15PIN M/M L=1M	Date MARCH 6.2012	Scale FREE
		32 1010			
		32 1010		Edition 1	Sheet 1/1