

1

2

3

4

5

6

Wiring information

PLUG 87654321  
C5e  
87654321  
JACK 2  
87654321  
JACK 1

SCALE 2/1

PIN.8  
PIN.1

58.0±0.2  
47.0  
41.8±0.2  
150.0±10.0

A

B

Specification :

Material :

1. Plastic Housing : ABS, UL 94-HB, with optional color.
2. RJ45 Jack :
  - 2-1. Housing : PBT+Glass Fiber, UL 94V-0.
  - 2-2. Contact Bracket : PBT+Glass Fiber, UL 94V-0.
3. RJ45 Jack Contact :
- 3-1. Material : Phosphor Bronze with Nickel plated.
- 3-2. Finish : 50 micro-inch Gold plated on Plug contact area.
4. RJ45 Plug :
- 4-1. Housing : (JE P/N PR8850) PC, UL 94V-2, Transparent color.
- 4-2. Contact Terminal : Phosphor Bronze with 50 micro-inch Gold plated.
5. IDC :
- 5-1. Housing : PC+Glass Fiber, UL 94V-2.
- 5-2. Terminal : Phosphor Bronze with Tin plated.
6. Assembly Type : Normal Molded, white PVC.
7. Cable Type : (UTP)Foil Shielded Twisted Pair, 24 AWG Stranded Conductor.
8. Cable Chip : SPCC with Nickel Plated.
9. Screw : Steel with Nickel Plated.
10. PCB : FR4, UL 94V-0.

22.1±0.2

SCALE 1/2

Remark : AAFDA06011301XX  
(1)(1) XX : Plastic Color  
05=White, 13=Ivory

智康科技文件控制中心  
2010.10.08  
發行

Performance :

- a. Insertion force : 20N max. (IEC 60603-7-4)
- b. Retention strength : 7.7 kg between Jack and Plug.
- c. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- d. Life(mating cycles) :
  - \* Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-4)

D

GENERAL TOLERANCE OF DIMENSIONS	DRAWING	27.SEP.2010	QIQI
X.XXX ±0.005	CHECK	27.SEP.2010	JANE
X.XX ±0.05	APPROVAL	27.SEP.2010	JAIMY
X.X ±0.1			
	SCALE	1/2 (A4)	UNIT mm
		DATE	NAME
			ITEM NO.:
			CAT5 2138
			DES.:CAT.5E MODULAR "Y" WIRING ADAPTOR

1

2

3

4

5

6

10cm