Horizontal IEC (C13) PDUs





- Horizontal IEC C13 10A outlets
- Tough 1.5U aluminium extrusion
- Shrouded switch with switch cover
- C14, C20, or 16A options
- 3-metre 1.5mm lead

Horizontal IEC PDUs are a popular unit when it comes to power distribution, as they allow a higher density of power sockets, to distribute power from one easy location in the rack.

The cable exits the unit at the rear, making mounting of the PDU easier, whilst taking up only 1.5U of vital rack space

Standard products

Order Code Product Description

| IEC6HC14 | 6 way horizontal IEC C13 PDU with switch to 3m lead to IEC C20 Plug |
|-----------|--|
| IEC8HC14 | 8 way horizontal IEC C13 PDU with switch to 3m lead to IEC C20 Plug |
| IEC10HC14 | 10 way horizontal IEC C13 PDU with switch to 3m lead to IEC C20 Plug |
| IEC12HC14 | 12 way horizontal IEC C13 PDU with switch to 3m lead to IEC C20 Plug |
| IEC16HC14 | 16 way horizontal IEC C13 PDU with switch to 3m lead to IEC C20 Plug |

PDU options



IEC C14 plug IEC 60320(320)



16A commando plug IEC 60309(309)



IEC C20 plug IEC 60320(320)

PDU technical data

| Weight of PDU 1.1kg - 1.2kg Net length of PDU 490mm Net width of PDU 60mm Net depth of PDU 45mm Shipping length of PDU 520mm Shipping Width of PDU 132mm Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg - 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz Acceptable Input Voltage 250VAC | . Do tooiiiicai aata | |
|---|--------------------------|---------------|
| Net width of PDU 60mm Net depth of PDU 45mm Shipping length of PDU 520mm Shipping Width of PDU 132mm Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg – 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Weight of PDU | 1.1kg – 1.2kg |
| Net depth of PDU 45mm Shipping length of PDU 520mm Shipping Width of PDU 132mm Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg - 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Net length of PDU | 490mm |
| Shipping length of PDU 520mm Shipping Width of PDU 132mm Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg – 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Net width of PDU | 60mm |
| Shipping Width of PDU 132mm Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg – 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Net depth of PDU | 45mm |
| Shipping Depth of PDU 75mm Shipping Weight of PDU 1.3kg - 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Shipping length of PDU | 520mm |
| Shipping Weight of PDU 1.3kg – 1.4kg PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Shipping Width of PDU | 132mm |
| PDU max power 3250W Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Shipping Depth of PDU | 75mm |
| Output rating 10A Overall rating 16A Input Frequency 50/60Hz | Shipping Weight of PDU | 1.3kg – 1.4kg |
| Overall rating 16A Input Frequency 50/60Hz | PDU max power | 3250W |
| Input Frequency 50/60Hz | Output rating | 10A |
| | Overall rating | 16A |
| Acceptable Input Voltage 250VAC | Input Frequency | 50/60Hz |
| | Acceptable Input Voltage | 250VAC |