

Vertical UK PDUs



Vertical UK PDU

Picture shows PDU10VC20

IEC C20 plug



- Vertical UK BS1363 right-angled outlets
- Tough aluminium extrusion
- Shrouded switch and switch cover
- C14, C20, or 16A commando options
- 3m 1.5mm cable

Vertical UK PDUs are widely used to accommodate cabinets where a higher number of UK sockets are needed, but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical hardware.

Standard products

Order Code

Product Description

| | |
|-----------|---|
| PDU4VC20 | 4-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU5VC20 | 5-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU6VC20 | 6-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU8VC20 | 8-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU10VC20 | 10-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU12VC20 | 12-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |
| PDU16VC20 | 16-way UK 13A power with switch to 3-metre lead to C20 IEC Plug |


PDU options



IEC C14 plug
IEC 60320(320)



16A commando plug
IEC 60309(309)



IEC C20 plug
IEC 60320(320)

PDU technical data

| | |
|--------------------------|----------------|
| Weight of PDU | 0.95kg – 1.9kg |
| Net length of PDU | 490mm – 1090mm |
| Net width of PDU | 60mm |
| Net depth of PDU | 45mm |
| Shipping length of PDU | 515mm – 1120mm |
| Shipping Width of PDU | 150mm |
| Shipping Depth of PDU | 70mm |
| Shipping Weight of PDU | 1.1kg – 2.4kg |
| PDU max power | 3250W |
| Output rating | 13A |
| Overall rating | 16A |
| Input Frequency | 50/60Hz |
| Acceptable Input Voltage | 250VAC |

