

The **AudioCodes RXVCam50L and RXVCam50M** video cameras are designed for all types of meeting rooms and conference rooms. They boast vivid image quality, leveraging HD 4K resolution for an exceptional video conferencing experience. Smart zoom and face detection technology combine to power an auto framing feature that automatically adjusts the camera's ePTZ (electronic pan, tilt and zoom), so that every meeting participant can be clearly seen – all with no user intervention required whatsoever.



The RXVCam50L is ideal for large meeting rooms with a narrow field of view (FOV), while the RXVCam50M is intended for small to medium rooms with a wide FOV.

The RXVCam50L and the RXVCam50M are integral elements of the AudioCodes RXV100 Room Experience suite, an exclusive range of audio and video devices creating a complete and customized meeting room solution. Both models are compatible with leading unified communications platforms, including Microsoft Teams and Zoom Rooms. They are super-quick to install via USB and very easy to operate.

High video quality when connected to the AudioCodes RXV100 suite or any computer, supporting 1080p HD real-time video through a 4K CMOS sensor for remarkably sharp images in any situation



Stunning images at 4K/30fps resolution



10x digital zoom for clear room coverage



Compatible with Microsoft Teams, Zoom and other UC platforms

Features

- ✓ Smart zoom and auto framing technology
- ✓ Plug and play via USB interface
- ✓ High quality image and natural color in all lighting conditions
- ✓ Compact and lightweight with smart mounting for fast and easy deployment
- ✓ Managed by AudioCodes One Voice Operations Center (OVOC)

Specifications	
Camera	
Image Sensor	1/2.5 inch high quality 4K CMOS sensor
Effective Pixels	8.28MP, 16:9
Video Output	USB3.0, Type B. Support for audio signal output.
Video Resolution	Main stream: 3840×2160 @30fps, 1920×1080P @30fps/25fps, 1280×720P@ 30fps/25fps Sub stream: 1280×720P @30fps/25fps, 640×480P @30fps/25fps, 320×172P @30fps/25fps
Angle of View	RXVCam50L 91° (D) / 81°(H) / 54°(V), RXVCam50M 102°(D) / 100°(H) / 64°(V)
Focal Length	RXVCam50L f=3.24mm, RXVCam50M f=2.26mm
Aperture	RXVCam50L F2.1, RXVCam50M F1.8
Minimum Illumination	0.1Lux (F1.8, AGC ON)
Digital Zoom	10x
DNR	2D & 3D DNR
USB	
Operating System	Windows 7 (1080P/720P), Windows 8.1, Windows 10, macOS™ 10.10 and above, Linux (UVC)
Video Compression	YUY2, MJPG, H.264, H.265
USB Protocol	UVC, UAC
PTZ Control	Supports ePTZ
Hardware Request	2.4 GHz Intel Core 2 Duo processor or better, 2GB capacity or more, USB 2.0, input (USB3.0 for 4K)
Other Parameters	
Input Voltage	DC 5V
Input Current	1A (Max)
Power Consumption	5W (Max)
Store Temperature	-10°C ~ +60°C
Store Humidity	20% ~ 90%
Working Temperature	-10°C ~ +50°C
Working Humidity	20% ~ 80%
Dimensions	220mm x 93.75mm x 56.5mm
Application	Indoor
Accessories	User manual, USB3.0 cable, remote controller



International Headquarters
 1 Hayarden Street, Airport City
 Lod 7019900, Israel
 Tel: +972-3-976-4000
 Fax: +972-3-976-4040

AudioCodes Inc.
 200 Cottontail Lane, Suite A101E,
 Somerset, NJ 08873
 Tel: +1-732-469-0880
 Fax: +1-732-469-2298

Contact us: www.audiocodes.com/corporate/offices-worldwide
 Website: www.audiocodes.com

©2021 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, What's Inside Matters, OSN, SmartTAP, User Management Pack, VMAS, VoIPerfect, VoIPerfectHD, Your Gateway To VoIP, 3GX, VocaNom, AudioCodes One Voice, AudioCodes Meeting Insights, AudioCodes Room Experience and CloudBond are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.