## Our Pure Planet USB-A to USB-C cable, 1.2m/4ft

Brand : Our Pure Planet

Product code: OPP102

Product name : USB-A to USB-C cable, 1.2m/4ft

Our Pure Planet USB-A to USB-C cable, 1.2m/4ft

Our Pure Planet USB-A to USB-C cable, 1.2m/4ft:

Quickly recharge your devices and transfer data with more speed, with the USB-A to USB-C cable. An ultra-fast charge and sync cable, this 1.2m/4ft USB-C cable gives your speed a boost.

This extra-strength braided cable has been bend-tested 20,000 times for durability you can rely on. What's more, the USB-A to USB-C cable comes with a 2-year warranty for added peace of mind.

With a 1.2m/4ft length, the USB-A to USB-C cable gives you the space you need between device and source, allowing you to enjoy high-speed charging and fast data transfer with ease.

And by choosing the USB-A to USB-C cable, you're making an eco-friendly choice. All our products are 200% plastic regenerative, 100% carbon neutral and use 100% sustainable packaging (FSC certified).



ROHS A CE

| Features  |  | Packaging data  |   |
|---|--|---|---|
| USB version *USB 2.0Connector 1 *USB AConnector 2 *USB CConnector 1 gender *MaleConnector 2 gender *MaleConnector 1 form factorStraight   | Package type<br>Package width<br>Package depth<br>Package height<br>Package weight<br>Biodegradable package              | Box<br>61 mm<br>25 mm<br>186 mm<br>73 g   |   |
| Connector 2 form factor   | Straight   | Packaging content   |   |
| Connector contacts plating<br>Cable jacket material   | Nickel<br>Polyvinyl chloride (PVC), Nylon  | Quantity per pack *   | 1 pc(s)   |
| Cable jacket type   | Braided  | Sustainability  |   |
| Maximum data transfer rate<br>Maximum data transfer rate<br>Product colour *<br>Cable type<br>Plug and Play<br>Fast charging<br>USB Power Delivery<br>USB Type-C DisplayPort Alternate<br>Mode<br>Reinforced charging cable<br>Display Stream Compression (DSC)<br>High Dynamic Range (HDR) | 480 Mbit/s<br>0.48 Gbit/s<br>Black<br>Round cable<br>✓<br>✓<br>✓   | Sustainability compliance Sustainability certificates Sustainability organizations Operational conditions Operating temperature (T-T)                           | CarbonFree, CarbonNeutral, Green<br>Tick Carbon Neutral, Green Tick<br>Sustainable, Ocean Bound Plastic<br>(OBP), Product Carbon Footprint<br>(PCF) Carbon Neutral, SCS Recycled<br>Content Certification, Sedex<br>Members Ethical Trade Audit<br>(SMETA)<br>Carbon Reduction Institute (NoCO2),<br>Plastic collective |
| supported   | ×  | Storage temperature (T-T)   | -40 - 70 °C   |
| HDCP  | X  | Logistics data  |   |
| 3D<br>EDID emulation (TX)<br>Thunderbolt technology<br>Certification  | <ul> <li>X</li> <li>CE, 200% plastic regenerative,<br/>100% carbon neutral, FSC certified<br/>packaging, ROHS</li> </ul> | Products per master (outer) case<br>Master (outer) case GTIN (EAN/UPC)<br>Master (outer) case width<br>Master (outer) case length<br>Master (outer) case height | 60 pc(s)<br>19360069000051<br>320 mm<br>360 mm<br>205 mm  |

| Power                                      |                         | Logistics data  |                                       |
|--|-------------------------|---|---------------------------------------|
| Input voltage                              | 5 V                     | Master (outer) case gross weight  | 5.5 kg                                |
| Input current (max)<br>Output voltage      | 3 A<br>5 V              | Quantity per box<br>Products per shipping (inner) case  | 1 pc(s)<br>6 pc(s)                    |
| Output current (max)                       | 2.4 A                   | Customs product code (TARIC)  | 8544421100                            |
| Weight & dimensions                        |                         | Shipping (inner) case GTIN<br>(EAN/UPC)   | 9360069000559                         |
| Cable length *<br>Cable diameter<br>Weight | 1.2 m<br>3.5 mm<br>30 g | Shipping (inner) case width<br>Shipping (inner) case length<br>Shipping (inner) case height<br>Shipping (inner) case gross weight | 6.8 cm<br>15.3 cm<br>18.8 cm<br>498 g |
|  |                         | Harmonized System (HS) code<br>Country of origin  | 8544421100<br>China                   |

| Other features          |                |
|-------------------------|----------------|
| Warranty period         | 2 year(s)      |
| Compliance certificates | CE, RoHS, WEEE |



9360069000047

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.