

Biamp Desono C-IC6 Two-Way 6.5-inch Ceiling Mount Conferencing Loudspeaker Black



Brand : Biamp

Product family: Desono

Product code: 911.0953.900

Product name : C-IC6 Two-Way
6.5-inch Ceiling Mount
Conferencing Loudspeaker Black


C-IC6 Two-Way 6.5-inch Ceiling Mount Conferencing Loudspeaker Black

[Biamp Desono C-IC6 Two-Way 6.5-inch Ceiling Mount Conferencing Loudspeaker Black:](#)

The Desono C-IC6 is a low-profile, two-way passive coaxial loudspeaker optimized for speech reproduction in conferencing applications. Designed with the installer in mind, the C-IC6 loudspeaker supports audio connections via either standard category cable or traditional speaker cable. They can be blind-mounted from below the ceiling, and feature a magnetic grille for easy toolless installation and removal. The grille plates are available in white, black, or red, or can be painted to match the room decor. The C-IC6 also directly integrates with the Tesira AMP-450BP — a four-channel “backpack” PoE+ amplifier — which reduces wiring requirements and installation time. The Desono C-IC6 loudspeakers are an ideal choice for any conferencing space that demands superior speech reproduction.

Certified for use with Zoom software.

Loudspeakers		Amplifier	
Speaker type *	2-way	Recommended amplifier power (max)	120 W
Speaker placement *	In-wall/in-ceiling	Recommended amplifier power (min)	60 W
Tweeter	✓	Ports & interfaces	
Number of tweeter drivers	1	Connectivity technology *	Wired
Tweeter diameter	2.5 cm	Bluetooth *	✗
Tweeter diameter (imperial)	2.54 cm (1")	Weight & dimensions	
Woofer	✓	Height	151 mm
Number of woofer drivers	1	Weight	3.5 kg
Woofer diameter	16.5 cm	Diameter	27.6 cm
Woofer diameter (imperial)	16.5 cm (6.5")	Packaging data	
Audio		Package width	304.8 mm
RMS rated power *	60 W	Package depth	711.2 mm
Peak Music Power Output (PMPO)	240 W	Package height	355.6 mm
Frequency range	60 - 20000 Hz	Package weight	7.08 kg
Sensitivity	88 dB	Packaging content	
Sound pressure level (max)	112 dB	Mounting brackets included	✓
Input sensitivity	2830 mV	Logistics data	
Performance		Export Control Classification Number (ECCN)	EAR99
Recommended usage *	Conferencing system	Harmonized System (HS) code	8518220000
Product colour *	Black	Other features	
Suitable for outdoor use	✗	Ethernet LAN (RJ-45) ports	2
Amplifier		Country of origin	China
Amplifier *	✗		



0814367026951



814367026951

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.