



Manhattan 4K@60Hz 2-Port HDMI Splitter Splits One HDMI Input to Two HDMI Outputs (1x2), 18G, Micro-USB input for power, EDID Switch for Downscaling to 1080p, Black, 3 year warranty



Brand : Manhattan

Product code: 207614

Product name : 4K@60Hz 2-Port HDMI Splitter Splits One HDMI Input to Two HDMI Outputs (1x2), 18G, Micro-USB input for power, EDID Switch for Downscaling to 1080p, Black, 3 year warranty

2 x HDMI out, 1 x HDMI in, DC, 4K@60Hz, HDMI 2.0, HDCP 2.3, 47 g
 Manhattan 4K@60Hz 2-Port HDMI Splitter Splits One HDMI Input to Two HDMI Outputs (1x2), 18G, Micro-USB input for power, EDID Switch for Downscaling to 1080p, Black, 3 year warranty. Video port type: HDMI, Video out: 2x HDMI. Maximum resolution: 3840 x 2160 pixels, Product colour: Black, Housing material: Plastic. Power consumption (max): 5 W. Width: 45 mm, Depth: 102 mm, Height: 15 mm. Quantity per pack: 1 pc(s), Package width: 92 mm, Package depth: 125 mm



Ports & interfaces		Packaging data	
Video port type *	HDMI	Quantity per pack	1 pc(s)
Video out *	2x HDMI	Package width	92 mm
HDMI version	2.0	Package depth	125 mm
Video ports quantity *	2	Package height	17 mm
DC-in jack	✓	Package weight	185 g
Features		Package type	Box
Product colour	Black	Packaging content	
Housing material	Plastic	Manual	✓
Maximum resolution *	3840 x 2160 pixels	Cables included	USB Type-A to Micro USB-B
HD type	4K Ultra HD	Packaging content	4K@60Hz 2-Port HDMI Splitter with Downscaling Micro-USB to USB-A power cable, 0.8 m (2.6 ft.) Instructions
Maximum refresh rate	60 Hz	Operational conditions	
Bandwidth	600 MHz	Operating temperature (T-T)	0 - 70 °C
HDCP version	2.3	Storage temperature (T-T)	-20 - 80 °C
Extended display identification data (EDID)	✓	Operating relative humidity (H-H)	5 - 90%
Cable length	0.8 m	Sustainability	
Data transfer rate	18 Gbit/s	Sustainability compliance	✓
HDCP	✓	Technical details	
Supported video modes	480p, 576i, 720p, 1080i, 1080p, 2160p	Maximum cable length	5 m
LED indicators	✓	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Number of displays supported	2	Logistics data	
Power		Master (outer) case width	270 mm
Power consumption (max)	5 W	Master (outer) case length	395 mm
Weight & dimensions		Master (outer) case height	210 mm
Width	45 mm	Master (outer) case gross weight	7.5 kg
Depth	102 mm	Products per master (outer) case	80 pc(s)
Height	15 mm		
Weight	47 g		



0766623207614



766623207614

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.