Fujitsu PRIMERGY RX2540 M7 server Rack (2U) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 900 W

Brand : Fujitsu

Product family: PRIMERGY

Product code: VFY:R2547SC020IN

Product name : RX2540 M7

- No OS
- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)
- 32GB (4800MHz) DDR5-SDRAM (1 x 32)

Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 32GB DDR5-SDRAM (4800MHz), LAN, 900W, No OS Fujitsu PRIMERGY RX2540 M7. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM. HDD size: 2.5". Ethernet LAN. Power supply: 900 W, Redundant power supply (RPS) support. Chassis type: Rack (2U)

Processor	
Processor manufacturer *	Intel
Processor family *	Intel Xeon Silver
Processor model *	4410Y
Processor frequency *	2 GHz
Processor boost frequency	3.9 GHz
Processor cores	12
Processor cache	30 MB
Motherboard chipset	Intel C741
Configurable TDP-down	4.5 W
Bus type	OPI

Memory	
Internal memory *	32 GB
Internal memory type *	DDR5-SDRAM
Memory clock speed	4800 MHz
Maximum internal memory *	8 TB

Storage	
HDD size	2.5"
Number of HDDs supported	16
RAID support *	✓

Network	
Ethernet LAN	✓

Ports & interfaces	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1

Expansion slots	
PCI Express x16 (Gen 4.x) slots	1

Design	
Chassis type *	Rack (2U)
Product colour	Black

Design	
Redundant fans support	✓

Performance	
Trusted Platform Module (TPM)	✓
Trusted Platform Module (TPM) version	2.0

Software	
Operating system installed *	✗
Compatible operating systems *	Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8

Processor special features	
CPU configuration (max)	1
Intel Smart Response Technology version	1.00
Intel Stable Image Platform Program (SIPP) version	0.00
Intel Secure Key Technology version	1.00
Intel TSX-NI version	0.00

Power	
Redundant power supply (RPS) support *	✓
Power supply *	900 W
Power supply input voltage	100 - 240 V
Power supply input frequency	50/60 Hz

Weight & dimensions	
Width	482.2 mm
Depth	800 mm
Height	86.9 mm
Weight	32 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date