Logitech Logi Dock Flex

Brand : Logitech

Product name : Logi Dock Flex

- Logi Dock Flex is a managed docking station that enables an easier desk booking experience and a better way to manage shared desks across locations

- Easily combine Logi Dock Flex with Microsoft Teams or Zoom Workspace Reservation or Logitech's own desk booking service for a simple and consistent user experience

Product code: 939-002180

- Logi Dock Flex includes ports for 6 USB peripherals, dual 4K displays, Gigabit Ethernet, and up to 100w of power, with no special drivers required

- By using a single USB-C cable, employees easily connect their laptops and gain immediate access to all desk peripherals

- The included cable management is designed to keep employees connected, day after day. Locked-in cables help you make sure desk peripherals aren't lost or unplugged

- Monitor and manage Logi Dock Flex remotely using compatible software such as Logitech Sync, Zoom Device Management, or Microsoft Teams Admin Center

Logi Dock Flex


Display

Display resolution * Display technology * LED backlight Viewing angle Display brightness	20.3 cm (8") 1280 x 800 pixels IPS ✓ 85° 300 cd/m ² Capacitive 5 ✓	Bluetooth version Ethernet LAN * Ethernet LAN data rates Security algorithms	5.0 ✓ 10,100,1000 Mbit/s 128-bit AES
		Ports & interfaces USB port RJ-45 ports quantity USB Type-C ports quantity USB 2.0 Type-A ports quantity	✓ 1 4 3
Design		Power	
Housing colour *	White	Power source type	DC
Cable lock slot Cable lock slot type Ambient light sensor Oleophobic coating	✓ Kensington ✓	Weight & dimensions Width Depth Height	201 mm 177 mm 141 mm
Audio		Weight	1 kg
Built-in speaker(s) * Built-in microphone *	××	Packaging content Cables included	AC, USB Type-C
Camera		Operational conditions	
Built-in camera *	×	Operating relative humidity (H-H)	10 - 90%
Network Wi-Fi * Wi-Fi standards * Bluetooth *	✓ 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) ✓	Storage relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T)	0 - 95% 0 - 40 °C -40 - 75 °C

Network







5099206119055

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.