


## POLY Studio X50 All-In-One Video Bar with TC8 Controller Kit

Brand: POLY Product code: 83Z47AA

Product name: Studio X50 All-In-One Video Bar with TC8

Controller Kit



- Keep your eye on the action with intelligent camera framing and NoiseBlockAl technology – powered by machine learning. Get exquisite vocal pickup from our next gen mics. Share content over wired or wireless connections via dual monitors.

Studio X50 All-In-One Video Bar with TC8 Controller Kit

## POLY Studio X50 All-In-One Video Bar with TC8 Controller Kit:

## Simple video conferencing

Poly Studio X50 video bars simplify and enhance your hybrid meeting experience in medium-sized rooms – no matter what video collaboration software you use. Experience board-room quality audio and video, all optimized into one sleek bar.

Performance		Network	
Number of persons *	1 person(s)	Ethernet LAN *	✓
Bluetooth	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Bluetooth version	5.0	Wi-Fi	✓
Product colour *	Black, Grey	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Product type *	Video collaboration bar	Camera	(002.121.7) 111 1.10 (002.12100)
Video			
HD type *	4K Ultra HD	Zoom capability	<b>√</b>
Maximum video resolution *	3840 x 2160 pixels	Digital zoom	5x
Supported video modes	2160p	Horizontal field of view	110°
	800 x 600 (SVGA), 1024 x 768	Diagonal field of view	121°
Supported graphics resolutions	(XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1400 x 1050 (SXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 3840 x 2160	Microphone	
		Number of microphones	2
		Features	
Maximum frame rate	60 fps	Cable lock slot	✓
Video formats supported	AVC, H.239, H.264, H.265	Cable lock slot type	Kensington
Audio		Operational conditions	
Built-in speaker(s)	✓	Operating temperature (T-T)	0 - 40 °C
Voice codecs	G.711, G.722, G.722.1, G.728,	Operating relative humidity (H-H)	15 - 80%
DMC retail resume	G.729A 20 W	Storage temperature (T-T)	-40 - 70 °C
RMS rated power	7.62 m	Storage relative humidity (H-H)	5 - 95%
Microphone pick-up range	7.62 111	Heat dissipation	65 BTU/h
Ports & interfaces		Packaging content	
HDMI output ports quantity	2	Camera control unit included	✓
HDMI input ports quantity	1	Cables included	HDMI, LAN (RJ-45)
HDMI version	1.4	AC adapter included	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Mounting kit Camera included	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Camera included	•
Line-in	✓		
PC Audio in	✓		





























197961954616

0197961954616





197961954609

0197961954609





197961954593

0197961954593





197961954579

0197961954579





197961954630

0197961954630