



## DELL P6524QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen

Brand : DELL

Product code: DELL-P6524QT

Product name : P6524QT

- 64.53" 4K UHD 3840 x 2160, IPS
- 9ms, 16:9, 350cd/m<sup>2</sup>, 1300:1
- USB, HDMI, DisplayPort"
- 64.53" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m<sup>2</sup> 1.07 Billion, 9 ms, 178°/178°, 1300:1

DELL P6524QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 65" 4K UHD large format monitor with 20-point touch, palm-rejection, USB-C connectivity and built-in dual 20W speakers. DELL P6524QT. Product design: Interactive flat panel. Display diagonal: 163.9 cm (64.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m<sup>2</sup>, HD type: 4K Ultra HD, Touchscreen. Product colour: Black



Display		Design	
Panel type	IPS	Bezel width (top)	4.47 cm
LED backlight	✓	Anti-glare screen	✓
Display diagonal *	163.9 cm (64.5")	<b>Performance</b>	
Display technology *	LCD	Purpose *	Corporate
Display resolution *	3840 x 2160 pixels	On Screen Display (OSD)	✓
Display brightness *	350 cd/m <sup>2</sup>	<b>Power</b>	
HD type *	4K Ultra HD	Power consumption (typical) *	101 W
Touchscreen *	✓	Power consumption (standby) *	0.4 W
Number of simultaneous touchpoints	20	Power consumption (off)	0.3 W
Multi-touch	✓	Power consumption (max)	370 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	F
Response time	9 ms	Energy efficiency class (HDR)	Not available
Contrast ratio (typical)	1300:1	Energy consumption (SDR) per 1000 hours	101 kWh
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50/60 Hz
Display number of colours	1.07 billion colours	Heat dissipation	344.63 BTU/h
Pixel pitch	0.372 x 0.372 mm	Energy efficiency scale	A to G
Display diagonal (metric)	163.906 cm	<b>Computer system</b>	
Horizontal scan range	30 - 140 kHz	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Vertical scan range	24 - 75 Hz	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Linux operating systems supported	✓
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	<b>Weight &amp; dimensions</b>	
Hardness	7H	Display width	1517.9 mm
Native refresh rate	60 Hz	Display depth	78.7 mm
		Display height	892.9 mm

<b>Display</b>		<b>Weight &amp; dimensions</b>	
RGB colour space	NTSC	Display weight	45.2 kg
Colour gamut	72%	<b>Packaging data</b>	
<b>Ports &amp; interfaces</b>		Package weight	55.3 kg
HDMI ports quantity *	3	<b>Packaging content</b>	
HDMI version	2.0	Remote control included	✓
DVI port *	✗	Stylus pen	✓
DisplayPorts quantity *	1	Number of stylus pens	2
USB port *	✓	Cables included	DisplayPort, HDMI, USB, USB Type-C
USB ports quantity	8	<b>Operational conditions</b>	
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Operating temperature (T-T)	0 - 40 °C
USB connector type	USB Type-A	Operating relative humidity (H-H)	10 - 80%
USB 2.0 Type-B ports quantity	3	Storage temperature (T-T)	-20 - 60 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Storage relative humidity (H-H)	5 - 90%
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Operating altitude	0 - 5000 m
USB Power Delivery	✓	Non-operating altitude	0 - 12192 m
USB Power Delivery up to	90 W	<b>Features</b>	
USB Type-C DisplayPort Alternate Mode	✓	Heat dissipation (max)	1262.49 BTU/h
Ethernet LAN *	✓	<b>Technical details</b>	
Ethernet LAN (RJ-45) ports	1	Sustainability compliance	✓
Wi-Fi *	✗	Sustainability certificates	ENERGY STAR
Audio (L/R) out	1	Doesn't contain	Arsenic, Mercury, PVC/BFR
RS-232 interface	✓	Compliance certificates	RoHS
<b>Audio</b>		<b>Other features</b>	
Built-in speaker(s) *	✓	Quick start guide	✓
Number of built-in speakers	2	Cable lock slot	✓
RMS rated power	40 W	LED indicators	✓
Speaker impedance	8 Ω	On/off switch	✓
Speaker frequency range	120 - 20000 Hz	Viewable size diagonal	16.4 cm
<b>Design</b>		Viewable size, horizontal	142.8 cm
Product design *	Interactive flat panel	Viewable size, vertical	80.3 cm
Placement supported *	Indoor	Power supply type	Internal
Product colour *	Black	Cable management	✓
Screen shape	Flat	Response time	9 s
VESA mounting *	✓	Plug and Play	✓
Panel mounting interface	400 x 400 mm		
Bezel width (bottom)	4.47 cm		
Bezel width (side)	4.47 cm		



5397184821541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date