

## ASUS ExpertWiFi EBP15 Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) White

**Brand :** ASUS

**Product code:** 90IG08D0-MO3B00

**Product name :** ExpertWiFi EBP15



EBP15 ExpertWiFi 5-Port GbE Smart Managed PoE+ Switch (4 PoE+ ports, 60W, supports PoE priority setting, perfect for PoE APs, IP cameras, VoIP phones, centralized app management with ExpertWiFi router)

ASUS ExpertWiFi EBP15. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 8000 entries. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE.... DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE)

| Management features                             |   | Power                                    |             |
|---|---|--|-------------|
| Switch type *                                   | Managed   | AC input voltage                         | 100 - 240 V |
| Quality of Service (QoS) support                | ✓   | AC input frequency                       | 50/60 Hz    |
| Web-based management                            | ✓   | DC input voltage                         | 54 V        |
| Ports & interfaces                              |   | Input current                            | 1.25 A      |
| Basic switching RJ-45 Ethernet ports quantity * | 5   | Input voltage                            | 54 V        |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)  | Power over Ethernet (PoE)                |             |
| Power connector                                 | DC-in jack  | Power over Ethernet (PoE) *              | ✓           |
| Network   |   | Power over Ethernet (PoE) ports quantity | 4           |
| Networking standards *                          | IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Power over Ethernet (PoE) power per port | 30 W        |
| 10G support *                                   | ✗   | Total Power over Ethernet (PoE) budget   | 60 W        |
| Port mirroring                                  | ✓   | Operational conditions                   |             |
| Auto MDI/MDI-X                                  | ✓   | Operating temperature (T-T)              | 0 - 40 °C   |
| Auto-negotiation                                | ✓   | Storage temperature (T-T)                | -20 - 70 °C |
| Data transmission                               |   | Operating relative humidity (H-H)        | 10 - 95%    |
| MAC address table *                             | 8000 entries  | Storage relative humidity (H-H)          | 5 - 95%     |
| Packet buffer memory                            | 4 MB  | Weight & dimensions                      |             |
| Security  |   | Width                                    | 121 mm      |
| IGMP snooping                                   | ✓   | Depth                                    | 75 mm       |
| Security algorithms                             | SSL/TLS   | Height                                   | 26 mm       |
| Loop protection                                 | ✓   | Weight                                   | 248 g       |
| Protocols                                       |   | Packaging content                        |             |
| Supported network protocols                     | IPv4  | Cables included                          | LAN (RJ-45) |
| Design  |   | Quick start guide                        | ✓           |
| Product colour                                  | White   | Packaging data                           |             |
| LED indicators                                  | Activity, Link, PoE, Power, Speed   | AC adapter included                      | ✓           |
|   |   | Package width                            | 231 mm      |
|   |   | Package depth                            | 211 mm      |
|   |   | Package height                           | 97 mm       |

**Performance**

Firmware upgradeable ✓

**Power**

Power source \* DC

Power supply included \* ✗

**Packaging data**

Package weight 1.1 kg



4711387093986

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date