

j5create 65W GaN USB-C 3-Port Traveler Charger with changeable AC plugs and USB-C cable

Brand : j5create

Product code: JUP3565CV-N

Product name : 65W GaN USB-C 3-Port Traveler Charger with changeable AC plugs and USB-C cable



65W GaN USB-C 3-Port Traveler Charger with changeable AC plugs and USB-C cable

[j5create 65W GaN USB-C 3-Port Traveler Charger with changeable AC plugs and USB-C cable:](#)

The 65W GaN USB-C® 3-Port Charger can simultaneously charge two USB-C® devices and one USB™ Type-A device. The charger uses GaN technology which enables it to deliver a significant amount of power in a small package. The USB-C® ports support Power Delivery 3.0/2.0 technology enabling laptops, tablets, and mobile devices to charge at the fastest rates possible. For the safety of your gadgets, the charger also has surge, overcharging, overcurrent, and overheating protection.

The 65W GaN USB-C® 3-Port Charger comes with a neatly tighten USB-C® cable and three different AC plugs are included. It's an excellent replacement for the original charger that comes with a variety of mobile devices.



Performance		Power	
Charger compatibility *	Laptop, Portable gaming console, Smartphone, Smartwatch, Tablet	Maximum power	65 W
Power source type *	AC	Port 1 output power	65 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Port 2 output power	65 W
USB Type-C ports quantity	2	Port 3 output power	30 W
Fast charging	✓	Weight & dimensions	
Fast charging technology	Adaptive Fast Charging, GaN, Power Delivery, Quick Charge 2.0, Quick Charge 3.0, SuperCharge	Width	49.7 mm
Charger type *	Indoor	Depth	56 mm
USB Power Delivery	✓	Height	30 mm
USB Power Delivery revision	3.0	Weight	123.5 g
USB Power Delivery up to	65 W	Packaging data	
Mobile operating systems supported	✓	Quantity per pack	1 pc(s)
Country of origin	China	Included power plug types	AU, EU, UK
Design		Package width	145 mm
Product colour *	White	Package depth	95 mm
Housing material	Plastic	Package height	45 mm
Power		Package weight	248 g
Input voltage	100 - 240 V	Operational conditions	
Input frequency	50 - 60 Hz	Operating temperature (T-T)	0 - 40 °C
Input current	1.5 A	Logistics data	
		Export Control Classification Number (ECCN)	EAR99



4712795088335



0847626007255



847626007255

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.