

Verbatim GNC-240 GaN Charger 240W with 1 x USB-C 140W / 1 x USB-C 100W / 1 x USB-C 65W / 1 x USB-A QC 3.0 (EU/UK/US)

Brand : Verbatim

Product code: 32205

Product name : GNC-240 GaN Charger 240W with 1 x USB-C 140W / 1 x USB-C 100W / 1 x USB-C 65W / 1 x USB-A QC 3.0 (EU/UK/US)



GNC-240 GaN Wall Charger 240W with 1 x USB-C 140W / 1 x USB-C 100W / 1 x USB-C 65W / 1 x USB-A QC 3.0 (EU/UK/US)

Verbatim GNC-240 GaN Charger 240W with 1 x USB-C 140W / 1 x USB-C 100W / 1 x USB-C 65W / 1 x USB-A QC 3.0 (EU/UK/US):

240W 4-in-1 Charging

Verbatim's 140W GaN Wall Charger combines two USB-C PD 140W ports, one USB-C PD 20W port and one USB-A QC 3.0 port in a sleek, palm sized design. Ideal for the office, home or travelling to power your laptop, tablet, smartphone, gaming devices, and more.

With its foldable US prongs and replaceable EU and UK plugs, it's the ultimate travel companion.

Safe and Reliable

The GaN charger is made with high-quality, flame-resistant materials and features four safety protection systems, including over-current protection, over-voltage protection, short circuit protection, and over-temperature protection to ensure your safety while charging.



Performance		Power	
Charger compatibility *	Universal	Port 4 output current	5 A
Power source type *	AC	Compatible power plug types	EU, UK, US
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Weight & dimensions	
USB Type-C ports quantity	3	Width	36.1 mm
Fast charging	✓	Depth	90.5 mm
Fast charging technology	Quick Charge 3.0	Height	65 mm
Charger type *	Indoor	Weight	414 g
Programmable power supply (PPS)	✓	Packaging data	
USB Power Delivery	✓	Quantity per pack	1 pc(s)
USB Power Delivery up to	240 W	Package type	Hanging box
Power protection features	Over current, Over voltage, Overheating, Short circuit	Package width	47 mm
Country of origin	China	Package depth	110 mm
		Package height	131.5 mm
		Package weight	520 g
Design		Operational conditions	
Product colour *	Black, Grey	Operating temperature (T-T)	-10 - 40 °C
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)	Storage temperature (T-T)	-20 - 80 °C
Plug and Play	✓	Operating relative humidity (H-H)	5 - 90%
Gallium nitride (GaN) transistors	✓	Packaging content	
		AC adapter included	✓
Power		Technical details	
Input voltage	100 - 240 V	Sustainability compliance	✓
Input frequency	50/60 Hz	Compliance certificates	REACH, RoHS
Input current	2.8 A	Logistics data	
Maximum power	240 W	Customs product code (TARIC)	85366990
Maximum output voltage	28 V	Master (outer) case width	280 mm
Minimum output voltage	3.3 V		
Port 1 output power	140 W		
Port 2 output power	100 W		

Power		Logistics data	
Port 3 output power	65 W	Master (outer) case length	305 mm
Port 4 output power	60 W	Master (outer) case height	302 mm
Output current (5V)	3 A	Master (outer) case gross weight	11.2 kg
Output current (9V)	3 A	Products per master (outer) case	20 pc(s)
Output current (12V)	3 A	Shipping (inner) case width	25.5 cm
Output current (15V)	3 A	Shipping (inner) case length	25.5 cm
Output current (20V)	5 A	Shipping (inner) case height	13.1 cm
Port 1 output current	5 A	Shipping (inner) case gross weight	5.4 kg
Port 2 output current	5 A	Products per shipping (inner) case	10 pc(s)
Port 3 output current	5 A		



0023942322054



023942322054



(01)20023942322058



(01)50023942322059

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.