ASUS ProArt Display PA32UCXR computer monitor 81.3 cm (32") 3840 x 2160 pixels 4K Ultra HD LCD Black

Brand : ASUS Product family: ProArt Product code: 90LM03H0-

B01K70

Product name: ProArt Display

PA32UCXR

ProArt Display PA32UCXR Professional Monitor – 32-inch, 4K UHD (3840 x 2160), 2,304 zones Mini LED Backlight, Built-in Motorized Colorimeter, Self / Auto Calibration, HDR-10, HLG, Dolby Vision, 99% Adobe RGB, 97% DCI-P3, Δ E < 1, Thunderbolt 4 PD 90W, VESA DisplayHDR 1400, Hardware Calibration, Calman Ready, ColourSpace Integration, Ergonomic Stand, Green Sustainability

ASUS ProArt Display PA32UCXR computer monitor $81.3 \text{ cm} (32") 3840 \times 2160 \text{ pixels } 4K \text{ Ultra HD LCD Black:}$

ProArt Display PA32UCXR

1600 Nits Mini-LED Monitor with Built-in Colorimeter for Ultimate Realism

ASUS ProArt Display PA32UCXR features mini-LED backlighting with 2304-zone local dimming, 1600 nits peak brightness, and up to 1000 nits sustained brightness without partial patch limitation. It boasts an industry-leading Delta E < 1 color difference, and features a built-in motorized flip colorimeter to ensure professional-grade color accuracy. Two Thunderbolt $^{\text{TM}}$ 4 ports and a host of other connectivity options enable seamless and efficient creative workflows, making this monitor ideal for content creators.







Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type	81.3 cm (32") 3840 x 2160 pixels 4K Ultra HD 16:9 LCD IPS Mini LED 1600 cd/m² 1000 cd/m² 5 ms ✓ Flat 1000:1 1000000:1 60 Hz 178° 178° 1.073 billion colours 0.1845 x 0.1845 mm	DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Headphone out * Headphone outputs HDCP HDCP version	1 1.4 2 ✓ 1 ✓ 2.2
Touchscreen * Display brightness (peak) Display brightness (typical) Response time * Anti-glare screen Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch		Ergonomics VESA mounting * Panel mounting interface Wall mountable Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment	✓ 100 x 100 mm ✓ Kensington ✓ 10 cm ✓ -90 - 90° ✓ -30 - 30°
Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency High Dynamic Range (HDR) supported High Dynamic Range (HDR) technology	70.8 cm 39.9 cm 135 - 135 kHz 40 - 60 Hz ✓ DisplayHDR 1400, Dolby Vision, High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)	Tilt angle range Power Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (HDR) per 1000 hours *	-5 - 23° G G
Colour gamut standard	DCI-P3	Power consumption (typical) *	46.62 W

Display		Power	
Colour gamut sRGB coverage (typical)	97% 100%	Power consumption (PowerSave) AC input voltage	0.5 W 100 - 240 V
Performance VESA Adaptive Sync support Flicker-free technology Low Blue Light technology	1	AC input frequency Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	50/60 Hz A to G 1692522
Multimedia Number of speakers	2	Weight & dimensions Width (with stand)	727 mm
RMS rated power Built-in speaker(s) * Built-in camera *	6 W ✓	Depth (with stand) Height (with stand) Weight (with stand) Width (without stand)	245 mm 601 mm 13.8 kg 727 mm
Design Product colour * Feet colour	Black Black	Depth (without stand) Height (without stand) Weight (without stand)	90 mm 445 mm 9.2 kg
Ports & interfaces		Packaging data	
Built-in USB hub * USB hub version USB Type-A downstream ports quantity USB Type-C downstream ports	3.2 Gen 2 (3.1 Gen 2) 3	Package width Package depth Package height Package weight Package type	965 mm 228 mm 555 mm 20.5 kg Box
quantity USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity	✓ 90 W ✓ 2	Other features Hardware calibration	✓
HDMI version	2.0		





4711387267103

0197105146303



197105146303

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.