

**Philips 1000 series 27E1N1100A/00 LED display 68.6 cm (27")
1920 x 1080 pixels Full HD LCD Black**

Brand : Philips **Product family:** 1000 series **Product code:** 27E1N1100A/00

Product name :
27E1N1100A/00

Monitor 27E1N1100A Full HD LCD monitor

Philips 1000 series 27E1N1100A/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

Experience productivity in Full HD. This monitor is equipped with essentials for the workplace, such as LowBlue mode to protect the eyes, IPS LED wide view technology for high-quality imagery, and 1ms MPRT for sharp visuals.

Philips 1000 series 27E1N1100A/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Tilt angle range	-5 - 20°
Panel type *	IPS	On Screen Display (OSD)	✓
LED backlight	✓	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Backlight type	W-LED	Number of OSD languages	21
Touchscreen *	✗	Plug and Play	✓
Display brightness (typical)	250 cd/m ²	LED indicators	Operation, Stand-by
Response time *	4 ms	Power	
Anti-glare screen	✓	Energy efficiency class (SDR) *	D
Screen shape *	Flat	Energy efficiency class (HDR) *	Not available
Contrast ratio (typical) *	1300:1	Power consumption (typical) *	18.8 W
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (standby) *	0.5 W
Maximum refresh rate *	100 Hz	Power consumption (off)	0.3 W
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50/60 Hz
Display number of colours *	16.7 million colours	Power supply type	Internal
Response time (fast)	1 ms	Operational conditions	
Pixel pitch	0.3114 x 0.3114 mm	Operating temperature (T-T)	0 - 40 °C
Pixel density	81.59 ppi	Storage temperature (T-T)	-20 - 60 °C
Horizontal scan range	30 - 85 kHz	Operating relative humidity (H-H)	20 - 80%
Vertical scan range	48 - 60 Hz	Operating altitude	0 - 3658 m
Viewable size, horizontal	59.8 cm	Non-operating altitude	3658 - 12192 m
Viewable size, vertical	33.6 cm		
Digital horizontal frequency	30 - 115 kHz		
Digital vertical frequency	48 - 100 Hz		
Display diagonal (metric)	68.6 cm		
DDC/CI	✓		
Haze rate	25%		

Display		Weight & dimensions	
Surface hardness	3H	Width (with stand)	617 mm
Colour gamut standard	sRGB	Depth (with stand)	211 mm
Display sRGB	✓	Height (with stand)	457 mm
Performance		Weight (with stand)	4 kg
NVIDIA G-SYNC *	✗	Width (without stand)	617 mm
AMD FreeSync *	✓	Depth (without stand)	46 mm
AMD FreeSync type	FreeSync	Height (without stand)	357 mm
Component video sync	Separate sync	Weight (without stand)	3.58 kg
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package width	690 mm
Multimedia		Package depth	141 mm
Number of speakers	2	Package height	455 mm
RMS rated power	4 W	Package weight	6.62 kg
Built-in speaker(s) *	✓	Packaging content	
Built-in camera *	✗	Stand included	✓
Design		Cables included	AC, HDMI
Market positioning *	Home	Manual	✓
Product colour *	Black	Sustainability	
Ports & interfaces		Sustainability compliance	✓
Built-in USB hub *	✗	Doesn't contain	Mercury, PVC/BFR
VGA (D-Sub) ports quantity	1	Other features	
HDMI *	✓	Compatible operating systems	Mac OS X Windows 11 / 10
HDMI ports quantity	1	Picture enhancement	SmartImage game
HDMI version	1.4	Recyclable packaging material	100%
Audio input	✓	Heavy metals free	Hg (mercury)
Audio output	✓	EasyRead mode	✓
HDCP	✓	LowBlue mode	✓
HDCP version	1.4	Compliance certificates	BSMI, CB, EAC, Federal Communications Commission (FCC), ICES, RoHS, cTUVus, VCCI
		Mean time between failures (MTBF)	50000 h



8712581804282

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date