ASUS PRIME H610M-K D4 ARGB Intel H610 LGA 1700 micro ATX

Brand : ASUS

Product code: 90MB1HN0-M0EAY0

Product name : PRIME H610M-K D4 ARGB

- Intel $\ensuremath{\mathbb{R}}$ LGA 1700 Socket: Ready for 14th, 13th and 12th Gen Intel $\ensuremath{\mathbb{R}}$ processors

- Ultrafast Connectivity: PCIe 4.0, 32Gbps M.2 slot, Realtek 1 Gb Ethernet and USB 5Gbps support

- Comprehensive Cooling: PCH heatsink and Fan Xpert

- Aura Sync RGB Lighting: Onboard Addressable Gen 2 headers for RGB LED strips, easily synced with Aura Sync-capable hardware

- Two-Way Al Noise Cancelation: Reduces background noise from the microphone and audio output for crystal-clear communication in games or video conferences

Intel H610 (LGA 1700) micro-ATX motherboard with DDR4, PCIe 4.0, M.2 slot, Realtek 1 Gb Ethernet, HDMI, USB 5Gbps, SATA 6 Gbps, Two-Way AI Noise Cancelation, Aura Sync





| Processor | | Internal I/O | |
|---|--|--|-------------------------------------|
| Processor manufacturer * | Intel | 12V power connector | 1 |
| Processor socket * | LGA 1700 | Rear panel I/O ports | |
| Compatible processor series * | Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9 | USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 4 2 |
| Supported processor sockets | LGA 1700 | Ethernet LAN (RJ-45) ports * | 1 |
| Memory | | PS/2 ports quantity | 1 |
| Supported memory types * Number of memory slots * | DDR4-SDRAM 2 | HDMI ports quantity * Microphone in | 1 ✓ |
| Memory slots type | DIMM | Network | |
| Memory channels Non-ECC Supported memory clock speeds | Dual-channel ✓ 3200,3000,2933,2800,2666,2400,2133 MHz | Ethernet LAN Ethernet interface type Wi-Fi * | ✔ Gigabit Ethernet ★ |
| Supported memory clock speed | 3200 MHz | Features | |
| (max) Maximum internal memory * Unbuffered memory | 3200 MHZ 64 GB ✓ | Motherboard chipset * Audio output channels * Component for * | Intel H610 7.1 channels PC |
| Storage controllers | | Motherboard form factor * | micro ATX |
| Supported storage drive types Supported storage drive interfaces | HDD & SSD * M.2, SATA III | Motherboard chipset family * Windows operating systems supported | Intel Windows 10 x64, Windows 11 |
| Graphics | | Expansion slots | |
| Parallel processing technology support * | Not supported | PCI Express x1 (Gen 3.x) slots | 1 |
| Internal I/O | | PCI Express x16 (Gen 4.x) slots | 2 |
| USB 2.0 connectors * | 1 | Number of M.2 (M) slots | 1 |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 1 | BIOS type * | UEFI AMI |
| Number of SATA III connectors * | 4 | BIOS memory size | 128 Mbit |
| S/PDIF out connector | 1 | Packaging data | |
| Audio connector Front panel audio connector | 4 | Package width | 270 mm |

| ATX Power connector (24-pin) ATX Power connector (24-pin) Package depth 263 mm Package height 51.5 mn Package height 51.5 mn Package weight 800 g PS power connector (8-pin) Package weight 800 g Weight & dimensions Width 234 mm Vidth 234 mm | | | | |
|---|----------------------------------|---|---------------------|---------|
| CPU fan connector Image: Package height 51.5 mm Number of chassis fan connectors 1 Package weight 800 g EPS power connector (8-pin) Image: Weight & dimensions 800 g Number of COM connectors 1 Weight & dimensions TPM connector Image: Width 234 mm | Internal I/O | | Packaging data | |
| Number of chassis fan connectors 1 Package weight 800 g EPS power connector (8-pin) ✓ Weight & dimensions Number of COM connectors 1 Width 234 mm | ATX Power connector (24-pin) | 1 | Package depth | 263 mm |
| EPS power connector (8-pin) ✓ Weight & dimensions Weight & dimensions Number of COM connectors 1 TPM connector ✓ | CPU fan connector | 1 | Package height | 51.5 mm |
| Number of COM connectors 1 Weight & dimensions TPM connector ✓ Width 234 mm | Number of chassis fan connectors | 1 | Package weight | 800 g |
| Number of COM connectors 1 Width 234 mm | EPS power connector (8-pin) | < | Weight & dimensions | |
| TPM connector | Number of COM connectors | 1 | | 234 mm |
| | TPM connector | ✓ | Depth | 203 mm |
| | | | Packaging content | |

Cables included

SATA



4711387460177

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.