## ScreenBeam Flex wireless presentation system HDMI + USB Type-A Desktop

Brand : ScreenBeam Product code: SBWD1100FEUINL

**Product name:** Flex

Miracast, Airplay, Google Cast, 802.11ac, 1000Base-T RJ-45 LAN, 4K30 ScreenBeam Flex. Form factor: Desktop, Product colour: White, Certification: FCC, RED, RoHS, UL. Wi-Fi standards: Wi-Fi 5 (802.11ac), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), Ethernet LAN data rates: 10,100,1000 Mbit/s. Interface: HDMI + USB Type-A. Power source type: DC, Input voltage: 12 DC, Input current: 3 A. Windows operating systems supported: Windows 10, Windows 11, Mac operating systems supported: Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Other operating systems supported: ChromeOS





Design		Power	
Form factor * Product colour Certification	Desktop White FCC, RED, RoHS, UL	Input voltage Input current Power consumption (max)	12 DC 3 A 24.8 W 8.4 W
Features		Power consumption (typical)	8.4 W
AirPlay mirroring Miracast Google Cast Network	<b>* * *</b>	System requirements Windows operating systems supported Mac compatibility	Windows 10, Windows 11  ✓  Mac OS X 11.0 Big Sur, Mac OS X
Wi-Fi standards Top Wi-Fi standard Dual-band Bluetooth Ethernet LAN	i-Fi standard Wi-Fi 5 (802.11ac) and  oth  et LAN	Mac operating systems supported  Other operating systems supported  Mobile operating systems supported	12.0 Monterey, Mac OS X 13.0 Ventura ChromeOS Android 8.0, Android 8.1, Android
Ethernet LAN data rates Cabling technology	10,100,1000 Mbit/s 10/100/1000Base-T(X)	Operational conditions	
Networking standards Supported network protocols	IEEE 802.1x IEEE 802.1x, WPA-PSK (TKIP), WPA2-PSK (AES), PEAP-MSCHAPv2, EAP-TLS	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 20 - 80% 20 - 85 °C 10 - 90%
Ports & interfaces		Weight & dimensions	
Interface * Number of HDMI outputs Ethernet LAN (RJ-45) ports USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A	HDMI + USB Type-A 1 1 2	Width Depth Height Weight	220 mm 144 mm 37.5 mm 453.5 g
ports quantity	1	Packaging content	
3.5 mm (1/8-inch) out DC-in jack	<b>✓</b>	Cables included	НДМІ
Power			
Power source type *	DC		





850015351051

0850015351051

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.