

ScreenBeam 1000 EDU Gen 2 wireless presentation system HDMI + USB Type-A Desktop

Brand : ScreenBeam

Product code: SBWD1000EDUG2EUINL

Product name : 1000 EDU Gen 2

Miracast, Airplay, Google Cast, 4K60, Wi-Fi, 220mm x 144mm x 37.5mm

ScreenBeam 1000 EDU Gen 2. Form factor: Desktop, Product colour: White, Certification: FCC, RED, RoHS, UL. Wi-Fi standards: Wi-Fi 5 (802.11ac), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), Ethernet LAN data rates: 10,100,1000 Mbit/s. Interface: HDMI + USB Type-A. Power source type: DC, Input voltage: 12 DC, Input current: 3 A. Windows operating systems supported: Windows 10, Windows 11, Mac operating systems supported: Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Other operating systems supported: ChromeOS



Design		Power	
Form factor *	Desktop	Input voltage	12 DC
Product colour	White	Input current	3 A
Certification	FCC, RED, RoHS, UL	Power consumption (max)	24.8 W
Features		Power consumption (typical)	8.4 W
AirPlay mirroring	✓	System requirements	
Miracast	✓	Windows operating systems supported	Windows 10, Windows 11
Google Cast	✓	Mac compatibility	✓
Network		Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Wi-Fi standards	Wi-Fi 5 (802.11ac)	Other operating systems supported	ChromeOS
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Mobile operating systems supported	Android 8.0, Android 8.1, Android 9.0, iOS 13, iOS 13.4, iOS 14, iOS 14.5, iOS 15, iOS 16
Dual-band	✓	Operational conditions	
Bluetooth	✓	Operating temperature (T-T)	0 - 40 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	20 - 80%
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage temperature (T-T)	20 - 85 °C
Cabling technology	10/100/1000Base-T(X)	Storage relative humidity (H-H)	10 - 90%
Networking standards	IEEE 802.1x	Weight & dimensions	
Supported network protocols	IEEE 802.1x, WPA-PSK (TKIP), WPA2-PSK (AES), PEAP-MSCHAPv2, EAP-TLS	Width	220 mm
Ports & interfaces		Depth	144 mm
Interface *	HDMI + USB Type-A	Height	37.5 mm
Number of HDMI outputs	1	Weight	453.5 g
Ethernet LAN (RJ-45) ports	1	Packaging content	
USB 2.0 ports quantity	2	Cables included	HDMI
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1		
3.5 mm (1/8-inch) out	✓		
DC-in jack	✓		
Power			
Power source type *	DC		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date