iiyama TE6512MIS-B3AG Signage Display Kiosk design 165.1 cm (65") LCD Wi-Fi 400 cd/m² 4K Ultra HD Black Touchscreen Built-in processor Android 11 24/7

Brand : iiyama **Product code:** TE6512MIS-B3AG

Product name: TE6512MIS-B3AG

65", IPS, 3840 x 2160, 16:9, 400 cd/m², 4000:1, PureTouch-IR, VGA, HDMI x4, USB-C, Mini jack x1, RS-232c x1, RJ45 x3, IR x1, S/PDIFI USB x5, WiFi, 7H, 1488.5 x 896.5 x 87.5mm, 35kg iiyama TE6512MIS-B3AG. Product design: Kiosk design. Display diagonal: 165.1 cm (65"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD, Touchscreen. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: Android 11. Product colour: Black





| Display | | Design | |
|--|--|---|--|
| Panel type Display diagonal * Display technology * Display resolution * Display brightness * HD type * | IPS 165.1 cm (65") LCD 3840 x 2160 pixels 400 cd/m ² 4K Ultra HD | Product colour * VESA mounting * Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top) | Black |
| Touchscreen * | P. o.T. ab ID | Performance | |
| Touchscreen technology Number of simultaneous touchpoints Native aspect ratio Response time Contrast ratio (typical) | PureTouch-IR 40 16:9 8 ms 1200:1 | Purpose * On Screen Display (OSD) On Screen Display (OSD) languages Operating hours (hours/days) | Commercial ✓ Czech, Danish, German, English, Spanish, Finnish, French, Italian, Polish, Russian, Slovenian 24/7 |
| Contrast ratio (dynamic) 4000:1 Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours 1.07 billion colour | 178° | HDCP HDCP version Mean time between failures (MTBF) | ✓ 2.2 50000 h |
| Pixel pitch | 0.372 x 0.372 mm | Power | |
| Active display area (W x H) Display diagonal (metric) Horizontal scan range Surface hardness Glass thickness | 1428.5 x 803.5 mm 163.9 cm 30 - 135 kHz 7H 3 mm | Power consumption (typical) * Power consumption (standby) * Power consumption (off) AC input voltage AC input frequency | 138 W 0.5 W 0.3 W 100 - 240 V 50/60 Hz |
| Glass film | AG/AR Film | Computer system | |
| Ports & interfaces HDMI ports quantity * HDMI version HDMI input ports quantity HDMI output ports quantity DVI port * VGA (D-Sub) input ports USB port * USB yersion | 4 2.0 3 1 X 1 J 5 3.2 Gen 1 (3.1 Gen 1) | Built-in processor * Processor manufacturer Processor family Processor model Processor architecture Processor cores Internal memory On-board graphics card model Internal storage capacity Operating system installed | ARM ARM Cortex A55 ARM Cortex-A55 4 8 GB ARM Mali-G52 32 GB Android 11 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | , | Weight & dimensions | |
| ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity Ethernet LAN * | 2 3 ✓ | Width (with stand) Depth (with stand) Height (with stand) | 1488.5 mm 87.5 mm 896.5 mm |

| Ports & interfaces | | Weight & dimensions | |
|-----------------------------------|--|-----------------------------------|--|
| Ethernet LAN (RJ-45) ports | 2 | Weight (with stand) | 35 kg |
| Wi-Fi * | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) | Packaging data | |
| Wi-Fi standards | | Package width Package depth | 1628 mm 208 mm |
| RS-232 interface | ✓ | Package height | 1005 mm |
| RS-232C | ✓ | Package volume | 44700 cm ³ |
| Remote (IR) input | 1 | Packaging content | |
| Audio Return Channel (ARC) | ✓ | Remote control included | 1 |
| Audio | | Batteries included | 1 |
| Built-in speaker(s) * | ✓ | Cables included | HDMI, Power, USB |
| Number of built-in speakers | 2 | Wi-Fi module included | ✓ |
| RMS rated power | 32 W | Operational conditions | |
| Design | | Operating temperature (T-T) | 0 - 40 °C |
| Product design * | Kiosk design | Operating relative humidity (H-H) | -20 - 60% |
| Placement supported * Orientation | Indoor Horizontal | Certificates | |
| | | Certification | CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, EPA 8.0 |



4948570123698

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.