POLY G7500 Video Conferencing System No Radio or Power Cord (BT and WiFi) GSA/TAA

Brand : POLY

Product code: 842T8AA

Product name : G7500 Video Conferencing System No Radio or Power Cord (BT and WiFi) GSA/TAA

- This modular video conferencing system makes it easy to outfit conference rooms to meet your organization's unique needs. Loaded with flexible features, the G7500 leverages your design to power your meetings and wow your teams.
- An easy to deploy solution for your modular meeting spaces. Seamlessly connects to Poly cameras and microphones for enhanced audio and video. And includes a robust set of REST APIs so you can easily integrate with other room components.
G7500 Video Conferencing System No Radio or Power Cord (BT and WiFi) GSA/TAA

POLY G7500 Video Conferencing System No Radio or Power Cord (BT and WiFi) GSA/TAA:

Customize rooms with confidence
Outfit conference rooms to meet your organization's unique needs. The Poly G7500 video conferencing system offers quality audio and video, plus it's flexible and customizable for any room space.
POLY G7500 Video Conferencing System No Radio or Power Cord (BT and WiFi) GSA/TAA. Product type: Group video conferencing system. HD type: 4K Ultra HD, Maximum frame rate: 60 fps. Ethernet LAN. Product colour: Black

Performance	
Product colour *	Black
Product type *	Group video conferencing system

Video	
HD type *	4K Ultra HD
Maximum video resolution *	3840 x 2160 pixels
Supported graphics resolutions	800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1400 x 1050 (SXGA+), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 3840 x 2160
Maximum frame rate	60 fps
Video formats supported	AVC, H.264, H.265

Ports & interfaces	
HDMI output ports quantity	3
HDMI input ports quantity	1
HDMI version	1.4
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
PC Audio in	✔
RS-232 ports	1

Network	
Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000 Mbit/s

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	15 - 80%
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	65 BTU/h

Weight & dimensions	
Width	349.2 mm
Depth	38.1 mm
Height	139.7 mm
Weight	952.5 g

Packaging content	
Cables included	LAN (RJ-45)
AC adapter included	✔
Remote control included	✔

0197497464658

197497464658

0198122152216

198122152216

0017229189478

017229189478