

GIGABYTE Z790 AORUS XTREME X ICE Motherboard - Supports Intel 14th Gen CPUs, LGA 1700, 24+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 10GbE LAN, USB 3.2 Gen 2x2

Brand : GIGABYTE



Product code: Z790 AORUS XTREME X ICE

Product name : Z790 AORUS XTREME X ICE Motherboard - Supports Intel 14th Gen CPUs, LGA 1700, 24+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 10GbE LAN, USB 3.2 Gen 2x2

Intel Z790, 4 x DDR5, 8266 MHz, Wi-Fi 7, 2 x RJ-45, 4 x SATA, E-ATX

GIGABYTE Z790 AORUS XTREME X ICE Motherboard - Supports Intel 14th Gen CPUs, LGA 1700, 24+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 10GbE LAN, USB 3.2 Gen 2x2:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	Thunderbolt ports quantity	2
Processor socket *	LGA 1700	WiFi-AP antenna jack	2
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold	USB connector type	USB Type-A, USB Type-C
Maximum number of SMP processors	1	Network	
Supported processor sockets	LGA 1700	Ethernet LAN	✓
Memory		Ethernet interface type	2.5 Gigabit Ethernet, 10 Gigabit Ethernet
Supported memory types *	DDR5-SDRAM	LAN controller	Aquantia AQC107
Number of memory slots *	4	Wi-Fi *	✓
Memory slots type	DIMM	Top Wi-Fi standard	Wi-Fi 7 (802.11be)
Memory channels	Dual-channel	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 7 (802.11be)
ECC	✓	WLAN controller model	Qualcomm QCNM865
Non-ECC	✓	Bluetooth	✓
Supported memory clock speeds	4000,4800,5200,5400,5600,5800,6000,6200,6400,6600,6800,7000,7200,7400,7600,7800,7900,7950,8000,8200,8266 MHz	Bluetooth version	5.3
Supported memory clock speed (max)	8266 MHz	Features	
Maximum internal memory *	192 GB	Motherboard chipset *	Intel Z790 Express
Supported memory module capacities	1GB, 2GB, 4GB, 8GB, 12GB, 16GB, 32GB, 48GB	Audio chip	ESS ES9280AC + ESS ES9080
Unbuffered memory	✓	Audio output channels *	7.1 channels
Storage controllers		Product colour	White
Supported storage drive types	HDD & SSD	PC health monitoring	Fan, Noise, Temperature, Voltage, Water cooling
Supported storage drive interfaces *	M.2, SATA III	Component for *	PC
Number of HDDs supported	4	Motherboard form factor *	Extended ATX
Number of storage drives supported	9	Motherboard chipset family *	Intel
RAID support	✓	Windows operating systems supported	Windows 11 x64
RAID levels	0, 1, 10	Expansion slots	
Graphics		PCI Express x16 (Gen 3.x) slots	1
Parallel processing technology support *	Not supported	PCI Express x16 (Gen 5.x) slots	1
Maximum resolution	5120 x 2880 pixels	Number of M.2 (M) slots	5
HDCP	✓	Internal I/O	
DirectX version	12.0	USB 2.0 connectors *	1
Internal I/O		USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2

Internal I/O		BIOS	
USB 3.2 Gen 2x2 connectors	2	BIOS type *	UEFI AMI
Number of SATA III connectors *	4	BIOS memory size	256 Mbit
Front panel audio connector	✓	ACPI version	5.0
Front panel connector	✓	Clear CMOS jumper	✓
ATX Power connector (24-pin)	✓	Clear CMOS button	✓
Number of EATX power connectors	2	Desktop Management Interface (DMI) version	2.7
CPU fan connector	✓	System Management BIOS (SMBIOS) version	2.7
Number of chassis fan connectors	3	Logistics data	
EPS power connector (8-pin)	✓	Country of origin	Taiwan
TPM connector	✓	Products per shipping (inner) case	1 pc(s)
Thunderbolt headers	2	Battery	
12V power connector	✓	Battery weight	3 g
RGB LED pin header	✓	Lithium weight per battery	0.07 g
Rear panel I/O ports		Number of battery cells	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	10	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
Ethernet LAN (RJ-45) ports *	2	Battery type	CR2032
Headphone outputs	1	Packaging data	
Microphone in	✓	Package width	417 mm
S/PDIF out port	✓	Package depth	378 mm
Digital audio optical out	1	Package height	127 mm
		Weight & dimensions	
		Width	305 mm
		Depth	285 mm
		Height	35 mm
		Packaging content	
		Cables included	SATA
		Batteries included	✓
		Antenna included	✓
		Bundled software	Norton® Internet Security (OEM version) LAN bandwidth management software
		Technical details	
		Warranty period	3 year(s)



4719331862268

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date