

DELL Latitude 3450 Intel® Core[™] i5 i5-1335U Laptop 35.6 cm (14") Full HD 16 GB DDR5-SDRAM 512 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Grey

Brand : DELL

Product family: Latitude

Product code: TNGPX

Product name : 3450

- Windows 11 Pro 64-bit

- Intel Core i5-1335U (12MB Cache)

- 35.6 cm (14") Full HD 1920 x 1080 IPS

- 16GB DDR5-SDRAM (2 x 8) & 512GB SSD

Intel Core i5-1335U (12MB Cache), 16GB DDR5-SDRAM, 512GB SSD, 35.6 cm (14") Full HD 1920 x 1080 IPS, Intel Iris Xe Graphics, LAN, WLAN, Webcam, Windows 11 Pro 64-bit

DELL Latitude 3450 Intel® Core ™ i5 i5-1335U Laptop 35.6 cm (14") Full HD 16 GB DDR5-SDRAM 512 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Grey:

Work from anywhere with our most intelligent and secure business laptops sustainably designed for productivity on the go.

DELL Latitude 3450. Product type: Laptop, Form factor: Clamshell. Processor family: Intel® Core[™] i5, Processor model: i5-1335U. Display diagonal: 35.6 cm (14"), HD type: Full HD, Display resolution: 1920 x 1080 pixels. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 512 GB, Storage media: SSD. On-board graphics card model: Intel Iris Xe Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey. Weight: 1.5 kg









Design		Network	
Product type * Product colour * Form factor * Market positioning	Laptop Grey Clamshell Business	WLAN controller manufacturer Ethernet LAN Ethernet LAN data rates Bluetooth	Intel ✓ 10,100,1000 Mbit/s ✓
Display		Ports & interfaces	
Display diagonal * Display resolution * Touchscreen * HD type Panel type LED backlight Native aspect ratio Anti-glare screen Display brightness Pixel pitch Pixel density	35.6 cm (14") 1920 x 1080 pixels	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB4 Gen 2x2 ports quantity Ethernet LAN (RJ-45) ports HDMI ports quantity * HDMI version Combo headphone/mic port Charging port type Power adapter barrel connector PowerShare Number of USB ports with PowerShare support	3 1 1 1.1 1.4 ✓ DC-in jack 4.5 mm ✓
RGB colour space Colour gamut	45%	Keyboard	
Display response rise/fall Maximum refresh rate Contrast ratio (typical)	35 ms 60 Hz 700:1	Pointing device Keyboard language Numeric keypad *	Touchpad UK English 🗙
Processor		Keyboard backlit	4
Processor manufacturer * Processor family * Processor generation	Intel Intel® Core™ i5 13th gen Intel® Core™ i5	Spill-resistant keyboard Keyboard number of keys Copilot key	✓ 80 ✓
Processor model *	i5-1335U	Software	
Processor cores Processor threads	10 12	Operating system architecture	64-bit

ProcessorSoftwareSoftwareProcessor to soft frequency4.6 GHzOperating system languageGerman, Dutch, English, FrenchPerformance core Max Turba4.6 GHzOperating system installed **Muthovait Office Licence IncludedPerformance-core Max Turba4.6 GHzOperating system installed **Withowait Office Licence IncludedPerformance-core Max Turba4.6 GHzOperating system installed **Withowait Office Licence IncludedPerformance-core Max Turba4.6 GHzOperating system installed **Withowait Office Licence IncludedPerformance-core Max Turba4.6 GHzOperating system installed **Withowait Office Licence IncludedPerformance-core Max Turba5.0 MBatteryExpress/Solid, In IBR Concess, TMS BorgSolid System IncludedProcessor Cache type5.5 WBattery ventopic5.4 WSolid System IncludedMaximum Internory6.6 GHOperating system language1.4 VMemory found Lice5.20 DMMBattery ventopic5.6 WMaximum Internory5.12 GHA cadapter proventic3.3 A AStorage5.12 GHA cadapter proventic3.3 A AStorage System Size Installed1.2 CHSolid Front Viewage1.4 VMaximum Internory Maximum Internation5.12 GHCalable Cole Col3.3 AStorage System Size Installed1.2 CHCalable Cole Col3.3 AStorage System Size Installed1.2 CHCalable Cole Col3.3 AStorage System Size Installed1.2 CHCalable Cole Col	Drocoscor		Foftwara	
Performance core2 meanOperating system inguigeInitial andEffectences8Trial software80 day Trial Offse Licene Incluided 30 day Trial Offse Licene Incluided	Processor	4.6.00	Software	
Partoninactories4ControlMicrosoft Ordific ControlMicrosoft Ordific ControlMicroso			Operating system language	
performance-ore Nax Turbo4.6 GHzOperating system installed30 day Inst OrderProgressor order by pe3.4 GHzMicrosoft CopietProcessor cache by peSmart CacheBand-specific featuresExpressSignin, IAR Camers, TMRProcessor cache by peStavBarteryStaverssignin, IAR Camers, TMRProcessor cache by peStaveBartery3Memory in Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory internal memory spiceIG GBBattery values34 dhy Inst OrderMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane CopietStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRMemory form Loren Jane Memory formStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRStavers Camers, TMRStaverssignin, IAR Camers, TMRStaverssignin, IAR Camers, TMRStorage mediaStaver			T (1) (1) (1)	
Frequency4.0 MPCOperating system installed*Windows 1 ProFrequency3 GPCMarcost CopilorSProcessor cache2 ABBand specific featuresEpress Charge Boost Capable, processor base powerProcessor cache2 NBBand specific featuresEpress Charge Boost Capable, processor base powerProcessor cache5 WBand specific technologiesEpress Charge Boost Capable, processor base powerMemory15 GBBattery weaper cache4 Whone Capable, processor base powerInternal memory 716 GBBattery weaper cache4 Whone Capable, processor base powerMemory form factor50 DMMBattery weaper cache2 D gMemory form factor50 DMMBattery weaper2 D gMemory dus tafter to2 S O GMMBattery weaper2 D gMemory dus tafter to2 D GMMA cadapter input voltage10 C MCMemory dus tafter to2 D G MFA cadapter onput voltage10 S VStorage modia5 D GA cadapter onput voltage10 S VStorage taffic factures7 C Cadapter onput voltage10 S V <td></td> <td></td> <td>Irial software</td> <td>30 day Trial Offer Only</td>			Irial software	30 day Trial Offer Only
Dickson cache typeJaviaProcessor cache typeJaviaProcessor cache typeSumar CacheProcessor cache typeSumar CacheSumar Cac		4.6 GHz		
Processor base powerSmart CacheBand specific technologiesExpress Charge Boost capable, Depression in UPD Camera, TANProcessor base power15 WBarteryDepression in UPD Camera, TANMaximum tubo power5 WBartery3Memory four factor16 GBBartery cells3Internal memory typeDDBS-SDRAMBartery voltage11.4 VMemory form factor2.4 K GBBartery voltage4Memory joyou (box s size)2.4 K GBBartery recharge time4Memory joyou (box s size)2.4 K GBBartery veltage time4Memory joyou (box s size)2.4 K GBBartery veltage time4Memory joyou (box s size)2.4 K GBBartery veltage time0.2 GOMemory joyou (box s size)2.4 K GBBartery veltage time3.0 K AMemory jobs2.4 K GBAC adapter notyrotage10.0 - 240 VStorage mediaSDDAC adapter outyrotage10.0 - 240 VStorage mediaSDCAC adapter outyrotage10.0 - 240 VStorage mediaSDCAC adapter outyrotage10.0 - 240 VStorage mediaSDCAC adapter outyrotage10.0 - 240 VStorage time of SDS installed1.2 C BCole ick sist-SD opacitySDC do CCCole ick sistSD opacityVCole ick sistSD opacityVCole ick sistSD opacityM 2SD opacitySD opacity <td< td=""><td>Efficient-core Max Turbo Frequency</td><td>3.4 GHz</td><td>Microsoft Copilot</td><td>4</td></td<>	Efficient-core Max Turbo Frequency	3.4 GHz	Microsoft Copilot	4
Processor base power Maximum turbo power15 WBrand specific technologiesExpressor signing, HOR Camputor, TWA Maximum turbo power50 WMaximum turbo power50 WSuttery3Memory16 GBBattery capacity54 Win Acada 114 VInternal memory typeDORS SDRAMBattery recharge time4 hMemory furn factorSO-DMMBattery recharge time50 forMemory furn factorSO-DMMBattery recharge time50 forMemory furn factorSO-SO-DMMBattery recharge time50 forSol fors factorSSDAc adapter output valtage100 - 240 VSol fors factorSSDAc adapter output valtage100 - 240 VSol fors factorSSDAc adapter output valtage314 ASol fors factorSSDCale factor function4Sol fors factorSD depender timeMemory function324 ASol fors factorMaxCale factor function4Sol fors factorMaxCale factor function4Sol fors factorMaxGale factor function4 <tr< td=""><td></td><td></td><td>Brand-specific features</td><td></td></tr<>			Brand-specific features	
Induces of lose ployer15 wExtremulation of a latery of			Brand specific technologies	
Henery Number of battery cells 3 Internal memory* 16 GB Battery capacity* 5 Wh Internal memory type DDRS-SDAM Battery varbarge time 11.4 V Memory form factor SO-DMM Battery varbarge time 4.h Memory fastor SO-DMM Battery varbarge time 4.h Memory fastor SO-DMM Cadapter output varbarge time 5.W Solarge media SSO-DMM SSO composition SSO composition SSO composition SSO composition SSO composition V SSO form factor M.2 Trusted Platform Module (TPM) V V SSO form factor M.2 Trustef Platform Module (TPM) V	•			ExpressSign-In, HDR Camera, TNR
Internal memory*16 GBBattery conception*54 WhInternal memory typeDDK5-SDRAMBattery vertage time11.4 VMemory form factorSO-DIIMMBattery vertage time4.hMemory loyuul (slots xize)2 x 8 GBFast charging4/Memory loyuul (slots xize)2 x 8 GBFast charging4/Memory loyuul (slots xize)2 x 8 GBBattery vertage time4.hMemory data transfer rateS200 M7/sAc adapter power6 WStorageSSDAC adapter forgency50/60 HzTotal Storage capacity*512 GBAC adapter forguncy voltage100 - 240 VStorage media *SSDAC adapter forguncy voltage19.5 VTotal Storage capacity512 GBAC adapter forguncy voltage19.5 VSSD capacity512 GBCable lock slot typeWedgeSSD installed1SecurityVSSD installedNCable lock slot typeWedgeSSD installed1Security2.0SSD installedNYSome module (TPM)4/SSD installedNYSome module (TPM)4/SSD installedNNNNSSD installedNNNNSSD installedNNNNSSD installedNNNNSSD installedNNNNSSD installedNNNNSSD installedNNN<	·	55 VV	Battery	
International Memory lypeDBS.SDRAMBattery vecharge has Battery recharge has Battery recharge has Battery recharge has Battery vecharge has bettery vecharge has bettery vecharge has bettery vecharge has better vecharge has <b< td=""><td></td><td></td><td>•</td><td></td></b<>			•	
Memory form factorSOMMABattery endage timeA (Addemain the many endage)Memory situs sizus2 × 8 6 GBSattery weight2 0 g (Addemain the many endage)Maximum internal memory4 200 MAXPerevSom MAXMemory situ standard2 500 MIXAdapter fragmenty500 MIXStandard2 500 MIXAdapter fragmenty500 MIXStandard2 500 MIXAdapter fragmenty weights3.34 Adapter input voltageStorage media5 50 Adapter input voltage3.34 Adapter input voltage3.34 Adapter input voltageStorage media5 200 MIXAdapter input voltage3.34 Adapter input voltageStorage media5 200 MIXAdapter input voltage3.34 Adapter input voltageStorage media5 200 MIXAdapter input voltage4.64 Sector input voltageStorage media5 200 MIXAdapter input voltage4.64 Sector input voltageStorage media9 CE Series ADMedia Sector input voltage4.64 Sector input voltageStorage mediaMaxMaxMedia4.64 Sector input voltageStorage mediaMaxMaxMax4.64 Sector input voltage				
Memory layout (slots x size)2 x 8 GBFast harging/ Battry weight/ 20 g/lineMemory layout (slots x size)2 x 8 GBBattry weight20 g/lineMaximum internal memory64 GBPowerMemory data transfer rate5200 MT/sA cadapter prevery5000 HzStorage				
Nemony side250 -0IMMBittery weight202 0g - Qui and side of the side o	•			
Maximum internal memory Memory data transfer rate6408 MT/sAccadapter power55 WMemory data transfer rate5200 MT/sAc dadpter power frequency5060 HzStorage capacity*512 GBAc dadpter output voltage100 -240 VStorage media*S5DAc dadpter output voltage132 AStorage media*S5DAc dadpter output voltage134 AStorage media*S12 GBCadele lock slotVSto capacity512 GBCadele lock slot typeWedgeS5D enapority typeQLCCadele lock slot typeWedgeS5D for factorM2Trusted Platform Module (TPM)4S5D form factorM2Trusted Platform Module (TPM)4S5D form factorM2Trusted Platform Module (TPM)4S5D rand rule transfer alsoNot availableStorage temperature (T-T)0 -0 °CS5D rand rule transfer alsoNot availableStorage relative hundidy (H)0 -0 S%On-baard graphics card famolIntel ins Xe GraphicsNon-operating altitude-52.2 304 mOn-baard graphics card famolIntel ins Xe GraphicsNon-operating altitude-52.2 304 mOn-baard graphics card famolIntel ins Xe GraphicsNon-operating altitude-52.2 304 mOn-baard graphics card famolIntel ins Xe GraphicsNon-operating altitude-52.2 304 mOn-baard graphics card famolNon-operating altitude-52.3 304 mOn-baard graphics card famolNon-operating altitude-52.3 304 mOn-baard graphics card fam				
Memory data transfer rate S200 MT/s Acadapter power 65 W Storage AC adapter frequency 50/60 Hz Total storage capacity 512 GB AC adapter input voltage 100 - 240 V Storage media S5D AC adapter output voltage 19.5 V Total SSD capacity 512 GB AC adapter output voltage 19.5 V SSD installed 1 SSE capacity S12 CB Cable lock slot 4 SSD instanted 1 SSE capacity Vedge 4 SSD instanted PCI Express 4.0 Filingerprint reader 4 SSD frant factor M2 Trusted Platform Module (TPM) 2.0 Card reader integrated X Operating temperature (T-T) 40 - 65 *C Onband graphics card model Not available Storage relative humidity (H-H) 0.90% On-board graphics card family Intel Iris Xe GraphicS Operating altitude 152 - 10668 m On-board graphics card family Intel Iris Xe GraphicS Operating altitude 152 - 10668 m On-board graphics card family Intel Iris Xe GraphicS <td></td> <td></td> <td></td> <td> 9</td>				9
StorageAC adapter frequency50/60 H2Total storage capacity*512 GBAC adapter input voltage100 - 240 VStorage meila*SSDAC adapter output voltage13.4 ATotal SSD capacity512 GBAC adapter output voltage19.5 VNumber of SSDs installed1SecurityVSSD capacity512 GBCable lock slotVSSD memory typeQLCCable lock slot typeVSSD instrateePCI Express 4.0Fingerprint readerVSSD for factorM2Trusted Platform Module (TPM)2.0SSD for factorXTrusted Platform Module (TPM)2.0Optical drive type*XPerating temperature (T-T)0.40 *COptical drive type*XStorage temperature (T-T)40 - 65 *COn-board graphics card*NOperating relative humidity (H+M)0.95%On-board graphics card*Intel Iris Xe GraphicsOperating relative humidity (H+M)0.95%On-board graphics card model*Intel Iris Xe GraphicsOperating altitude15.2 - 3048 mOn-board graphics card model*Intel Iris Xe GraphicsOperating altitude15.2 - 3048 mOn-board graphics card model*Natorecard meiler typeStatiability Competing altitude15.2 - 3048 mOn-board graphics card*Natorecard meiler typeStatiability Competing altitude15.2 - 3048 mOn-board graphics card*Natorecard meiler typeStatiability Competing altitude15.2 - 3048 mOn-board graphics card*Maxes<		5200 MT/s		SE M
Total storage capacityS12 GBAc adapter input votage100 - 240 VStorage mediaSDDAc adapter input votage100 - 240 VStoragentyS12 GBAc adapter output vortent3.3 ASDD ensorityS12 GBAc adapter output votage19.5 VNumber of SDD installed1SecurityStoragentySDD apacityS12 GBCable lock slot typeVedgeSDD interfacePCI Express 4.0Fingerprint readerImagentySDD from factorM.2Trusted Platform Module (TPM)ImagentyOptical drive typeXTrusted Platform Module (TPM)ImagentyCard reader integratedXOperating temperature (T-T)-40 - 65 °COn-board graphics card model*Not availableStorage temperature (T-T)-40 - 65 °COn-board graphics card model*Intel Iris Xe GraphicsOperating relative humidity (H-H)0 - 95%Discrete graphics card model*Intel Iris Xe GraphicsOperating altitude-15.2 - 3048 mOn-board graphics card model*Intel Iris Xe GraphicsOperating altitude-15.2 - 10668 mOn-board graphics card forderYOperating altitude-15.2 - 10668 mOn-board graphics card model*Intel Iris Xe GraphicsOperating altitude-15.2 - 10668 mOn-board graphics card forderYOperating altitude-15.2 - 10668 mOn-board graphics card model*Intel Iris Xe GraphicsStoragenty20Number of built-in speakers2Sustainability certificatesENERGY STAR,	Storage		• •	
Storage media*SSDAC adapter output current3.34 ATotal SSDs capacity512 GBAC adapter output voltage19.5 VSSD capacity512 GBGable lock slot/SSD memory typeQLCCable lock slot typeWedgeSSD interfacePCI Express 4.0Fingerprint reader/NVMe/Tusted Platform Module (TPM)/SSD form factorM.2Tusted Platform Module (TPM).0Optical drive typeXOperating temperature (T-T)0.40 °COptical drive typeVolta valiableStorage temperature (T-T)0.40 °COn-board graphics card*Volta valiableStorage reating relative humidity (H+H)0.90%On-board graphics card*Volta valiableStorage reating relative humidity (H+H)0.90%On-board graphics card*XOperating altitude0.52.3048 mOn-board graphics card model*Intel Iris Xe GraphicsOperating altitude0.52.3048 mOn-board graphics card*XOperating altitude0.52.3048 mOn-board graphics card*XOperating altitude1.52.3048 mOn-board graphics card*XOperating valoration0.66Audio chipReatex LC3204Sustainability cortificatesENERGY STAR, EPEAT Climate +Audio systemMaxxAudio ProSustainability cortificatesENERGY STAR, EPEAT Climate +Speakers mouteYYN1.51 gBuilt in incrophone2Wedit f Carono CortificatesENERGY STAR, EPEAT Climate + </td <td>-</td> <td>512 GB</td> <td></td> <td></td>	-	512 GB		
Total SSDs capacityS12 GBAC adapter output voltage19.5 VNumber of SSDs installo1SecuritySSD capacityS12 GBCable lock slot typeWedgeSSD interfaceQLCCable lock slot typeWedgeSSD interfaceM.2Trusted Platform Module (TPM)JOptical drive typeXTrusted Platform Module (TPM)JOptical drive typeXOptical ConditionsJOrtoad graphics card model *Not availableStorage temperature (TT)JOn-board graphics card model *Not availableStorage relative humidity (H+H)JOn-board graphics card familyIntel fits X GraphicsOperating altitude15.2 - 1066 mOn-board graphics card familyIntel fits X GraphicsOperating altitude15.2 - 1066 mOn-board graphics card familyIntel fits X GraphicsOperating altitude15.2 - 1066 mOn-board graphics card familyIntel fits X GraphicsOperating altitude15.2 - 1066 mOn-board graphics card model *Non-operating altitude15.2 - 1066 mOn-board graphics card model *Non-operating altitude15.2 - 1066 mOn-board graphics card model *Non-operating altitude15.2 - 1066 mOn-board GPUNone operating altitude16.6 GAudio stype mutancture	5 1 5			
SD capacityS12 GBGalculorSD memory typeQLCCable lock slot typeWedgeSD memory typeQLCCable lock slot typeWedgeSD interfacePCI Express 4.0Fingerprint reader✓NVMe✓Trusted Platform Module (TPM)✓SD form factorM.2Trusted Platform Module (TPM)✓.0Optical drive type *✓Operating temperature (T-T)0.40 °CCard reader integrated✓Operating temperature (T-T)0.40 °CDiscrete graphics card model *Not availableStorage temperature (T-T)0.40 °COn-board graphics card familyIntelNot availableOperating relative humidity (H+H)0.90%On-board graphics card familyIntel ins Xe GraphicsOperating relative humidity (H+H)0.90%On-board graphics card familyIntel ins Xe GraphicsOperating altitude15.2 · 3048 mOn-board graphics card familyIntel ins Xe GraphicsOperating altitude15.2 · 3048 mOn-board graphics card familyIntel ins Xe GraphicsOperating solution.66 GAudio systemMaxxAudio ProSustainability complianceINFGY STAR, EPEAT Climate +, EPEAT SilverSpeaker power2 WWeight & dimensions.172 cmSpeaker power2 WWeight & form).193 cmBuilt-in microphones2 WWeight & form).193 cmFront camera resolution (numeri)207 MPWeight & form).193 cmFront camera resolution (numeri)207 MPTell carbon				
SDC capacityS12 GBCable lock slot✓SD memory typeQLCCable lock slot typeWedgeSD memory typeQLCCable lock slot typeWedgeSDS interfacePCI Express 4.0Fingerprint reader✓NWe✓Trusted Platform Module (TPM)✓SDS form factorM.2Trusted Platform Module (TPM)✓Optical drive type *XPerational conditions0.0Card reader integratedXOperating temperature (T-T)0.40 °COn-board graphics card model *Not availableStorage temperature (T-T)40 · 65 °COn-board graphics card model *Not availableStorage relative humidity (H+H)0.95%On-board graphics card model *XOperating relative humidity (H+H)0.95%On-board graphics card model *XOperating altitude15.2 · 10668 mOn-board graphics card model *Intel lris Xe GraphicsOperating altitude15.2 · 10668 mOn-board graphics card model *MaxXAudio ProSustainability compliance✓Audio chipRealtek ALC3204Sustainability compliance✓Audio systemMaxXAudio ProSustainability compliance✓Speaker power2Wedet & dimensions1.77 cmSpeaker power2Wedet & dimensions1.93 cmBuilt-In microphones2Weight *1.93 cmFront camera resolution (numeri)2.07 MPWeight *1.93 cmFront camera resolution (numeri)2.07 MPTeal carbon	Number of SSDs installed	1	Security	
SSD memory typeQLCCable lock slot typeWedgeSSD interfacePCI Express 4.0Fingerprint reader✓SNMe✓Trusted Platform Module (TPM)✓SD form factorM.2Trusted Platform Module (TPM)2.0Optical drive type *✓ Porating tender Module (TPM) 2.0Card reader integrated✓ Porating tender Module (TPM) 0.0 °CCard reader integrated✓Porating tengerature (T-T)-40.65 °COn-board graphics card *✓Operating relative humidity (H+H)0.90%On-board graphics card *✓Operating relative humidity (H+H)0.90%On-board graphics card *✓Operating altitude-15.2 - 304B mOn-board graphics card *✓Operating altitude-15.2 - 304B mOn-board graphics card *✓Operating altitude-15.2 - 1066B mOn-board graphics card *✓Operating altitude-15.2 - 304B mOn-board graphics card *✓Operating altitude-15.2 - 1066B mOn-board graphics card *✓Operating altitude-15.2 - 1066B mOn-board graphics card *MaxxAudio POSustainability-15.2 - 1066B mAudio stypeRealtex ALC3204SustainabilitySustainabilityAudio systemMaxxAudio POSustainability compliance✓Speaker power2Sustainability compliance✓Port camera resolution (numeric)2.0 MPEpidt (front)1.17 cmFront camera resolution (numeric)2.01M	SSD capacity	512 GB	•	1
SbD interface PCI Express 4.0 Fingerprint reader Image PCI Express 4.0 NWMe Image PCI Express 4.0 Fingerprint reader Image PCI Express 4.0 SbD form factor M.2 Trusted Platform Module (TPM) Image PCI Express 4.0 SbD form factor M.2 Trusted Platform Module (TPM) 2.0 Graphics X Operating temperature (T-T) 40-65 °C On-board graphics card model * Not available Storage relative humidity (H-H) 0.90% On-board graphics card model * Not available Storage relative humidity (H-H) 0.95% On-board graphics card model * Intel Iris Xe Graphics Operating altitude 15.2 - 3048 m On-board graphics card model * Intel Iris Xe Graphics Operating vibration 0.66 G Audio chip Realtek ALC3204 Sustainability compliance Image PC STAR, EPEAT Climate +, EPEAT Sliver Speaker power 2 Sustainability certificates EMERGY STAR, EPEAT Climate +, EPEAT Sliver Speaker power 2 Weight & dimensions 22.2 mm Number of microphone 2 With 1.93 cm		-		
NVMeVTrusted Platform Module (TPM)VSSD form factorM.2.aTrusted Platform Module (TPM)2.0Optical drive type *XTrusted Platform Module (TPM)2.0Card reader integratedXOperating temperature (T-T)0.40 °CGraphisNot availableStorage temperature (T-T)40 - 65 °COn-board graphics card model *Not availableStorage temperature (T-T)0.90%On-board GPU manufacturerIntelStorage temperature (T-T)0.95%On-board graphics card *XOperating altitude15.2 - 3048 mOn-board graphics card familyIntel Iris Xe GraphicsNon-operating altitude15.2 - 10668 mOn-board graphics card model *Intel Iris Xe GraphicsOperating shock140 GAudio chipRealtek ALC3204Sustainability complianceVAudio systemMaxxAudio ProSustainability certificatesENEGY STAR, EPEAT Climate +, EPEAT SilverSpeaker snamufacturerYYYYSpeaker snamufacturerVYYYBuilt-In microphone2YYYFront camera esolution (numeric)2.07 MPYYYFront camera resolution (numeric)2.07 MPYYYVideo capturing speed30 fpsCarbon emissions, nandrafcuring2.3Front camera resolution (numeric)2.07 MPTotal carbon footprint (Kg of CO2e)111Video capturing speed30 fpsCarbon emissions, nandrafcuring2.3<		•		5
Optical drive type *XTrusted Platform Module (TPM) version2.0Card reader integratedXOperational conditionsOperating temperature (T-M)0.40 °CDiscrete graphics card *Not availableStorage temperature (T-T)40 · 65 °COn-board graphics card */Operating temperature (T-M)0.90%On-board GPU manufacturerIntelStorage relative humidity (H-H)0.90%Discrete graphics card *XOperating relative humidity (H-H)0.95%On-board graphics card *XOperating altitude15.2 · 3048 mOn-board graphics card familyIntel Iris Xe GraphicsOperating shock1406On-board graphics card modelIntel Iris Xe GraphicsOperating vibration0.666 GAudio chipRealtek ALC3204Sustainability complianceAudio systemMaxAudio ProSustainability complianceSpeaker smanufacturerWavesSustainability certificatesEPERT SilverSpeaker smanufactureVavesWidth322.2 mmBuilt-in microphone2Width322.2 mmBuilt-in microphone2.07 MPWeight * dimensions19.4 mmFront camera resolution (numeric)1.902 NID80 pxielsCarbon emissions, manufacturingFront camera resolution (numeric)0.07 MPWeight *1.5 kgFront camera resolution (numeric)0.07 MPGarbon emissions, manufacturingVideo capturing speed30 fpsGarbon emissions, logistic (kg of C02e)111Video capturing s				1
Card reader integrated × Operational conditions Card reader integrated × Operating temperature (T-T) 40 - 65 °C Discrete graphics card model * Not available Storage temperature (T-T) 40 - 65 °C On-board GPU manufacturer Intel Storage temperature (T-T) 40 - 65 °C Discrete graphics card * ✓ Operating relative humidity (H-H) 0 - 90% On-board GPU manufacturer Intel Storage relative humidity (H-H) 0 - 90% Discrete graphics card * × Operating altitude -15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Non-operating altitude -15.2 - 10668 m On-board graphics card model * Non Auxaudio Pro Sustainability compliance ✓ Audio chip Realtek ALC3204 Sustainability compliance ✓ Number of built-in speakers 2 Sustainability compliance ✓ Speaker power 2 W Sustainability certificates ENERCY STAR, EPEAT Climate +, EPEAT Silver Speaker power 2 W Width 322.2 mm 2 Number of microphones 2 Vidth 322.2 mm Front camera ✓ Height (rear) 1.93 cm Front camera resolution (numeric) 2.07 MP Vidth <td></td> <td></td> <td></td> <td>2.0</td>				2.0
Graphics Operational conditions Discrete graphics card model * Not available Storage temperature (T-T) 0 - 40 °C On-board graphics card * ✓ Operating temperature (T-T) -40 - 65 °C On-board GPU manufacturer Intel Storage relative humidity (H-H) 0 - 90% On-board GPU manufacturer Intel Storage relative humidity (H-H) 0 - 90% On-board graphics card * X Operating altitude -15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Non-operating altitude -15.2 - 10668 m On-board graphics card model * Intel Iris Xe Graphics Operating shock 140 G Audio chip Realtek ALC3204 Sustainability ENERGY STAR, EPEAT Climate +, EPEAT Sliver Speakers manufacturer Waves Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Sliver Speakers mover 2 W Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Sliver Speakers mover 2 W Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Sliver Speakers mower 2 W				
Discrete graphics card model × Not available Storage temperature (1-1) 0 - 40 °C On-board graphics card * ✓ Operating temperature (1-1) 40 - 65 °C On-board GPU manufacturer Intel Storage temperature (1-1) 0 - 99% On-board GPU manufacturer Intel Storage relative humidity (H-H) 0 - 95% Discrete graphics card * ✓ Operating altitude - 15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Operating altitude - 15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Operating shock - 140 G Audio Chip Realtek ALC3204 Sustainability Audio system MaxxAudio Pro Sustainability compliance ✓ Sustainability compliance ✓ Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Silver Speaker manufacturer Waves Speaker power 2 W Built-in microphone ✓ Number of microphones 2 Number of microphones 2 Front camera resolution (numeric) 2.07 MP Front camera fib type Full HD Front camera resolution (numeric) 2.07 MP Front camera fib type Full HD Front camera fib type Ful	-	~	Operational conditions	
On-board graphics card *✓Operating relative humidity (H-H) Operating relative humidity (H-H) Operating relative humidity (H-H) Operating relative humidity (H-H) Operating altitude0 - 90% Operating relative humidity (H-H) Operating relative humidity (H-H) 	•	Net available		
On-board GPU manufacturer Intel Subcraft graphics card * × Operating altitude 0 - 95% Discrete graphics card * × Operating altitude -15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Non-operating altitude -15.2 - 10668 m On-board graphics card model * Intel Iris Xe Graphics Operating shock 140 G Audio Verating shock 140 G Audio system Realtek ALC3204 Sustainability 0-66 G Number of built-in speakers 2 Sustainability compliance ✓ Speakers manufacturer Waves Sustainability compliance ✓ Speaker power 2 W Weight & dimensions Sustainability compliance ✓ Number of microphones 2 Width 322.2 mm Speaker power 2 W Built-in microphone 2 Width 322.2 mm Speaker power 2.0 M Front camera ✓ Height (front) 1.77 cm Speaker power 1.93 cm Front camera resolution (numeric) 2.07 MP Weight *				
Discrete graphics card * X Operating altitude -15.2 - 3048 m On-board graphics card family Intel Iris Xe Graphics Non-operating altitude -15.2 - 10668 m On-board graphics card model * Intel Iris Xe Graphics Operating shock 140 G Audio Uperating shock 140 G Audio chip Realtek ALC3204 Sustainability Audio system MaxxAudio Pro Sustainability compliance / Number of built-in speakers 2 Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Silver Speakers manufacturer Waves Sustainability certificates ENERGY STAR, EPEAT Climate +, EPEAT Silver Speaker power 2 W Width 322.2 mm Number of microphone 4 Width 322.2 mm Number of microphones 2 Width 322.2 mm Rumar 140 G 190 nm 190 nm Front camera resolution (numeric) 2.07 MP Weight & dimensions 191 nm Front camera resolution (numeric) 1920 x 1080 pixels Carbon footprint (kg of CO2e) 111 Front camera resolution (numeric) 1920 x 1080 pixels Carbon emissions, logistics (kg of CO2e) 111 Front camera HD type Full HD Carbon emissions, logistics (kg of CO2e) <				
On-board graphics card family On-board graphics card model* Intel Iris Xe Graphics Intel Iris Xe Graphics Non-operating altitude Operating shock 140 G Audio Uperating shock 140 G Audio chip Realtek ALC3204 Sustainability	Discrete graphics card *	×	.	
On-board graphics card model* Intel Iris Xe Graphics Operating shock 140 G Audio Operating vibration 0.66 G Audio chip Realtek ALC3204 Sustainability Image: Comparison of Compar	On-board graphics card family	Intel Iris Xe Graphics		
Audio chipRealtek ALC3204SustainabilityAudio systemMaxxAudio ProSustainability complianceINumber of built-in speakers2Sustainability certificatesENERGY STAR, EPEAT Climate +, EPEAT SilverSpeakers manufacturerWavesSustainability certificatesENERGY STAR, EPEAT Climate +, EPEAT SilverSpeaker power2Weight & dimensions322.2 mmBuilt-in microphoneIVidth322.2 mmNumber of microphones2Veight (front)1.94 mmCameraIHeight (front)1.93 cmFront cameraIKeight (rear)1.93 cmFront camera resolution (numeric)2.07 MPWeight *1.5 kgFront camera resolution1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Video capturing speed30 fpsGarbon emissions, manufacturing (kg of CO2e)32Privacy cameraICarbon emissions, logistics (kg of of CO2e)4Privacy typeFrivacy shutterCarbon emissions, energy usage for CO2e32Top Wi-Fi standard *Wi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of cO2e)32	On-board graphics card model *	Intel Iris Xe Graphics		140 G
Audio systemMaxxAudio ProSustainability complianceImage: Complex co	Audio		Operating vibration	0.66 G
Number of built-in speakers2Sustainability certificatesFNERGY STAR, EPEAT Climate +, EPEAT SilverSpeaker smanufacturerWavesSustainability certificatesENERGY STAR, EPEAT Climate +, EPEAT SilverSpeaker power2 WWeight & dimensions322.2 mmBuilt-in microphoneImage: Speaker powerSpeaker powerSpeaker powerNumber of microphones2Width322.2 mmNumber of microphones2PepthSignal PiperCameraImage: Speaker powerSpeaker powerSpeaker powerFront cameraImage: Speaker powerSpeaker powerSpeaker powerFront cameraImage: Speaker powerSpeaker powerSpeaker powerFront camera resolution (numeric)Sort PowerHeight (rear)1.93 cmFront camera resolution (numeric)Sort PowerStation footprintSpeaker powerFront camera resolution (numeric)Sort PowerSpeaker powerSpeaker powerFront camera HD typeFull HDTotal carbon footprint (kg of CO2e)Speaker powerInfrared (IR) cameraImage: Speaker powerStation emissions, nanufacturing (kg of CO2e)Speaker powerPrivacy cameraImage: Speaker powerScathon emissions, logistics (kg of cO2e)Speaker powerPrivacy typePrivacy shutterScathon emissions, energy usage (kg of CO2e)Speaker powerNetworkSpeaker powerSpeaker powerSpeaker powerSpeaker powerTop Wi-Fi standard *Wi-Fi 6E (802.11ax)Carbon emissions, end-of-life (k	Audio chip	Realtek ALC3204	Sustainability	
Speakers manufacturerWavesSustainability certificatesEPEAT Silver EPEAT SilverSpeaker power2 WBuilt-in microphone✓Number of microphones2Camera2Front camera✓Front camera resolution (numeric)2.07 MPFront camera resolution (numeric)2.07 MPFront camera resolution (numeric)2.07 MPFront camera resolution (numeric)1.02 x 1080 pixelsFront camera resolution (numeric)1.02 x 1080 pixelsFront camera HD typeFull HDVideo capturing speed30 fpsInfrared (IR) camera✓Privacy camera✓Privacy typePrivacy shutterPrivacy typePrivacy shutterNetworkCarbon emissions, energy usage (response) (Co2e)Privacy typeWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of CO2e)Pui-Fi standard *Wi-Fi 6E (802.11ax)	Audio system	MaxxAudio Pro	Sustainability compliance	1
Speakers manufacturerWavesEPEAT SilverSpeaker power2 WBuilt-in microphoneImage: Speaker powerNumber of microphonesImage: Speaker power2WithNumber of microphones2CameraImage: Speaker powerFront cameraImage: Speaker powerFront camera resolution (numeric)2.07 MPFront camera resolution (numeric)2.07 MPFront camera resolution (numeric)2.07 MPFront camera resolution (numeric)1.020 x 1080 pixelsFront camera resolution (numeric)2.07 MPVideo capturing speed30 fpsInfrared (IR) cameraImage: Speaker powerInfrared (IR) cameraImage: Speaker powerPrivacy cameraImage: Speaker powerPrivacy typePrivacy shutterImage: Speaker powerCarbon emissions, energy usage (speaker power)NetworkSpeaker powerTop Wi-Fi standard *Wi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of power)2Speaker powerCarbon emissions, end-of-life (kg of power)Speaker powerSpeaker power<	•		Sustainability certificates	
Built-in microphoneImage: A constraint of the second s	•			EPEAT Silver
Number of microphones2Width322.2 mmDepthDepth219.4 mmCameraImage: Composition of the system	• •		Weight & dimensions	
CameraDepth219.4 mmCameraHeight (front)1.77 cmFront cameraImage: Composition (numeric)Image: Composition (numeric)Image: Composition (numeric)Front camera resolution (numeric)2.07 MPWeight *1.5 kgFront camera resolution (numeric)1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)82Privacy cameraImage: Composition (kg of CO2e)4Privacy typePrivacy shutterCarbon emissions, energy usage (kg of CO2e)23NetworkWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of CO2e)2	•			
Front cameraImagine (indit)InformationFront camera resolution (numeric)2.07 MPWeight *1.5 kgFront camera resolution (numeric)1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)82Privacy cameraImage for the standard *Carbon emissions, energy usage (kg of CO2e)4NetworkCarbon emissions, energy usage (kg of CO2e)2	•		•	
Front camera resolution (numeric)2.07 MPWeight *1.5 kgFront camera resolution1920 x 1080 pixelsCarbon footprint111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)82Infrared (IR) camera✓Carbon emissions, logistics (kg of CO2e)4Privacy camera✓Carbon emissions, energy usage (kg of CO2e)23NetworkWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of CO2e)2		1	-	
Front camera resolution1920 x 1080 pixelsCarbon footprintFront camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)82Infrared (IR) camera✓Carbon emissions, logistics (kg of CO2e)4Privacy camera✓Carbon emissions, energy usage (kg of CO2e)23NetworkWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of Carbon			-	
Front camera HD typeFull HDCarbon rootprintVideo capturing speed30 fpsTotal carbon footprint (kg of CO2e)111Infrared (IR) camera✓Carbon emissions, manufacturing (kg of CO2e)82Privacy camera✓Carbon emissions, logistics (kg of CO2e)4Privacy typePrivacy shutterCarbon emissions, energy usage (kg of CO2e)23NetworkWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of CO2e)2			-	1.5 Kg
Video capturing speed30 fpsTotal carbon footprint (kg of CO2e)111Infrared (IR) camera✓Carbon emissions, manufacturing (kg of CO2e)82Privacy camera✓Carbon emissions, logistics (kg of CO2e)4Privacy typePrivacy shutterCarbon emissions, energy usage (kg of CO2e)23NetworkWi-Fi 6E (802.11ax)Carbon emissions, end-of-life (kg of Carbon emissions,		•	•	111
Infrared (IR) camera Image: With a standard with				111
Privacy camera✓Carbon emissions, logistics (kg of CO2e)4Privacy typePrivacy shutterCarbon emissions, energy usage (kg of CO2e)23NetworkCarbon emissions, end-of-life (kg of Carbon emissione, end-of	Infrared (IR) camera	4		82
Privacy type Privacy shutter CO2e) Network Carbon emissions, energy usage (kg of CO2e) 23 Top Wi-Fi standard * Wi-Fi 6E (802.11ax) Carbon emissions, end-of-life (kg of 2)	Privacy camera	1		Λ
Top Wi-Fi standard * Wi-Fi 6E (802.11ax) Carbon emissions, end-of-life (kg of 2	Privacy type	Privacy shutter	CO2e)	
Top Wi-Fi standard * Wi-Fi 6E (802.11ax) Carbon emissions, end-of-life (kg of	Network		Carbon emissions, energy usage (kg of CO2e)	23
- /	Top Wi-Fi standard *	Wi-Fi 6E (802.11ax)		2
			CO2e)	2

Network

Wi-Fi standards

Mobile network connection * Wi-Fi data rate (max) Antenna type WLAN controller model 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax) 2400 Mbit/s 2x2 Intel Wi-Fi 6E AX211

Carbon footprint Total carbon emissions, w/o use phase (kg of CO2e) 88 PAIA version GaBi verison1 Packaging content Cables included



5397184875544

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.