

## iiyama LH5041UHS-B2AG Signage Display Digital signage flat panel 127 cm (50") LCD 500 cd/m<sup>2</sup> 4K Ultra HD Black 24/7

Brand : iiyama

Product code: LH5041UHS-B2AG

Product name : LH5041UHS-B2AG

iiyama LH5041UHS-B2AG. Product design: Digital signage flat panel. Display diagonal: 127 cm (50"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Operating hours (hours/days): 24/7. Product colour: Black



Display		Design	
Panel type	VA	Bezel width (side)	1.39 cm
Display diagonal *	127 cm (50")	Bezel width (top)	1.39 cm
Display technology *	LCD	Bezel colour	black, glossy
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	500 cd/m <sup>2</sup>	Purpose *	Commercial
HD type *	4K Ultra HD	On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Russian
Touchscreen *	✗	Operating hours (hours/days)	24/7
Native aspect ratio	16:9	HDCP	✓
Response time	9.5 ms	HDCP version	2.2
Contrast ratio (typical)	5000:1	Mean time between failures (MTBF)	50000 h
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	115 W
Display number of colours	1.07 billion colours	Power consumption (standby) *	0.5 W
Pixel pitch	0.285 x 0.285 mm	Power consumption (off)	0.3 W
Active display area (W x H)	1096 x 616.4 mm	Energy efficiency class (SDR)	G
Display diagonal (metric)	125.7 cm	Energy consumption (SDR) per 1000 hours	115 kWh
Horizontal scan range	30 - 80 kHz	AC input voltage	100 - 240 V
Haze rate	25%	AC input frequency	50/60 Hz
Ports & interfaces		Energy efficiency scale	A to G
HDMI ports quantity *	3	Computer system	
DVI port *	✗	Computer system *	✗
VGA (D-Sub) input ports	1	Built-in processor *	✗
USB port *	✓	Weight & dimensions	
USB ports quantity	1	Width (with stand)	1122.5 mm
USB version	2.0	Depth (with stand)	55 mm
Ethernet LAN *	✓	Height (with stand)	643.5 mm
Ethernet LAN (RJ-45) ports	1	Weight (with stand)	11.1 kg
Wi-Fi *	✗		
Audio (L/R) in	1		
RS-232 interface	✓		

Ports & interfaces		Packaging data	
RS-232C	✓	Package width	1261 mm
Remote (IR) input	1	Package depth	132 mm
<b>Audio</b>		Package height	761 mm
Built-in speaker(s) *	✓	<b>Packaging content</b>	
Number of built-in speakers	2	Cables included	HDMI, Power, RS-232
RMS rated power	20 W	<b>Operational conditions</b>	
<b>Design</b>		Operating temperature (T-T)	0 - 40 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	-20 - 60%
Placement supported *	Indoor	<b>Certificates</b>	
Orientation	Horizontal/Vertical	Certification	CE, TÜV-Bauart, RoHS support, ErP, WEEE, REACH, UKCA
Product colour *	Black		
VESA mounting *	✓		
Panel mounting interface	400 x 400 mm		
Bezel width (bottom)	1.49 cm		



4948570123537

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date