

DELL Latitude 7450 Intel Core Ultra 7 165U Laptop 35.6 cm (14") Full HD+ 32 GB LPDDR5x-SDRAM 512 GB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey

Brand : DELL Product family: Latitude Product code: R4XDN

Product name: 7450

- Windows 11 Pro 64-bit
- Intel Core Ultra 7 165U (12MB Cache)
- 35.6 cm (14") Full HD+ 1920 x 1200 WVA
- 32GB LPDDR5x-SDRAM & 512GB SSD

Intel Core Ultra 7 165U (12MB Cache), 32GB LPDDR5x-SDRAM, 512GB SSD, 35.6 cm (14") Full HD+ 1920 x 1200 WVA, Intel Graphics, WLAN, Webcam, Windows 11 Pro 64-bit

DELL Latitude 7450 Intel Core Ultra 7 165U Laptop 35.6 cm (14") Full HD+ 32 GB LPDDR5x-SDRAM 512 GB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey:

Work from anywhere with our most intelligent and secure business laptops sustainably designed for productivity on the go.

DELL Latitude 7450. Product type: Laptop, Form factor: Clamshell. Processor family: Intel Core Ultra 7, Processor model: 165U. Display diagonal: 35.6 cm (14"), HD type: Full HD+, Display resolution: 1920 x 1200 pixels. Internal memory: 32 GB, Internal memory type: LPDDR5x-SDRAM. Total storage capacity: 512 GB, Storage media: SSD. On-board graphics card model: Intel Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey. Weight: 1.33 kg











Design		Network	
Product type * Product colour * Form factor * Housing material Market positioning Intel® vPro™ Platform Eligibility	Laptop Grey Clamshell Aluminium Business	Wi-Fi standards Mobile network connection * Antenna type WLAN controller model	802.11a, 802.11b, 802.11g, Wi-Fi 5 (802.11ac), Wi-Fi 6E (802.11ax), Wi Fi 7 (802.11be) 2x2 Intel Wi-Fi 7 BE200
Display		WLAN controller manufacturer Ethernet LAN	Intel
Display diagonal * Display resolution *	35.6 cm (14") 1920 x 1200 pixels	Bluetooth Near Field Communication (NFC)	<i>'</i>
Touchscreen *	X	Ports & interfaces	
HD type Panel type LED backlight Native aspect ratio Anti-glare screen Display brightness Pixel pitch Pixel density RGB colour space Colour gamut Display response rise/fall	Full HD+ WVA 16:10 250 cd/m² 0.157 x 0.157 mm 162 ppi NTSC 45% 35 ms	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port Charging port type USB Type-C DisplayPort Alternate Mode USB Power Delivery	2 1 2.1 2 ✓ USB Type-C ✓
Maximum refresh rate	60 Hz	Performance	
Contrast ratio (typical)	800:1	Ambient light sensor	✓
Processor		Keyboard	
Processor manufacturer * Processor family * Processor generation Processor model *	Intel Intel Core Ultra 7 Intel® Core™ Ultra (Series 1) 165U	Pointing device Keyboard language Numeric keypad * Keyboard backlit	Clickpad UK English

Keyboard backlit

_			
Processor		Keyboard	
Processor cores	12	Keyboard number of keys	80
Processor threads	14	Software	
Processor boost frequency Performance cores	4.9 GHz 2	Operating system architecture	64-bit
Efficient cores	8	Operating system language	German, Dutch, English, French, Italian
Low Power Efficient-cores Performance-core Max Turbo	2	Trial software	No Microsoft Office License Included 30 day Trial Offer Only
Frequency Efficient-core Max Turbo Frequency	4.9 GHz 3.8 GHz	Operating system installed *	Windows 11 Pro
Low Power Efficient-core Max Turbo	2.1 GHz	Battery	
Frequency		Number of battery cells	3
Performance-core base frequency	1.7 GHz	Battery capacity *	57 Wh
Efficient-core base frequency	1.2 GHz	Battery voltage	11.4 V
Low Power Efficient-core Base Frequency	700 MHz	Browsing time (Wi-Fi)	4 h
Processor cache	12 MB	Battery recharge time	4 h
Processor cache type	Smart Cache	Fast charging Battery charge indicator	1
Processor base power	15 W	Battery weight	227 g
Maximum turbo power	57 W	, ,	227 g
Neural processor unit (NPU)		Power	
Neural processor unit (NPU)	Intel Al Boost	AC adapter power	65 W
•	1.4 GHz	AC adapter frequency	50 - 60 Hz
Maximum frequency NPU	1.4 GHZ ✓	AC adapter input voltage	100 - 240 V
Sparsity support Windows Studio effects support	V	USB charging voltage	20,5,9,15 V
Al datatype support on NPU	FP16, FP32, Int8	USB charging current	3 A
Al software frameworks supported	DirectML, ONNX RT, OpenVINO,	Security	
by NPU	Windows ML	Cable lock slot	1
Memory		Cable lock slot type	Wedge
	32 GB	Fingerprint reader	✓
Internal memory *	LPDDR5x-SDRAM	Smart card reader	✓
Internal memory type	On-board	Trusted Platform Module (TPM)	✓
Memory form factor	On-board	Trusted Platform Module (TPM)	2.0
	22 CB		20
Maximum internal memory *	32 GB	version	2.0
Memory channels	Dual-channel		2.0
Memory channels Memory data transfer rate		version	0 - 35 °C
Memory channels Memory data transfer rate Storage	Dual-channel 6400 MT/s	version Operational conditions	
Memory channels Memory data transfer rate Storage Total storage capacity *	Dual-channel 6400 MT/s 512 GB	version Operational conditions Operating temperature (T-T)	0 - 35 °C
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media *	Dual-channel 6400 MT/s 512 GB SSD	Operational conditions Operating temperature (T-T) Storage temperature (T-T)	0 - 35 °C -40 - 65 °C
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity	Dual-channel 6400 MT/s 512 GB SSD 512 GB	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C -40 - 65 °C 10 - 90%
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95%
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type *	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model *	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card *	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X Not available ✓	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X Not available ✓ Intel	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card *	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X Not available ✓ Intel	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G ✓ ENERGY STAR, EPEAT Climate +, TCO
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card model * On-board graphics card model * Audio	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 ✓ M.2 X Not available ✓ Intel X Intel Graphics	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card model * Audio Audio chip	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel X Intel Graphics	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth Height (front)	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio chip Number of built-in speakers	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel Intel Graphics Realtek ALC3281 4	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm 1.82 cm
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio chip Number of built-in speakers Speaker power	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel X Intel Graphics	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth Height (front)	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio chip Number of built-in speakers	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel Intel Graphics Realtek ALC3281 4 2 W	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm 1.82 cm
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio chip Number of built-in speakers Speaker power Built-in microphone Camera	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel Intel Graphics Realtek ALC3281 4 2 W	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth Height (front) Height (rear) Weight *	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm 1.82 cm
Memory channels Memory data transfer rate Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board graphics card * On-board graphics card model * Audio Audio chip Number of built-in speakers Speaker power Built-in microphone	Dual-channel 6400 MT/s 512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0 M.2 X Not available Intel Intel Graphics Realtek ALC3281 4 2 W	version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration Certificates Wi-Fi certified Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth Height (front) Height (rear) Weight * Carbon footprint	0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G V ENERGY STAR, EPEAT Climate +, TCO 313 mm 222.8 mm 1.71 cm 1.82 cm 1.33 kg

Camera		Carbon footprint	
Front camera HD type Video capturing speed Infrared (IR) camera Privacy camera Privacy type	Full HD 30 fps ✓ ✓ Privacy shutter	Carbon emissions, manufacturing (kg of CO2e)	86
		Carbon emissions, logistics (kg of CO2e)	5
		Carbon emissions, energy usage (kg of CO2e)	18
Network		Carbon emissions, end-of-life (kg of CO2e)	2
Top Wi-Fi standard *	Wi-Fi 7 (802.11be)	Total carbon emissions, w/o use phase (kg of CO2e)	92
		PAIA version	GaBi verison1
		Packaging content	
		Cables included	AC



5397184873199

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.