

GIGABYTE B650 EAGLE Motherboard - Supports AMD Ryzen 9000 CPUs, 12+2+2 Phases Digital VRM, up to 7600MHz DDR5 (OC), 1xPCIe 5.0 + 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen2

Brand : GIGABYTE

Product code: B650 EAGLE


Product name : B650 EAGLE Motherboard - Supports AMD Ryzen 9000 CPUs, 12+2+2 Phases Digital VRM, up to 7600MHz DDR5 (OC), 1xPCIe 5.0 + 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen2



B650 EAGLE Motherboard - Supports AMD Ryzen 9000 CPUs, 12+2+2 Phases Digital VRM, up to 7600MHz DDR5 (OC), 1xPCIe 5.0 + 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen2

[GIGABYTE B650 EAGLE Motherboard - Supports AMD Ryzen 9000 CPUs, 12+2+2 Phases Digital VRM, up to 7600MHz DDR5 \(OC\), 1xPCIe 5.0 + 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen2:](#)

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge



| Processor | | Rear panel I/O ports | |
|--|---|-------------------------------------|--|
| Processor manufacturer * | AMD | HDMI version | 2.1 |
| Processor socket * | Socket AM5 | DisplayPorts quantity | 1 |
| Compatible processor series * | AMD Ryzen™ 5, AMD Ryzen 7 7th Gen, AMD Ryzen 9 7th Gen | DisplayPort version | 1.4 |
| Supported processor sockets | Socket AM5 | Headphone outputs | 3 |
| Maximum internal memory supported by processor | 192 GB | Microphone in | ✓ |
| | | WiFi-AP antenna jack | 2 |
| | | USB connector type | USB Type-A, USB Type-C |
| Memory | | Network | |
| Supported memory types * | DDR5-SDRAM | Ethernet LAN | ✓ |
| Number of memory slots * | 4 | Ethernet interface type | Gigabit Ethernet |
| Memory slots type | DIMM | Wi-Fi * | ✗ |
| Memory channels | Dual-channel | | |
| Non-ECC | ✓ | Features | |
| Supported memory clock speeds | 4400,4800,5200,5600,6000,6200,6400,6600,6800,7000,7200,7600 MHz | Motherboard chipset * | AMD B650 |
| Supported memory clock speed (max) | 7600 MHz | Audio chip | Realtek ALC897 |
| Maximum internal memory * | 192 GB | Audio output channels * | 7.1 channels |
| Supported memory module capacities | 1GB, 2GB, 4GB, 8GB, 12GB, 16GB, 32GB, 40GB, 48GB | Product colour | Brown |
| Unbuffered memory | ✓ | PC health monitoring | Fan, Temperature, Voltage, Water cooling |
| Storage controllers | | Component for * | PC |
| Supported storage drive types | HDD & SSD | Motherboard form factor * | ATX |
| Supported storage drive interfaces * | M.2, PCI Express 4.0, SATA III | Motherboard chipset family * | AMD |
| Number of HDDs supported | 4 | Cooling type | Active |
| Number of storage drives supported | 7 | Power source type | ATX |
| RAID support | ✓ | Windows operating systems supported | Windows 10 x64, Windows 11 x64 |
| RAID levels | 0, 1, 10 | Expansion slots | |
| Graphics | | PCI Express x16 slots | 3 |
| Parallel processing technology support * | Not supported | Number of M.2 (M) slots | 3 |
| Maximum resolution | 4096 x 2160 pixels | BIOS | |
| HDCP | ✓ | BIOS type * | UEFI AMI |
| DirectX version | 12.0 | BIOS memory size | 256 Mbit |
| Internal I/O | | | |
| USB 2.0 connectors * | 3 | | |

| Internal I/O | | BIOS | |
|---|---|--|--|
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 1 | ACPI version | 5.0 |
| USB 3.2 Gen 2 (3.1 Gen 2) connectors * | 1 | Clear CMOS jumper | ✓ |
| Number of SATA III connectors * | 4 | Clear CMOS button | ✓ |
| Total number of SATA connectors | 4 | Desktop Management Interface (DMI) version | 2.7 |
| Front panel audio connector | ✓ | System Management BIOS (SMBIOS) version | 2.7 |
| Front panel connector | ✓ | Logistics data | |
| ATX Power connector (24-pin) | ✓ | Country of origin | China |
| CPU fan connector | ✓ | Products per shipping (inner) case | 1 pc(s) |
| EPS power connector (8-pin) | ✓ | Battery | |
| TPM connector | ✓ | Battery weight | 3 g |
| Serial port headers | 1 | Lithium weight per battery | 0.07 g |
| 12V power connector | ✓ | Number of battery cells | 1 |
| RGB LED pin header | ✓ | Battery technology | Lithium-Manganese Dioxide (LiMnO2) |
| Rear panel I/O ports | | Battery type | CR2032 |
| USB 2.0 ports quantity * | 6 | Packaging data | |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * | 1 | Package width | 335 mm |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 2 | Package depth | 270 mm |
| Ethernet LAN (RJ-45) ports * | 1 | Package height | 80 mm |
| HDMI ports quantity * | 1 | Package weight | 1.82 kg |
| | | Weight & dimensions | |
| | | Width | 305 mm |
| | | Depth | 244 mm |
| | | Height | 35 mm |
| | | Packaging content | |
| | | Cables included | SATA |
| | | Batteries included | ✓ |
| | | Bundled software | Norton Internet Security (OEM version) LAN bandwidth management software |
| | | Technical details | |
| | | Warranty period | 3 year(s) |



4719331863081

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date