

DELL Latitude 9450 2-in-1 Intel Core Ultra 7 165U Hybrid (2-in-1) 35.6 cm (14") Touchscreen Quad HD+ 32 GB LPDDR5x-SDRAM 1 TB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey

Brand : DELL Product family: Latitude Product code: WN9K9

Product name: 9450 2-in-1

- Windows 11 Pro 64-bit
- Intel Core Ultra 7 165U (12MB Cache)
- 35.6 cm (14") Quad HD+ 2560 x 1600 IPS Touch
- 32GB LPDDR5x-SDRAM & 1000GB SSD

Intel Core Ultra 7 165U (12MB Cache), 32GB LPDDR5x-SDRAM, 1000GB SSD, 35.6 cm (14") Quad HD+ 2560 \times 1600 IPS Touch, Intel Graphics, WLAN, Webcam, Windows 11 Pro 64-bit

DELL Latitude 9450 2-in-1 Intel Core Ultra 7 165U Hybrid (2-in-1) 35.6 cm (14") Touchscreen Quad HD+ 32 GB LPDDR5x-SDRAM 1 TB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey:

Work from anywhere with our most intelligent and secure business laptops sustainably designed for productivity on the go.

DELL Latitude 9450 2-in-1. Product type: Hybrid (2-in-1), Form factor: Convertible (Folder). Processor family: Intel Core Ultra 7, Processor model: 165U. Display diagonal: 35.6 cm (14"), HD type: Quad HD+, Display resolution: 2560 x 1600 pixels, Touchscreen. Internal memory: 32 GB, Internal memory type: LPDDR5x-SDRAM. Total storage capacity: 1 TB, Storage media: SSD. On-board graphics card model: Intel Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey











Design		Camera	
Product type * Product colour * Form factor * Market positioning Intel® vPro™ Platform Eligibility	Hybrid (2-in-1) Grey Convertible (Folder) Business ✓	Front camera Front camera resolution (numeric) Front camera resolution Front camera HD type Video capturing speed	2.07 MP 1920 x 1080 pixels Full HD 30 fps
Display Display diagonal * Display resolution *	35.6 cm (14") 2560 x 1600 pixels	Infrared (IR) camera Privacy camera Privacy type	✓ ✓ Privacy shutter
Touchscreen *	✓ 1000 pixels	Network	
HD type Panel type Display technology marketing name LED backlight Native aspect ratio Anti-reflective coating Anti-smudge coating Display brightness Pixel density RGB colour space Colour gamut Low Blue Light technology Maximum refresh rate	Quad HD+ IPS ComfortView Plus ✓ 16:10 ✓ 500 cd/m² 161 ppi sRGB 100% ✓ 60 Hz	Top Wi-Fi standard * Wi-Fi standards Mobile network connection * Antenna type WLAN controller model WLAN controller manufacturer Bluetooth Ports & interfaces Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port	Wi-Fi 7 (802.11be) 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)
Contrast ratio (typical)	1000:1	Charging port type	USB Type-C
Processor Processor manufacturer * Processor family *	Intel Intel Core Ultra 7	USB Type-C DisplayPort Alternate Mode USB Power Delivery	1
Processor generation	Intel® Core™ Ultra (Series 1)	Performance	
Processor generation Processor model * Processor cores Processor threads Processor boost frequency Performance cores Efficient cores	165U 12 14 4.9 GHz 2	Electronic compass Ambient light sensor Accelerometer Proximity sensor Gyroscope Hall sensor	1 1 1 1

Processor		Keyboard	
Low Power Efficient-cores	2	Pointing device	Touchpad
Performance-core Max Turbo	4.9 GHz	Keyboard language	UK English
Frequency	3.0.CU-	Numeric keypad *	×
Efficient-core Max Turbo Frequency Low Power Efficient-core Max Turbo	3.8 GHz	Keyboard backlit	4
Frequency	2.1 GHz	Spill-resistant keyboard	4
Performance-core base frequency	1.7 GHz	Copilot key	1
Efficient-core base frequency	1.2 GHz	Software	
Low Power Efficient-core Base	700 MHz	Operating system architecture	64-bit
Frequency		Operating system language	German, Dutch, English, French,
Processor cache	12 MB Smart Cache	, , , , ,	Italian
Processor cache type Processor base power	15 W	Trial software	Activate Your Microsoft 365 For A 30 Day Trial
Maximum turbo power	57 W	Operating system installed *	Windows 11 Pro
·		Microsoft Copilot	✓
Neural processor unit (NPU)		Processor special features	
Neural processor unit (NPU)	Intel Al Boost	Intel® Evo™ Platform Verified	1
Maximum frequency NPU	1.4 GHz		•
Sparsity support Windows Studio effects support	1	Brand-specific features	
Al datatype support on NPU	FP16, FP32, Int8	Brand specific technologies	Battery-saving Mini-LED, ExpressSign-In, Intelligent Privacy,
Al software frameworks supported	DirectML, ONNX RT, OpenVINO,	Brana specific technologies	TNR
by NPU	Windows ML	Battery	
Memory		Number of battery cells	3
Internal memory *	32 GB	Battery capacity *	60 Wh
Internal memory type	LPDDR5x-SDRAM	Battery voltage	11.55 V
Memory form factor	On-board	Battery recharge time	3 h
Maximum internal memory *	32 GB	Fast charging	✓
Memory channels	Dual-channel	Battery charge indicator	✓
Memory data transfer rate	7467 MT/s	Battery weight	240 g
Storage		Power	
Jiorage		i owe.	
	1 TB		65 W
Total storage capacity * Storage media *	1 TB SSD	AC adapter power AC adapter frequency	65 W 50 - 60 Hz
Total storage capacity *		AC adapter power	
Total storage capacity * Storage media *	SSD	AC adapter power AC adapter frequency	50 - 60 Hz
Total storage capacity * Storage media * Total SSDs capacity	SSD 1 TB	AC adapter power AC adapter frequency AC adapter input voltage	50 - 60 Hz 100 - 240 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed	SSD 1 TB 1 1 TB TLC	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security	50 - 60 Hz 100 - 240 V 5,9,15,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface	SSD 1 TB 1 1 TB TLC PCI Express 4.0	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot	50 - 60 Hz 100 - 240 V 5,9,15,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security	50 - 60 Hz 100 - 240 V 5,9,15,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type	50 - 60 Hz 100 - 240 V 5,9,15,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm)	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM)	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type *	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	50 - 60 Hz 100 - 240 V 5,9,15,20 V ✓ Wedge ✓ ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model *	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	50 - 60 Hz 100 - 240 V 5,9,15,20 V ✓ Wedge ✓ ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card *	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T)	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge ✓ 2.0 ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T)	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge 4 2.0 4 0 - 35 °C -40 - 65 °C
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card *	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel X	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 V 0 - 35 °C -40 - 65 °C 10 - 90%
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card model * On-board graphics card * On-board graphics card model *	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge ✓ 2.0 ✓ 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95%
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card * On-board graphics card model * Audio	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel X Intel Graphics	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel Intel Graphics MaxxAudio Pro	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel Intel Graphics MaxxAudio Pro 4	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating shock	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel Intel Graphics MaxxAudio Pro 4 Waves	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 V 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer Speaker power	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel MaxxAudio Pro 4 Waves 2 W	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Sustainability	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 V 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G 0.66 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer	SSD 1 TB 1 1 TB TLC PCI Express 4.0 ✓ M.2 2230 (22 x 30 mm) X Not available ✓ Intel Intel Graphics MaxxAudio Pro 4 Waves	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 V 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer Speaker power Built-in microphone	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel MaxxAudio Pro 4 Waves 2 W	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Sustainability Sustainability compliance Sustainability certificates	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 O - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G 0.66 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer Speaker power Built-in microphone	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel MaxxAudio Pro 4 Waves 2 W	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 O - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G 0.66 G V ENERGY STAR, TCO
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer Speaker power Built-in microphone	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel MaxxAudio Pro 4 Waves 2 W	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 V 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G 0.66 G V ENERGY STAR, TCO
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card model * Audio Audio system Number of built-in speakers Speakers manufacturer Speaker power Built-in microphone	SSD 1 TB 1 1 TB TLC PCI Express 4.0 M.2 2230 (22 x 30 mm) Not available Intel MaxxAudio Pro 4 Waves 2 W	AC adapter power AC adapter frequency AC adapter input voltage USB charging voltage Security Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions	50 - 60 Hz 100 - 240 V 5,9,15,20 V Wedge V 2.0 O - 35 °C -40 - 65 °C 10 - 90% 0 - 95% 0 - 3048 m 0 - 10668 m 140 G 0.66 G V ENERGY STAR, TCO

Weight & dimensions		
Height (rear)	1.63 cm	
Weight *	1.54 kg	
Packaging content		
Cables included	AC	



5397184848586

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.