Yealink

Yealink CTP25 meeting room display 25.6 cm (10.1") 1280 x 800 pixels IPS 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) Black Bluetooth

Brand : Yealink

Product code: CTP25

Product name : CTP25

- Simple deployment: plug-and-play, One Cable Solution for console deployment and sharing
- Intuitive touch control
- Teams/Zoom Certified
- Security ensured: support latest Android 13 and beyond, MDEP coming
- Standard PD power supply for PC

10.1" IPS, 1280 x 800, 350 cd/□, Wi-Fi 6, Bluetooth 5.0, 286 x 198 x 140 mm, Android 13.0

Yealink CTP25 meeting room display 25.6 cm (10.1") 1280 x 800 pixels IPS 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) Black Bluetooth:

The Yealink CTP25 is an Android-based touch console for controlling Yealink MeetingBar. With just a few touches on the CTP25, you can start or join a meeting and navigate all meeting controls, including adjusting the camera, changing participant layouts, recording, and more.
Yealink CTP25. Display diagonal: 25.6 cm (10.1"), Display resolution: 1280 x 800 pixels, Display technology: IPS. Housing colour: Black. Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Power source type: PoE, USB, Power consumption (average): 7.3 W, Power consumption (max): 15.2 W. Width: 242.9 mm, Depth: 27.5 mm, Height: 161.9 mm

Display	
Display diagonal *	25.6 cm (10.1")
Display resolution *	1280 x 800 pixels
Display technology *	IPS
Viewing angle	178°
Display brightness	350 cd/m²
Contrast ratio (typical)	1000:1
Touchscreen	✓
Touchscreen technology	Capacitive
Design	
Housing colour *	Black
LED indicators	✓
Camera	
Built-in camera *	✗
Network	
Wi-Fi *	✓
Wi-Fi standards *	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
Bluetooth *	✓
Bluetooth version	5.0
Ethernet LAN *	✓
Ports & interfaces	
USB port	✓

Ports & interfaces	
RJ-45 ports quantity	1
USB Type-C ports quantity	2
USB 2.0 Type-A ports quantity	1
Power	
Power source type	PoE, USB
Power consumption (average)	7.3 W
Power consumption (max)	15.2 W
Weight & dimensions	
Width	242.9 mm
Depth	27.5 mm
Height	161.9 mm
Weight	683 g
Packaging data	
Package width	286 mm
Package depth	140 mm
Package height	198 mm
Package weight	1.58 kg
Operational conditions	
Operating temperature (T-T)	-10 - 45 °C
Storage temperature (T-T)	-30 - 70 °C

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date