

# Opengear CM7116-2-DAC-UK console server RJ-45



**Brand :** Opengear

**Product code:** CM7116-2-DAC-UK

**Product name :** CM7116-2-DAC-UK

Opengear 16 serial Cisco Straight pinout, dual AC, 2 GbE Ethernet, 4GB flash  
 Opengear CM7116-2-DAC-UK. Management protocols: HTTPS, SSH, Nagios NSCA, NRPE, SNMP, TFTP, FTP. Authentication method: PAP/CHAP, RADIUS w/ RSA SecurID & LDAP, Security algorithms: 802.1x RADIUS, FIPS 140-2, HTTPS, IPSEC, SNMP, SSH, SSH-2, SSL/TLS. Console port: RJ-45. Dimensions (WxDxH): 440 x 175 x 45 mm, Weight: 4 kg. Power source type: AC, AC input voltage: 100-240 V, AC input frequency: 50 - 60 Hz

Technical details		Operational conditions	
Rack mounting	✓	Operating temperature (T-T)	5 - 50 °C
MIB support	✓	Storage temperature (T-T)	-30 - 60 °C
Event logging	✓	Operating relative humidity (H-H)	5 - 90%
Management features		Certificates	
Management protocols	HTTPS, SSH, Nagios NSCA, NRPE, SNMP, TFTP, FTP	Certification CE, UL 1950, TUV, C-Tick, RoHS FCC Part 15 Subpart B Class A Radiated Emissions 30MHz - 1000MHz ICES-003 Issue 4 February 2004 Class A Radiated Emissions 30MHz - 1000MHz AS/NZS CISPR 22: 2004 Class A Radiated Emissions 30MHz - 1000MHz EN5502: 1998 + A1: 2000 + A2: 2003 Class A Radiated Emissions 30MHz - 1000MHz EN55024: 1998 +A1: 2001 +A2: 2003 IEC61000-4-2: 1995 ESD 8kV Air Discharge (Direct), 4kV Contact Discharge (Direct/Indirect) IEC61000-4-3: 1995 Radiated Immunity 3.0V/m, 1KHz AM Sine Wave at 80% IEC61000-4-4: 1995 EFT/Burst 1.0kV Power Lines, 0.5kV I/O Lines IEC61000-4-5: 1995 Surge Immunity 1.0kV Common Mode, 1.0 kV Differential Mode IEC61000-4-6: 1996 Conducted Immunity 3.0 Vrms, 80% AM Modulated (1KHz) IEC61000-4-11: 1994 Voltage Dips and Interrupts (>95%,0.5 periods), (30%,25 periods), (>95%,250 periods)	
Security			
Authentication method	PAP/CHAP, RADIUS w/ RSA SecurID & LDAP		
Security algorithms	802.1x RADIUS, FIPS 140-2, HTTPS, IPSEC, SNMP, SSH, SSH-2, SSL/TLS		
IP address filtering	✓		
Ports & interfaces			
Console port	RJ-45		
Serial ports quantity	16		
USB 2.0 ports quantity	2		
Ethernet LAN (RJ-45) ports	2		
Weight & dimensions			
Dimensions (WxDxH)	440 x 175 x 45 mm		
Weight	4 kg		
Power			
Power source type	AC		
AC input voltage	100-240 V		
AC input frequency	50 - 60 Hz		
Power consumption (typical)	20 W		
Number of power supply units	2		
		Memory	
		Internal memory	256 MB
		Flash memory	4000 MB



0843295100624



843295100624

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.