


Display		Operational conditions	
Sync-on-green (SOG)	✓	Operating relative humidity (H-H)	20 - 80%
Display diagonal (metric)	57.2 cm	Operating altitude	0 - 3658 m
DDC/CI	✓	Non-operating altitude	0 - 12192 m
Haze rate	25%	Weight & dimensions	
Surface hardness	3H	Width (with stand)	499 mm
Colour gamut standard	sRGB	Depth (with stand)	216 mm
Colour gamut	85%	Height (with stand)	512 mm
sRGB coverage (typical)	101.8%	Weight (with stand)	4.3 kg
NTSC coverage (typical)	85%	Width (without stand)	499 mm
Display sRGB	✓	Depth (without stand)	56 mm
Performance		Height (without stand)	323 mm
VESA Adaptive Sync support	✓	Weight (without stand)	2.7 kg
Component video sync	Separate sync, Sync-on-green (SOG)	Packaging data	
Flicker-free technology	✓	Package width	565 mm
Low Blue Light technology	✓	Package depth	161 mm
Multimedia		Package height	519 mm
Number of speakers	2	Package weight	6.25 kg
RMS rated power	2 W	Packaging content	
Built-in speaker(s) *	✓	Stand included	✓
Built-in camera *	✗	Cables included	VGA, DVI, HDMI, DisplayPort, AC
Design		Manual	✓
Market positioning *	Home	Bundled software	SmartControl
Product colour *	Black	Sustainability	
Front bezel colour	Black	Sustainability certificates	ENERGY STAR, TCO
Feet colour	Black	Doesn't contain	PVC/BFR, Mercury
Ports & interfaces		Other features	
VGA (D-Sub) ports quantity	1	Exterior finish type	Textured
DVI port	✓	Recommended resolution	1920 x 1200 @ 60 Hz
DVI-D ports quantity	1	Picture enhancement	SmartImage
HDMI *	✓	Recyclable packaging material	100%
HDMI ports quantity	1.4	Regulatory Approvals	CE Mark; FCC Class B; EPA; UKRAINIAN; ICES-003; TUV Ergo; TUV/GS; CU-EAC
HDMI version	1.4	Heavy metals free	Hg (mercury)
DisplayPorts quantity	1.2	EasyRead mode	✓
DisplayPort version	1.2	LowBlue mode	✓
Headphone out *	✓	Compliance certificates	WEEE, RoHS
PC Audio in	✓	Mean time between failures (MTBF)	70000 h
Ergonomics		Certification	CE Mark, FCC Class B, EPA, UKRAINIAN, ICES-003, TUV Ergo, TUV/GS, CU-EAC
VESA mounting *	✓	Recycling data	
Panel mounting interface	100 x 100 mm	Total amount of recyclable materials	85%
Cable lock slot *	✓	Total amount of recycled materials used for making	85%
Cable lock slot type	Kensington	Logistics data	
Height adjustment *	✓	Harmonized System (HS) code	85285210
Height adjustment	13 cm		
Pivot	✓		



8712581762810

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date