

GIGABYTE UD850GM power supply unit 850 W 20+4 pin ATX ATX Black

Brand : GIGABYTE

Product code: GP-UD850GM

Product name : UD850GM

- Ultra Durable
- Main Japanese capacitors
- Enhanced thermal solution
- 120mm smart hydraulic bearing (HYB) fan
- OVP/OPP/SCP/UV/OC/OTP protection
- 80 PLUS Gold certified
- Fully modular design
- Powerful single +12V rail
- Compact design

850W, ATX, 80 PLUS Gold, ATX 12V v2.31

GIGABYTE UD850GM. Total power: 850 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, CPU power cable length: 60 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm



Power		Ports & interfaces	
Total power *	850 W	PCI Express power connectors (6+2 pin)	4
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	60 cm
Maximum input current (@110V)	12 A	ATX power connector (20+4 pin)	✓
Maximum input current (@220V)	6 A	Floppy drive power connector	2
Power factor	0.9	Floppy disk drive connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	105 W	Performance	
Combined power (+12V)	849.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	120 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	15 W	ATX version	2.31
Max output current (+3.3V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V)	70.8 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	3 A	Fan diameter	12 cm
Hold time	16 ms	Number of fans	1 fan(s)
Efficiency	90%	Fan location	Top
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	On/off switch	✓
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Motherboard power cable length	61 cm	Depth	140 mm
Number of SATA power connectors	8	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	3	Packaging data	
		Package type	Box
		Logistics data	
		Harmonized System (HS) code	84733020



4719331552541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date