

GIGABYTE GP-UD750GM power supply unit 750 W 20+4 pin ATX ATX Black

Brand : GIGABYTE


Product code: GP-UD750GM

Product name : GP-UD750GM

- 80 PLUS Gold certified
- Fully modular design
- Powerful single +12V rail
- Compact design

Active PFC, 100-240 Vac, 12-6A, 60-50 Hz, 750W, 120mm Hydraulic Bearing(HYB)fan, 80 PLUS Gold, OVP/OPP/SCP/UV/OC/OTP

GIGABYTE GP-UD750GM. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,300,450,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA



| Power | | Ports & interfaces | |
|---|---|---------------------------------------|-------------------------------------|
| Total power * | 750 W | PCI Express power cable length | 60 cm |
| AC input voltage * | 100 - 240 V | CPU power connector (4+4 pin) | ✓ |
| AC input frequency | 50 - 60 Hz | CPU power cable length | 60 cm |
| Input current | 12 A | ATX power connector (20+4 pin) | ✓ |
| Power Factor Correction (PFC) type | Active | Floppy drive power connector | 1 |
| Combined power (+3.3V) | 105 W | Floppy disk drive connector | ✓ |
| Combined power (+12V) | 732 W | Floppy disk drive cable length | 15 cm |
| Combined power (+5V) | 105 W | Cabling type | Fully-Modular |
| Combined power (-12V) | 3.6 W | Performance | |
| Combined power (+5Vsb) | 15 W | 80 PLUS certification * | 80 PLUS Gold |
| Max output current (+3.3V) | 20 A | Purpose * | PC |
| Max output current (+12V) | 61 A | Power supply unit (PSU) form factor * | ATX |
| Max output current (+5V) | 20 A | ATX version | 2.31 |
| Max output current (-12V) | 2.3 A | Bearing technology | HYB |
| Max output current (+5Vsb) | 3 A | Mean time between failures (MTBF) | 100000 h |
| Hold time | 16 ms | Design | |
| Efficiency | 90% | Product colour | Black |
| Power protection features | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | Cooling type | Active |
| Ports & interfaces | | Fan diameter | 12 cm |
| Motherboard power connector * | 20+4 pin ATX | Number of fans | 1 fan(s) |
| Motherboard power cable length | 61 cm | Fan location | Top |
| Number of SATA power connectors | 8 | On/off switch | ✓ |
| SATA power cable length | 150,300,450,600 mm | Packaging content | |
| Peripheral (Molex) power connectors (4-pin) * | 3 | Cables included | CPU, PCIe, Peripheral (Molex), SATA |
| Peripheral (Molex) power cable length | 120,500 mm | Weight & dimensions | |
| EPS power connector (4+4 pin) | ✓ | Width | 150 mm |
| PCI Express power connectors (6+2 pin) | 4 | Depth | 140 mm |
| | | Height | 86 mm |
| Logistics data | | Harmonized System (HS) code | 84733020 |



4719331552671

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2024. Prints or copies of Information are only valid on the printed Publication date