



TP-Link EAP211-BRIDGE KIT bridge/repeater Network bridge 867 Mbit/s White

Brand : TP-Link

Product code: EAP211-BRIDGE KIT

Product name : EAP211-BRIDGE KIT

- 802.11ac for up to 867 Mbps on the 5 GHz wireless data rate.*1
 - Ideal for long-range wireless transmission up to 1 km.*2
 - Auto-pairing and agile LEDs for efficient deployment
 - 3x Gigabit Ethernet ports for more high-speed IP camera connections
 - Supports Omada SDN for remote and centralized management
 - IP65 weatherproof enclosure and 6kV lightning protection ensure all-weather suitability.*3
 - Supports Passive PoE for flexible deployment (adapter included)
- 3x Gigabit Ethernet Ports, 12V DC / 24V Passive PoE, IP65, 1000m, IEEE 802.11 a/b/g/n/ac, 5 GHz: Up to 867 Mbps



| Data transmission | | Features | |
|-------------------------------|---|------------------------------------|---------------|
| Maximum data transfer rate * | 867 Mbit/s | Product colour | White |
| Maximum transfer distance | 1000 m | LED indicators | Power |
| Antenna | | Reset button | ✓ |
| Antenna design | Internal | International Protection (IP) code | IP65 |
| Antenna type | 2x2 | Power | |
| Antenna gain level (max) | 7 dBi | Power source type | DC, PoE |
| Wireless LAN features | | DC input voltage | 12 V |
| Wi-Fi | ✓ | Power over Ethernet (PoE) | ✓ |
| Top Wi-Fi standard | Wi-Fi 5 (802.11ac) | Power over Ethernet (PoE) voltage | 24 V |
| WLAN data transfer rate (max) | 867 Mbit/s | Operational conditions | |
| Frequency band | 5 GHz | Operating temperature (T-T) | -40 - 70 °C |
| Network | | Operating relative humidity (H-H) | 10 - 90% |
| Ethernet LAN | ✓ | Storage temperature (T-T) | -40 - 70 °C |
| Ethernet LAN interface type | Gigabit Ethernet | Storage relative humidity (H-H) | 5 - 90% |
| Networking standards | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n | Certificates | |
| Cabling technology | 10/100/1000Base-T(X) | Certification | CE, FCC, RoHS |
| Ports & interfaces | | Weight & dimensions | |
| Ethernet LAN (RJ-45) ports | 3 | Width | 224 mm |
| Management features | | Depth | 79 mm |
| Web-based management | ✓ | Height | 60 mm |
| Features | | | |
| Product type * | Network bridge | | |
| Mounting type | Pole | | |



4895252502541



0840030709142



840030709142



8885020627053

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.