

# Statement of Volatility – Dell U2424H Monitor

**⚠ CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell U2424H Monitor contains both volatile and non-volatile components. Volatile components lose their data immediately after power is removed from the component. Non-volatile components continue to retain their data even after power is removed from the component. The following Non-volatile components are present on the U2424H Monitor system board.

**Table 1.** List of Non-Volatile Components on System Board

Description	Reference Designator	Volatility Description	User Accessible for external data	Remedial Action (action necessary to erase data)
System EEPROM	U901	Non-Volatile memory, 32 KB For Storage of system setting (OSD)	No	NA
HDMI EDID EEPROM	U6	Non-Volatile memory, 2 KB For Storage of HDMI EDID	No	NA
System Flash	U902	Non-Volatile memory, 32 MB For Storage of system firmware	No	NA
USB HUB Flash	U21	Non-Volatile memory, 4 MB For Storage of USB HUB firmware	No	NA

**⚠ CAUTION:** All other components on the system board lose data if power is removed from the system. Primary power loss (unplugging the power cord and removing the battery) destroys all user data on the memory (DDR4, 2667 MHz). Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.